

Axima EWX R2

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28
EWX-680/05-B in m3/h	33.1	46.6	53.8	27.9	44.3	37.8	53.3	61.5	31.9	50.8	43.4	61.2	70.7	36.7	58.5	47.7	67.3	77.8	40.4	64.4	55.2	77.9	90.1	46.8	74.7
EWX-680/08-A in m3/h	56.4	79.5	91.7	47.6	75.6	64.4	90.8	104.9	54.4	86.6	73.9	104.3	120.5	62.6	99.6	81.3	114.7	132.6	68.9	109.8	94.0	132.8	153.5	79.8	127.3
EWX-1260/05-A in m3/h	66.6	93.8	108.2	56.2	89.2	76.0	107.1	123.8	64.2	102.1	87.2	123.1	142.2	73.8	117.6	95.9	135.4	156.5	81.3	129.5	111.0	156.7	181.1	94.2	150.2
EWX-1800/05-B in m3/h	99.7	140.4	162.0	84.1	133.5	113.8	160.4	185.3	96.2	152.9	130.6	184.3	212.9	110.6	176.0	143.6	202.7	234.2	121.7	193.9	166.1	234.6	271.2	141.0	224.9
EWX-1800/08-A in m3/h	122.2	172.2	198.7	103.2	163.7	139.5	196.7	227.2	117.9	187.5	160.1	226.0	261.2	135.6	215.9	176.1	248.5	287.3	149.3	237.8	203.7	287.7	332.6	172.9	275.8
EWX-2100/05-A in m3/h	142.9	201.3	232.4	120.6	191.4	163.1	230.0	265.7	137.9	219.3	187.3	264.2	305.4	158.5	252.4	205.9	290.6	335.9	174.5	278.0	238.2	336.4	388.9	202.2	322.5
EWX-3100/05-A in m3/h	177.9	250.6	289.2	150.2	238.2	203.0	286.3	330.7	171.7	272.9	233.1	328.9	380.1	197.3	314.2	256.3	361.7	418.1	217.2	346.1	296.5	418.7	484.1	251.7	401.4
EWX-3100/08-B in m3/h	213.6	300.9	347.3	180.3	286.1	243.8	343.8	397.1	206.1	327.8	279.9	394.9	456.4	237.0	377.3	307.7	434.4	502.1	260.8	415.6	356.1	502.8	581.3	302.3	482.1
EWX-4500/05-A in m3/h	214.4	301.9	348.5	180.9	287.1	244.7	345.0	398.5	206.9	328.9	280.9	396.3	458.0	237.8	378.6	308.8	435.9	503.8	261.8	417.1	357.3	504.6	583.4	303.3	483.7
EWX-4500/05-B in m3/h	252.0	354.9	409.7	212.7	337.5	287.6	405.5	468.5	243.2	386.6	330.2	465.8	538.4	279.5	445.1	363.0	512.4	592.2	307.7	490.2	420.0	593.1	685.7	356.5	568.6
EWX-4500/08-A in m3/h	270.8	381.4	440.3	228.6	362.6	309.1	435.8	503.4	261.3	415.5	354.8	500.6	578.6	300.4	478.3	390.1	550.6	636.4	330.7	526.8	451.3	637.3	736.9	383.1	611.0
EWX-4500/08-B in m3/h	304.7	429.1	495.3	257.1	408.0	347.7	490.3	566.3	294.0	467.4	399.1	563.2	650.9	337.9	538.1	438.9	619.5	716.0	372.0	592.7	507.8	717.0	829.0	431.0	687.4

Axima EWX R2

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	24	24	27	27	27	27	27	29	29	29	29	29	32.2	32.2	32.2	32.2	32.2	21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	5	5.56	5	5
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.2	44.2	45.2	44.2	47.2	32	35.00	37	37
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.2	38.2	39.2	36.2	39.2	27	29.44	32	32
EWX-680/05-B in m3/h	64.1	90.5	104.7	54.5	87.0	74.7	105.6	122.1	63.6	101.6	83.0	117.2	135.5	70.7	112.9	98.3	138.9	160.7	84.0	134.2	88.3	70.9	101.0	88
EWX-680/08-A in m3/h	109.2	154.3	178.4	92.9	148.2	127.4	179.9	208.1	108.5	173.2	141.4	199.7	231.0	120.6	192.5	167.6	236.7	273.9	143.2	228.7	150.4	120.9	172.2	150
EWX-1260/05-A in m3/h	128.9	182.1	210.6	109.6	174.9	150.3	212.3	245.6	128.0	204.4	166.9	235.7	272.6	142.3	227.2	197.8	279.4	323.2	168.9	269.8	177.5	142.6	203.2	177
EWX-1800/05-B in m3/h	193.0	272.6	315.2	164.1	261.9	225.1	317.9	367.7	191.6	306.0	249.8	352.8	408.1	213.0	340.1	296.2	418.2	483.9	252.9	404.0	265.8	213.5	304.2	265
EWX-1800/08-A in m3/h	236.7	334.3	386.6	201.2	321.2	276.0	389.9	450.9	235.0	375.3	306.4	432.7	500.6	261.2	417.1	363.2	512.9	593.4	310.2	495.5	325.9	261.9	373.1	325
EWX-2100/05-A in m3/h	276.7	390.9	452.0	235.3	375.5	322.7	455.8	527.2	274.8	438.8	358.2	506.0	585.3	305.4	487.7	424.7	599.8	693.9	362.7	579.3	381.1	306.2	436.3	380
EWX-3100/05-A in m3/h	344.5	486.5	562.7	292.9	467.4	401.7	567.4	656.3	342.1	546.1	445.9	629.8	728.5	380.1	607.0	528.6	746.5	863.7	451.4	721.1	474.4	381.1	543.1	473
EWX-3100/08-B in m3/h	413.6	584.2	675.7	351.7	561.3	482.4	681.3	788.1	410.8	655.8	535.5	756.3	874.8	456.5	728.9	634.8	896.5	1037.1	542.1	866.0	569.6	457.7	652.1	568
EWX-4500/05-A in m3/h	415.1	586.3	678.0	352.9	563.3	484.1	683.7	790.9	412.2	658.2	537.3	758.9	877.9	458.1	731.5	637.0	899.6	1040.8	544.0	869.0	571.6	459.3	654.4	570
EWX-4500/05-B in m3/h	487.9	689.2	797.0	414.8	662.1	569.0	803.7	929.6	484.5	773.6	631.6	892.1	1031.9	538.5	859.8	748.8	1057.5	1223.4	639.5	1021.5	671.9	539.8	769.2	670
EWX-4500/08-A in m3/h	524.3	740.6	856.5	445.8	711.5	611.5	863.7	999.0	520.7	831.3	678.8	958.6	1108.9	578.6	924.0	804.6	1136.4	1314.7	687.2	1097.7	722.1	580.1	826.6	720
EWX-4500/08-B in m3/h	589.9	833.2	963.5	501.5	800.4	687.9	971.6	1123.9	585.8	935.3	763.6	1078.5	1247.5	651.0	1039.5	905.2	1278.4	1479.0	773.1	1234.9	812.3	652.6	930.0	810