

Nihon Spindle Manufacturing Company, Ltd.
CTA-KX Series of CTI Certified Cooling Towers
CTI Certification Validation Number 08-33-01
May 26, 2008 (Revision 0)

<u>STANDARD MODEL SERIES</u>		<u>ENTIRE MODEL SERIES</u>		<u>N MODEL SERIES</u>	
<u>CTA-KX3</u>	<u>CTA-KX30</u>	<u>CTA-KX3</u>	<u>CTA-KX30</u>	<u>CTA-KX3-N</u>	<u>CTA-KX30-N</u>
CTA-200KX3	CTA-200KX30	CTA-200KX3L CTA-225KX3M	CTA-200KX30L CTA-225KX30M	CTA-300KX3-N	CTA-300KX30-N
CTA-250KX3E	CTA-250KX30E	CTA-250KX3S	CTA-250KX30S	CTA-350KX3E-N	CTA-350KX30E-N
CTA-250KX3	CTA-250KX30	CTA-250KX3L CTA-290KX3M	CTA-250KX30L CTA-290KX30M	CTA-350KX3-N	CTA-350KX30-N
CTA-310KX3E	CTA-310KX30E	CTA-310KX3S	CTA-310KX30S	CTA-450KX3E-N	CTA-450KX30E-N
CTA-300KX3	CTA-300KX30	CTA-300KX3L CTA-335KX3M	CTA-300KX30L CTA-335KX30M	CTA-450KX3-N	CTA-450KX30-N
CTA-370KX3E	CTA-370KX30E	CTA-370KX3S	CTA-370KX30S	CTA-550KX3E-N	CTA-550KX30E-N
CTA-350KX3	CTA-350KX30	CTA-350KX3L CTA-390KX3M	CTA-350KX30L CTA-390KX30M	CTA-500KX3-N	CTA-500KX30-N
CTA-415KX3E	CTA-415KX30E	CTA-415KX3S	CTA-415KX30S	CTA-600KX3E-N	CTA-605KX30E-N
CTA-400KX3	CTA-400KX30	CTA-400KX3L CTA-450KX3M	CTA-400KX30L CTA-450KX30M	CTA-600KX3-N	CTA-600KX30-N
CTA-475KX3E	CTA-475KX30E	CTA-475KX3S	CTA-475KX30S	CTA-700KX3E-N	CTA-700KX30E-N
CTA-450KX3	CTA-450KX30	CTA-450KX3L	CTA-450KX30L	CTA-650KX3-N	CTA-650KX30-N
CTA-500KX3E	CTA-500KX30E	CTA-500KX3M	CTA-500KX30M	CTA-750KX3E-N	CTA-750KX30E-N

Footnotes:

1. Standard Model Series are 1.00 m³/h/RT @ 37°C-32°C-28°C for distribution in Japanese market.
Entire Model Series are 1.00 m³/h/RT @ 37°C-32°C-28°C for distribution in markets except Japan.
N Model Series are 0.78 m³/h/RT @ 37°C-32°C-27°C for distribution in markets except Japan.
2. CTA-KX3 Models include an integral cold water basin.
CTA-KX30 Models do not include an integral cold water basin.
3. Multiple cell models of the single cell models above are also available but not listed.