

Elendoo EL R2

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	21	21	21	21	21	24	24
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36	34	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28	28	30
EL-1205A-NA in m ³ /h	28.6	40.3	46.5	24.1	38.3	32.6	46.0	53.1	27.6	43.9	37.5	52.8	61.1	31.7	50.5	41.2	58.1	67.2	34.9	55.6	47.6	67.3	77.8	40.4	64.5	55.3	78.2
EL-1205A-NB in m ³ /h	32.3	45.6	52.6	27.3	43.3	36.9	52.1	60.1	31.2	49.6	42.4	59.8	69.1	35.9	57.1	46.6	65.8	76.0	39.5	62.9	53.9	76.1	88.0	45.8	73.0	62.6	88.5
EL-1205A-NC in m ³ /h	36.5	51.4	59.3	30.8	48.9	41.6	58.7	67.8	35.2	56.0	47.8	67.4	77.9	40.5	64.4	52.6	74.2	85.7	44.5	71.0	60.8	85.9	99.3	51.6	82.3	70.6	99.8
EL-1205A-ND in m ³ /h	41.4	58.3	67.3	34.9	55.4	47.2	66.6	76.9	39.9	63.5	54.2	76.5	88.4	45.9	73.1	59.6	84.1	97.2	50.5	80.5	69.0	97.4	112.6	58.5	93.4	80.1	113.1
EL-1405A-NA in m ³ /h	63.6	89.5	103.3	53.6	85.1	72.5	102.3	118.2	61.3	97.5	83.3	117.5	135.8	70.5	112.3	91.6	129.2	149.4	77.6	123.7	105.9	149.6	173.0	89.9	143.4	123.1	173.8
EL-1405A-NB in m ³ /h	71.8	101.2	116.8	60.6	96.2	82.0	115.6	133.5	69.3	110.2	94.1	132.8	153.5	79.7	126.9	103.5	146.1	168.8	87.7	139.8	119.7	169.1	195.5	101.6	162.1	139.1	196.5
EL-1405A-NC in m ³ /h	79.7	112.3	129.6	67.3	106.8	91.0	128.3	148.2	76.9	122.3	104.5	147.4	170.4	88.5	140.8	114.9	162.1	187.4	97.4	155.1	132.9	187.7	217.0	112.8	179.9	154.4	218.1
EL-1405A-ND in m ³ /h	85.8	120.8	139.4	72.4	114.8	97.9	138.0	159.4	82.7	131.6	112.4	158.5	183.2	95.1	151.5	123.5	174.4	201.5	104.7	166.8	142.9	201.8	233.3	121.3	193.5	166.0	234.5
EL-1707A-NA in m ³ /h	70.0	98.5	113.7	59.0	93.7	79.8	112.6	130.1	67.5	107.3	91.7	129.3	149.5	77.6	123.6	100.8	142.2	164.4	85.4	136.1	116.6	164.6	190.4	99.0	157.9	135.5	191.3
EL-1707A-NB in m ³ /h	79.4	111.8	129.0	67.0	106.3	90.6	127.7	147.5	76.6	121.8	104.0	146.7	169.6	88.0	140.2	114.3	161.4	186.5	96.9	154.4	132.3	186.8	215.9	112.3	179.1	153.7	217.0
EL-1707A-NC in m ³ /h	88.0	124.0	143.1	74.3	117.9	100.5	141.6	163.6	84.9	135.0	115.3	162.7	188.0	97.6	155.4	126.8	179.0	206.8	107.5	171.2	146.7	207.1	239.5	124.5	198.6	170.4	240.7
EL-1707A-ND in m ³ /h	97.0	136.7	157.8	81.9	129.9	110.8	156.2	180.4	93.6	148.9	127.1	179.4	207.3	107.6	171.4	139.8	197.3	228.1	118.5	188.8	161.7	228.4	264.0	137.3	219.0	187.9	265.4
EL-1707A-NE in m ³ /h	101.2	142.5	164.5	85.4	135.5	115.5	162.8	188.1	97.6	155.2	132.6	187.0	216.2	112.2	178.7	145.7	205.7	237.8	123.5	196.8	168.6	238.1	275.3	143.1	228.3	195.9	276.7
EL-3022A-NA in m ³ /h	105.3	148.3	171.2	88.9	141.0	120.2	169.5	195.8	101.6	161.6	138.0	194.7	225.0	116.8	186.0	151.7	214.1	247.5	128.6	204.9	175.5	247.9	286.6	149.0	237.6	203.9	288.0
EL-3022A-NB in m ³ /h	119.2	167.9	193.8	100.6	159.7	136.1	191.9	221.6	115.0	182.9	156.2	220.4	254.7	132.3	210.6	171.7	242.4	280.2	145.6	231.9	198.7	280.6	324.4	168.7	269.0	230.9	326.1
EL-3022A-NC in m ³ /h	131.6	185.4	214.0	111.1	176.3	150.2	211.8	244.7	127.0	202.0	172.5	243.4	281.2	146.0	232.5	189.6	267.7	309.4	160.7	256.1	219.4	309.8	358.2	186.3	297.0	254.9	360.0
EL-3022A-ND in m ³ /h	152.3	214.5	247.6	128.6	204.0	173.9	245.1	283.2	147.0	233.7	199.6	281.6	325.4	169.0	269.0	219.4	309.7	358.0	186.0	296.3	253.9	358.5	414.5	215.5	343.7	294.9	416.6
EL-3022A-NE in m ³ /h	161.4	227.3	262.3	136.2	216.1	184.2	259.7	300.0	155.7	247.5	211.4	298.3	344.7	179.0	285.0	232.4	328.1	379.2	197.0	313.9	268.9	379.7	439.0	228.3	364.1	312.4	441.3

Elendoo EL R2

Condition Reference #	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	27	27	27	27	27	29	29	29	29	29	32.2	32.2	32.2	32.2	32.2	21	25.56	27	28
Range °C	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	5	5.56	5	5
Approach °C	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4
Inlet Water Temperature °C	37	36	39	37	39	40	39	42	39	41	42	41	44	42.2	44.2	45.2	44.2	47.2	32	35.00	37	37
Outlet Water Temperature °C	31	28	31	31	33	34	31	34	33	35	36	33	36	36.2	38.2	39.2	36.2	39.2	27	29.44	32	32
EL-1205A-NA in m ³ /h	90.4	47.1	75.1	64.5	91.2	105.4	55.0	87.8	71.6	101.2	117.1	61.1	97.5	84.9	120.0	138.8	72.5	115.9	76.2	61.2	87.3	76.0
EL-1205A-NB in m ³ /h	102.3	53.2	85.0	73.0	103.2	119.3	62.2	99.3	81.1	114.5	132.5	69.1	110.4	96.1	135.7	157.0	82.1	131.1	86.2	69.3	98.7	86.0
EL-1205A-NC in m ³ /h	115.4	60.1	95.9	82.4	116.4	134.6	70.1	112.0	91.4	129.2	149.4	78.0	124.5	108.4	153.1	177.1	92.6	147.9	97.3	78.2	111.4	97.0
EL-1205A-ND in m ³ /h	130.9	68.1	108.7	93.4	131.9	152.6	79.6	127.0	103.7	146.5	169.4	88.4	141.2	122.9	173.6	200.9	105.0	167.7	110.3	88.6	126.3	110.0
EL-1405A-NA in m ³ /h	201.0	104.6	167.0	143.5	202.7	234.5	122.2	195.1	159.3	225.0	260.3	135.8	216.9	188.9	266.7	308.6	161.3	257.7	169.5	136.2	194.0	169.0
EL-1405A-NB in m ³ /h	227.2	118.3	188.7	162.2	229.1	265.0	138.1	220.5	180.1	254.3	294.2	153.5	245.1	213.5	301.5	348.8	182.3	291.2	191.5	153.9	219.3	191.0
EL-1405A-NC in m ³ /h	252.2	131.3	209.5	180.0	254.3	294.1	153.3	244.8	199.9	282.3	326.5	170.4	272.1	236.9	334.6	387.1	202.3	323.2	212.6	170.8	243.4	212.0
EL-1405A-ND in m ³ /h	271.2	141.2	225.3	193.6	273.5	316.3	164.9	263.3	214.9	303.6	351.2	183.2	292.6	254.8	359.9	416.3	217.6	347.6	228.7	183.7	261.8	228.0
EL-1707A-NA in m ³ /h	221.3	115.2	183.8	158.0	223.1	258.1	134.5	214.8	175.3	247.7	286.5	149.5	238.7	207.9	293.6	339.6	177.5	283.6	186.5	149.9	213.5	186.0
EL-1707A-NB in m ³ /h	251.0	130.6	208.5	179.2	253.1	292.8	152.6	243.6	198.9	280.9	325.0	169.6	270.8	235.8	333.0	385.3	201.4	321.7	211.6	170.0	242.3	211.0
EL-1707A-NC in m ³ /h	278.4	144.9	231.2	198.7	280.7	324.7	169.2	270.2	220.6	311.6	360.4	188.1	300.3	261.5	369.3	427.3	223.3	356.7	234.7	188.5	268.7	234.0
EL-1707A-ND in m ³ /h	306.9	159.7	254.9	219.1	309.5	358.0	186.6	297.9	243.2	343.5	397.4	207.3	331.1	288.3	407.2	471.1	246.2	393.3	258.7	207.9	296.2	258.0
EL-1707A-NE in m ³ /h	320.0	166.6	265.8	228.4	322.7	373.2	194.5	310.6	253.6	358.2	414.3	216.2	345.2	300.6	424.6	491.2	256.7	410.1	269.8	216.7	308.8	269.0
EL-3022A-NA in m ³ /h	333.1	173.4	276.7	237.8	335.9	388.5	202.5	323.3	264.0	372.8	431.3	225.0	359.3	312.9	441.9	511.3	267.2	426.9	280.8	225.6	321.5	280.0
EL-3022A-NB in m ³ /h	377.1	196.3	313.3	269.2	380.3	439.8	229.3	366.0	298.8	422.1	488.2	254.8	406.8	354.3	500.3	578.8	302.6	483.3	317.9	255.4	363.9	317.0
EL-3022A-NC in m ³ /h	416.3	216.7	345.9	297.2	419.8	485.6	253.1	404.1	329.9	466.0	539.1	281.3	449.2	391.1	552.4	639.1	334.0	533.6	351.0	282.0	401.8	350.0
EL-3022A-ND in m ³ /h	481.8	250.8	400.2	343.9	485.8	561.9	292.9	467.6	381.8	539.2	623.8	325.5	519.8	452.6	639.2	739.5	386.5	617.5	406.2	326.3	465.0	405.0
EL-3022A-NE in m ³ /h	510.3	265.6	423.9	364.3	514.6	595.2	310.2	495.3	404.4	571.2	660.7	344.8	550.6	479.4	677.1	783.3	409.4	654.0	430.2	345.7	492.5	429.0