

Evapco, Inc.
L Series Line of CTI Certified Cooling Towers
CTI Certification Validation Number 05-13-03
May 15, 2009(Revision 1)

L Series – LSTB Models

LSTB 5112	LSTB 8P112	LSTB 8P124	LSTB 10112	LSTB 10124
LSTB 5212	LSTB 8P212	LSTB 8P224	LSTB 10212	LSTB 10224
LSTB 5312	LSTB 8P312	LSTB 8P324	LSTB 10312	LSTB 10324
LSTB 5412	LSTB 8P412	LSTB 8P424	LSTB 10412	LSTB 10424
LSTB 5512	LSTB 8P512	LSTB 8P524	LSTB 10512	LSTB 10524
			LSTB 10612	
LSTB 5118	LSTB 8P118	LSTB 8P136	LSTB 10118	LSTB 10136
LSTB 5218	LSTB 8P218	LSTB 8P236	LSTB 10218	LSTB 10236
LSTB 5318	LSTB 8P318	LSTB 8P336	LSTB 10318	LSTB 10336
LSTB 5418	LSTB 8P418	LSTB 8P436	LSTB 10418	LSTB 10436
LSTB 5518	LSTB 8P518	LSTB 8P536	LSTB 10518	LSTB 10536
LSTB 5618	LSTB 8P618		LSTB 10618	LSTB 10636
LSTB 5718			LSTB 10718	

See Footnotes for Additional Information

L Series – LPT Models

LPT 316	LPT 516	LPT 519	LPT 5112	LPT 819	LPT 8112
LPT 326	LPT 526	LPT 529	LPT 5212	LPT 829	LPT 8212
LPT 336	LPT 536	LPT 539	LPT 5312	LPT 839	LPT 8312
LPT 346	LPT 546	LPT 549	LPT 5412	LPT 849	LPT 8412
LPT 356	LPT 556	LPT 559	LPT 5512	LPT 859	LPT 8512
LPT 366	LPT 566	LPT 569	LPT 5612	LPT 869	LPT 8612
	LPT 576		LPT 5712	LPT 879	LPT 8712
	LPT 586				LPT 8812
	LPT 596				

See Footnotes for Additional Information

Evapco, Inc.
L Series Line of CTI Certified Cooling Towers
CTI Certification Validation Number 05-13-03
May 15, 2009(Revision 1)

Footnotes:

1. The following suffixes (I, D, H, F, L, U, LI, LD, LH and LF) are to be added to the basic numeric model designations listed above to indicate the tower configuration options that are also included in the CTI Certification.
 - I = Intake sound attenuation
 - D = Discharge sound attenuation
 - H = Tapered Discharge Hood
 - F = Full sound attenuation
 - L = One motor size smaller
 - U = Two motor sizes smaller
 - LI = Intake sound attenuation + One motor size smaller
 - LD = Discharge sound attenuation + One motor size smaller
 - LH = Tapered Discharge Hood + One motor size smaller
 - LF = Full sound attenuation + One motor size smaller

2. The optional tower configurations are unique in capacity. Selection software should be consulted for appropriate ratings of the tower configuration.