

## KIMCO Cooling Tower - EnduraCool Line

STD-201RS Table 3b - SI Units - Cooling Towers (CT) - l/s

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28
<b>Model</b>	<b>Water Flow, l/s</b>																								
EX-80Klb & EC-65	5.68	8.00	9.23	4.79	7.60	6.48	9.14	10.56	5.48	8.71	7.44	10.50	12.13	6.30	10.03	8.18	11.55	13.35	6.93	11.05	9.46	13.36	15.45	8.03	12.81
EX-100Klb & EC-80	7.10	10.00	11.54	5.99	9.51	8.10	11.42	13.19	6.85	10.89	9.30	13.12	15.16	7.87	12.54	10.22	14.43	16.68	8.67	13.81	11.83	16.70	19.31	10.04	16.02
EX-125Klb & EC-100	8.87	12.49	14.42	7.49	11.88	10.13	14.28	16.49	8.56	13.61	11.62	16.40	18.96	9.84	15.67	12.78	18.04	20.85	10.83	17.26	14.79	20.88	24.14	12.55	20.02
EX-150Klb & EC-120	10.65	14.99	17.31	8.99	14.26	12.15	17.13	19.79	10.27	16.33	13.95	19.68	22.75	11.81	18.81	15.34	21.65	25.02	13.00	20.71	17.74	25.06	28.97	15.06	24.02
EX-175Klb & EC-140	12.42	17.49	20.19	10.48	16.63	14.18	19.99	23.09	11.99	19.06	16.27	22.96	26.54	13.78	21.94	17.89	25.25	29.19	15.17	24.16	20.70	29.23	33.80	17.57	28.03
EX-200Klb & EC-160	14.20	19.99	23.08	11.98	19.01	16.20	22.85	26.39	13.70	21.78	18.60	26.24	30.33	15.75	25.07	20.45	28.86	33.36	17.33	27.62	23.66	33.41	38.63	20.08	32.03
EX-225Klb & EC-180	15.97	22.49	25.96	13.48	21.39	18.23	25.70	29.69	15.41	24.50	20.92	29.52	34.12	17.72	28.21	23.00	32.47	37.53	19.50	31.07	26.62	37.58	43.46	22.60	36.04
EX-250Klb & EC-200	17.75	24.99	28.85	14.98	23.76	20.26	28.56	32.98	17.12	27.22	23.25	32.80	37.91	19.69	31.34	25.56	36.08	41.70	21.66	34.52	29.57	41.76	48.29	25.11	40.04
MEX-300 & EC-240	21.29	29.99	34.62	17.97	28.52	24.31	34.27	39.58	20.55	32.67	27.90	39.37	45.49	23.62	37.61	30.67	43.29	50.04	26.00	41.42	35.49	50.11	57.94	30.13	48.05
MEX-350 & EC-280	24.84	34.99	40.39	20.97	33.27	28.36	39.98	46.18	23.97	38.11	32.55	45.93	53.07	27.56	43.88	35.78	50.51	58.39	30.33	48.33	41.40	58.46	67.60	35.15	56.06
MEX-400 & EC-320	28.39	39.98	46.16	23.96	38.02	32.41	45.69	52.78	27.40	43.56	37.20	52.49	60.66	31.50	50.15	40.90	57.73	66.73	34.66	55.23	47.32	66.82	77.26	40.17	64.06
MEX-450 & EC-360	31.94	44.98	51.93	26.96	42.78	36.46	51.40	59.37	30.82	49.00	41.85	59.05	68.24	35.43	56.42	46.01	64.94	75.07	39.00	62.14	53.23	75.17	86.92	45.19	72.07
MEX-500 & EC-400	35.49	49.98	57.70	29.95	47.53	40.51	57.11	65.97	34.24	54.44	46.50	65.61	75.82	39.37	62.69	51.12	72.16	83.41	43.33	69.04	59.15	83.52	96.57	50.21	80.08
MEX-600 & EC-480	42.59	59.98	69.23	35.94	57.03	48.61	68.54	79.16	41.09	65.33	55.80	78.73	90.99	47.25	75.22	61.34	86.59	100.09	51.99	82.85	70.98	100.23	115.89	60.25	96.10
MEX-700 & EC-560	49.69	69.97	80.77	41.93	66.54	56.71	79.96	92.36	47.94	76.22	65.10	91.85	106.15	55.12	87.76	71.57	101.02	116.77	60.66	96.66	82.81	116.93	135.20	70.30	112.11
MEX-700M & EC-560M	49.69	69.97	80.77	41.93	66.54	56.71	79.96	92.36	47.94	76.22	65.10	91.85	106.15	55.12	87.76	71.57	101.02	116.77	60.66	96.66	82.81	116.93	135.20	70.30	112.11
MEX-800M & EC-640M	56.79	79.97	92.31	47.92	76.04	64.82	91.38	105.55	54.79	87.11	74.40	104.98	121.31	62.99	100.30	81.79	115.45	133.45	69.33	110.47	94.64	133.63	154.52	80.34	128.13
MEX-900M & EC-720M	63.88	89.96	103.85	53.91	85.55	72.92	102.80	118.75	61.64	98.00	83.70	118.10	136.48	70.87	112.84	92.02	129.88	150.13	77.99	124.27	106.47	150.34	173.83	90.38	144.14
MEX-1050M & EC-820M	74.53	104.96	121.16	62.90	99.81	85.07	119.94	138.54	71.91	114.33	97.65	137.78	159.22	82.68	131.64	107.35	151.53	175.16	90.99	144.99	124.21	175.39	202.80	105.45	168.17
MEX-1125M & EC-900M	79.85	112.45	129.81	67.39	106.94	91.15	128.50	148.43	77.05	122.50	104.62	147.62	170.60	88.58	141.04	115.02	162.35	187.67	97.49	155.34	133.08	187.92	217.29	112.98	180.18
MEX-1200M & EC-960M	85.18	119.95	138.47	71.89	114.07	97.23	137.07	158.33	82.19	130.67	111.60	157.46	181.97	94.49	150.45	122.69	173.18	200.18	103.99	165.70	141.95	200.45	231.77	120.51	192.19
EX-80KLSb & EC-65L	5.68	8.00	9.23	4.79	7.60	6.48	9.14	10.56	5.48	8.71	7.44	10.50	12.13	6.30	10.03	8.18	11.55	13.35	6.93	11.05	9.46	13.36	15.45	8.03	12.81
EX-100KLSb & EC-80L	7.10	10.00	11.54	5.99	9.51	8.10	11.42	13.19	6.85	10.89	9.30	13.12	15.16	7.87	12.54	10.22	14.43	16.68	8.67	13.81	11.83	16.70	19.31	10.04	16.02
EX-112.5KLSb & EC-90L	7.99	11.25	12.98	6.74	10.69	9.11	12.85	14.84	7.71	12.25	10.46	14.76	17.06	8.86	14.10	11.50	16.24	18.77	9.75	15.53	13.31	18.79	21.73	11.30	18.02
EX-125KLSb & EC-100L	8.87	12.49	14.42	7.49	11.88	10.13	14.28	16.49	8.56	13.61	11.62	16.40	18.96	9.84	15.67	12.78	18.04	20.85	10.83	17.26	14.79	20.88	24.14	12.55	20.02
EX-150KLSb & EC-120L	10.65	14.99	17.31	8.99	14.26	12.15	17.13	19.79	10.27	16.33	13.95	19.68	22.75	11.81	18.81	15.34	21.65	25.02	13.00	20.71	17.74	25.06	28.97	15.06	24.02
EX-175KLSb & EC-140L	12.42	17.49	20.19	10.48	16.63	14.18	19.99	23.09	11.99	19.06	16.27	22.96	26.54	13.78	21.94	17.89	25.25	29.19	15.17	24.16	20.70	29.23	33.80	17.57	28.03
EX-200KLSb & EC-160L	14.20	19.99	23.08	11.98	19.01	16.20	22.85	26.39	13.70	21.78	18.60	26.24	30.33	15.75	25.07	20.45	28.86	33.36	17.33	27.62	23.66	33.41	38.63	20.08	32.03
MEX-250KLS & EC-200L	17.75	24.99	28.85	14.98	23.76	20.26	28.56	32.98	17.12	27.22	23.25	32.80	37.91	19.69	31.34	25.56	36.08	41.70	21.66	34.52	29.57	41.76	48.29	25.11	40.04
MEX-300KLS & EC-240L	21.29	29.99	34.62	17.97	28.52	24.31	34.27	39.58	20.55	32.67	27.90	39.37	45.49	23.62	37.61	30.67	43.29	50.04	26.00	41.42	35.49	50.11	57.94	30.13	48.05
MEX-350KLS & EC-280L	24.84	34.99	40.39	20.97	33.27	28.36	39.98	46.18	23.97	38.11	32.55	45.93	53.07	27.56	43.88	35.78	50.51	58.39	30.33	48.33	41.40	58.46	67.60	35.15	56.06
MEX-400KLS & EC-320L	28.39	39.98	46.16	23.96	38.02	32.41	45.69	52.78	27.40	43.56	37.20	52.49	60.66	31.50	50.15	40.90	57.73	66.73	34.66	55.23	47.32	66.82	77.26	40.17	64.06
MEX-500KLS & EC-400L	35.49	49.98	57.70	29.95	47.53	40.51	57.11	65.97	34.24	54.44	46.50	65.61	75.82	39.37	62.69	51.12	72.16	83.41	43.33	69.04	59.15	83.52	96.57	50.21	80.08
DYNA-1401	5.14	7.36	8.56	4.29	6.98	5.90	8.46	9.84	4.94	8.04	6.82	9.78	11.37	5.72	9.32	7.53	10.80	12.56	6.32	10.30	8.76	12.57	14.62	7.37	12.02
DYNA-1402	5.68	8.14	9.46	4.74	7.71	6.52	9.35	10.88	5.46	8.89	7.53	10.81	12.57	6.32	10.30	8.32	11.93	13.88	6.98	11.39	9.69	13.89	16.16	8.15	13.29
DYNA-1403	6.96	9.98	11.60	5.81	9.46	8.00	11.47	13.33	6.69	10.90	9.24	13.25	15.41	7.75	12.63	10.20	14.63	17.02	8.56	13.96	11.88	17.03	19.81	9.99	16.30
DYNA-1701	6.22	8.91	10.36	5.19	8.45	7.14</																			

STD-201RS Table 3b - SI Units - Cooling Towers (CT) - I/s

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28
<b>Model</b>	<b>Water Flow, I/s</b>																								
DYNA-2505	16.79	23.71	27.39	14.17	22.59	19.23	27.17	31.39	16.26	25.96	22.15	31.29	36.16	18.77	29.97	24.40	34.47	39.83	20.71	33.07	28.33	39.99	46.21	24.09	38.46
DYNA-2507	18.68	26.38	30.47	15.76	25.13	21.40	30.22	34.92	18.09	28.88	24.64	34.81	40.23	20.88	33.34	27.15	38.34	44.31	23.04	36.79	31.51	44.49	51.41	26.80	42.79
DYNA-2511	21.48	30.33	35.03	18.12	28.90	24.60	34.75	40.15	20.80	33.20	28.33	40.02	46.25	24.01	38.34	31.22	44.09	50.95	26.49	42.30	36.23	51.15	59.11	30.81	49.20
DYNA-2515	24.49	34.58	39.94	20.66	32.95	28.05	39.62	45.78	23.72	37.85	32.30	45.63	52.73	27.37	43.71	35.59	50.26	58.09	30.20	48.23	41.31	58.31	67.39	35.13	56.09
DYNA-2805	19.52	27.56	31.84	16.47	26.26	22.36	31.58	36.49	18.91	30.17	25.75	36.37	42.03	21.82	34.84	28.37	40.07	46.31	24.07	38.45	32.93	46.48	53.72	28.00	44.71
DYNA-2807	22.04	31.12	35.95	18.60	29.65	25.24	35.66	41.20	21.35	34.07	29.07	41.06	47.46	24.64	39.34	32.03	45.24	52.28	27.18	43.41	37.18	52.48	60.65	31.62	50.48
DYNA-2811	25.19	35.56	41.08	21.25	33.89	28.85	40.75	47.08	24.39	38.93	33.23	46.93	54.24	28.16	44.96	36.61	51.70	59.75	31.06	49.61	42.49	59.98	69.32	36.13	57.69
DYNA-2815	27.99	39.52	45.65	23.62	37.65	32.06	45.28	52.32	27.11	43.26	36.92	52.15	60.26	31.28	49.95	40.67	57.44	66.39	34.52	55.12	47.21	66.64	77.02	40.15	64.10
DYNA-2819	30.16	42.58	49.18	25.45	40.57	34.54	48.79	56.37	29.21	46.61	39.78	56.19	64.93	33.71	53.83	43.83	61.89	71.53	37.19	59.39	50.87	71.81	82.99	43.26	69.07
DYNA-2822	31.49	44.46	51.35	26.57	42.36	36.06	50.94	58.86	30.49	48.67	41.53	58.66	67.80	35.19	56.20	45.76	64.62	74.69	38.83	62.01	53.11	74.98	86.65	45.17	72.12
DYNA-2907	23.52	33.06	38.13	19.89	31.55	26.91	37.85	43.67	22.82	36.22	30.97	43.56	50.26	26.32	41.79	34.10	47.96	55.33	29.02	46.08	39.54	55.59	64.13	33.73	53.55
DYNA-2911	26.83	37.73	43.51	22.70	36.00	30.71	43.19	49.83	26.04	41.33	35.34	49.71	57.35	30.03	47.69	38.91	54.72	63.14	33.11	52.59	45.12	63.43	73.19	38.49	61.11
DYNA-2915	29.52	41.50	47.86	24.97	39.60	33.78	47.51	54.81	28.64	45.46	38.87	54.68	63.09	33.03	52.46	42.80	60.20	69.46	36.43	57.85	49.64	69.78	80.51	42.34	67.22
DYNA-2919	32.20	45.28	52.21	27.24	43.20	36.85	51.83	59.79	31.25	49.60	42.41	59.65	68.82	36.04	57.22	46.69	65.67	75.77	39.74	63.11	54.15	76.12	87.82	46.18	73.33
DYNA-2922	34.18	48.06	55.42	28.92	45.86	39.11	55.02	63.47	33.16	52.64	45.01	63.31	73.05	38.25	60.74	49.56	69.70	80.42	42.18	66.98	57.47	80.79	93.22	49.02	77.83
DYNA-3011	30.06	42.06	48.41	25.52	40.20	34.37	48.10	55.38	29.25	46.11	39.52	55.30	63.67	33.70	53.15	43.48	60.84	70.05	37.14	58.57	50.37	70.44	81.11	43.12	67.98
DYNA-3015	33.35	46.65	53.69	28.31	44.60	38.13	53.36	61.43	32.44	51.15	43.83	61.34	70.63	37.38	58.96	48.23	67.49	77.71	41.19	64.97	55.88	78.14	89.97	47.83	75.41
DYNA-3019	35.99	50.35	57.95	30.56	48.13	41.15	57.59	66.30	35.01	55.20	47.31	66.20	76.22	40.34	63.63	52.05	72.83	83.86	44.46	70.12	60.30	84.33	97.10	51.62	81.39
DYNA-3022	37.85	52.95	60.94	32.13	50.61	43.27	60.56	69.72	36.82	58.05	49.75	69.62	80.16	42.42	66.91	54.74	76.59	88.19	46.75	73.74	63.41	88.68	102.10	54.28	85.59
DYNA-3030	40.49	56.64	65.19	34.37	54.15	46.29	64.79	74.58	39.39	62.10	53.22	74.48	85.75	45.39	71.58	58.56	81.94	94.34	50.02	78.88	67.84	94.87	109.23	58.07	91.56
DYNA-3111	39.92	55.85	64.27	33.89	53.38	45.64	63.87	73.53	38.84	61.23	52.47	73.43	84.54	44.75	70.57	57.74	80.78	93.01	49.31	77.77	66.88	93.53	107.69	57.25	90.27
DYNA-3115	44.63	62.44	71.86	37.89	59.69	51.03	71.41	82.21	43.42	68.46	58.66	82.09	94.52	50.03	78.90	64.55	90.32	104.00	55.13	86.95	74.78	104.58	120.41	64.01	100.93
DYNA-3119	49.99	69.93	80.48	42.44	66.85	57.15	79.98	92.08	48.63	76.67	65.70	91.95	105.87	56.03	88.37	72.30	101.16	116.47	61.75	97.39	83.75	117.13	134.85	71.69	113.04
DYNA-3122	51.42	71.93	82.78	43.65	68.76	58.79	82.27	94.71	50.02	78.86	67.58	94.57	108.89	57.63	90.90	74.36	104.05	119.80	63.51	100.17	86.15	120.47	138.71	73.74	116.27
DYNA-3130	57.13	79.92	91.98	48.50	76.40	65.32	91.41	105.23	55.58	87.62	75.09	105.08	120.99	64.04	101.00	82.63	115.61	133.11	70.57	111.30	95.72	133.86	154.12	81.94	129.19
DYNA-3137	60.56	84.72	97.50	51.41	80.98	69.24	96.89	111.55	58.91	92.88	79.60	111.39	128.25	67.88	107.06	87.58	122.54	141.10	74.80	117.98	101.46	141.89	163.37	86.85	136.94
DYNA-3145	65.45	89.76	102.50	54.28	86.42	74.57	102.28	116.83	64.35	98.76	85.40	117.13	133.81	73.87	113.40	93.73	128.52	146.82	81.20	124.65	108.14	148.20	169.30	93.91	144.10
DYNA-3615	39.96	54.80	62.57	129.62	52.76	45.52	62.44	71.32	39.28	60.29	52.13	71.51	81.69	45.10	69.23	57.22	78.46	89.63	49.57	76.09	66.02	90.48	103.35	57.33	87.97
DYNA-3619	44.73	61.34	70.05	145.10	59.06	50.96	69.90	79.84	43.97	67.49	58.36	80.04	91.44	50.48	77.50	64.05	87.83	100.34	55.49	85.18	73.90	101.28	115.69	64.18	98.47
DYNA-3622	46.37	63.59	72.61	150.42	61.22	52.83	72.46	82.77	45.59	69.97	60.50	82.98	94.79	52.33	80.34	66.40	91.05	104.01	57.53	88.30	76.61	104.99	119.94	66.53	102.08
DYNA-3630	52.18	71.56	81.72	169.28	68.90	59.45	81.55	93.15	51.30	78.74	68.09	93.38	106.68	58.90	90.41	74.73	102.47	117.06	64.74	99.38	86.22	118.16	134.98	74.87	114.88
DYNA-3637	54.72	75.04	85.69	177.50	72.25	62.34	85.51	97.67	53.80	82.56	71.39	97.92	111.86	61.76	94.80	78.35	107.44	122.74	67.88	104.20	90.40	123.90	141.53	78.51	120.46
DYNA-3645	58.45	80.15	91.53	189.59	77.17	66.58	91.33	104.33	57.46	88.19	76.26	104.59	119.48	65.96	101.26	83.69	114.76	131.10	72.51	111.30	96.56	132.34	151.17	83.86	128.67
DYNA-3622	65.90	90.37	103.20	213.77	87.01	75.08	102.98	117.63	64.79	99.44	85.98	117.93	134.72	74.38	114.18	94.37	129.40	147.83	81.76	125.50	108.88	149.22	170.46	94.55	145.08
DYNA-3730	73.21	100.39	114.64	237.47	96.66	83.40	114.40	130.67	71.97	110.46	95.52	131.01	149.66	82.62	126.84	104.83	143.75	164.22	90.82	139.41	120.95	165.76	189.35	105.04	161.16
DYNA-3737	80.14	109.90	125.50	259.96	105.81	91.30	125.23	143.05	78.79	120.92	104.56	143.41	163.83	90.45	138.85	114.76	157.36	179.77	99.42	152.61	132.41	181.46	207.29	114.98	176.43
DYNA-3745	83.87	115.01	131.34	272.05	110.73	95.55	131.06	149.70	82.45	126.55	109.42	150.08	171.45	94.65	145.31	120.09	164.68	188.13	104.05						

# KIMCO Cooling Tower

STD-201RS Table 3b - SI Units - Co

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	24	24	27	27	27	27	27	29	29	29	29	29	32.2	32.2	32.2	32.2	32.2	21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	5	5.56	5	5
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.2	44.2	45.2	44.2	47.2	32	35.00	37	37
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.2	38.2	39.2	36.2	39.2	27	29.44	32	32
<b>Model</b>																								
EX-80Klb & EC-65	10.99	15.53	17.96	9.35	14.92	12.82	18.11	20.95	10.92	17.43	14.23	20.10	23.25	12.13	19.38	16.87	23.83	27.57	14.41	23.02	15.14	12.19	17.33	15.10
EX-100Klb & EC-80	13.74	19.41	22.45	11.69	18.65	16.03	22.64	26.18	13.65	21.79	17.79	25.13	29.07	15.17	24.22	21.09	29.78	34.46	18.01	28.77	18.92	15.24	21.67	18.87
EX-125Klb & EC-100	17.18	24.26	28.06	14.61	23.31	20.03	28.30	32.73	17.06	27.24	22.24	31.41	36.33	18.96	30.27	26.36	37.23	43.07	22.51	35.96	23.66	19.05	27.08	23.59
EX-150Klb & EC-120	20.62	29.12	33.67	17.53	27.97	24.04	33.95	39.28	20.47	32.68	26.69	37.69	43.60	22.75	36.33	31.63	44.68	51.69	27.02	43.16	28.39	22.86	32.50	28.31
EX-175Klb & EC-140	24.05	33.97	39.29	20.45	32.63	28.05	39.61	45.82	23.89	38.13	31.13	43.97	50.87	26.54	42.38	36.91	52.12	60.30	31.52	50.35	33.12	26.67	37.92	33.02
EX-200Klb & EC-160	27.49	38.82	44.90	23.37	37.30	32.05	45.27	52.37	27.30	43.58	35.58	50.25	58.13	30.33	48.44	42.18	59.57	68.92	36.02	57.54	37.85	30.47	43.33	37.74
EX-225Klb & EC-180	30.92	43.67	50.51	26.29	41.96	36.06	50.93	58.91	30.71	49.03	40.03	56.54	65.40	34.13	54.49	47.45	67.02	77.53	40.53	64.74	42.58	34.28	48.75	42.46
EX-250Klb & EC-200	34.36	48.53	56.12	29.21	46.62	40.07	56.59	65.46	34.12	54.47	44.48	62.82	72.67	37.92	60.55	52.72	74.46	86.15	45.03	71.93	47.31	38.09	54.17	47.18
MEX-300 & EC-240	41.23	58.23	67.35	35.06	55.94	48.08	67.91	78.55	40.95	65.37	53.37	75.38	87.20	45.50	72.66	63.27	89.35	103.38	54.04	86.31	56.77	45.71	65.00	56.61
MEX-350 & EC-280	48.10	67.94	78.57	40.90	65.27	56.09	79.23	91.64	47.77	76.26	62.27	87.94	101.73	53.08	84.77	73.81	104.25	120.61	63.04	100.70	66.24	53.33	75.83	66.05
MEX-400 & EC-320	54.97	77.64	89.79	46.74	74.59	64.11	90.55	104.73	54.60	87.16	71.16	100.51	116.27	60.67	96.88	84.36	119.14	137.84	72.05	115.09	75.70	60.95	86.67	75.48
MEX-450 & EC-360	61.85	87.35	101.02	52.59	83.92	72.12	101.86	117.83	61.42	98.05	80.06	113.07	130.80	68.25	108.99	94.90	134.03	155.07	81.05	129.47	85.16	68.57	97.50	84.92
MEX-500 & EC-400	68.72	97.05	112.24	58.43	93.24	80.13	113.18	130.92	68.24	108.95	88.95	125.64	145.33	75.84	121.10	105.45	148.92	172.30	90.06	143.86	94.62	76.19	108.33	94.36
MEX-600 & EC-480	82.46	116.46	134.69	70.11	111.89	96.16	135.82	157.10	81.89	130.74	106.74	150.76	174.40	91.00	145.32	126.54	178.71	206.76	108.07	172.63	113.55	91.42	130.00	113.23
MEX-700 & EC-560	96.20	135.87	157.14	81.80	130.54	112.19	158.46	183.28	95.54	152.53	124.53	175.89	203.47	106.17	169.53	147.63	208.49	241.22	126.08	201.40	132.47	106.66	151.67	132.10
MEX-700M & EC-560M	96.20	135.87	157.14	81.80	130.54	112.19	158.46	183.28	95.54	152.53	124.53	175.89	203.47	106.17	169.53	147.63	208.49	241.22	126.08	201.40	132.47	106.66	151.67	132.10
MEX-800M & EC-640M	109.95	155.29	179.59	93.49	149.18	128.21	181.09	209.47	109.19	174.32	142.32	201.02	232.53	121.34	193.75	168.72	238.28	275.68	144.10	230.17	151.40	121.90	173.33	150.97
MEX-900M & EC-720M	123.69	174.70	202.04	105.17	167.83	144.24	203.73	235.65	122.84	196.11	160.11	226.14	261.60	136.50	217.97	189.81	268.06	310.14	162.11	258.94	170.32	137.14	195.00	169.84
MEX-1050M & EC-820M	144.31	203.81	235.71	122.70	195.80	168.28	237.68	274.93	143.31	228.79	186.80	263.83	305.20	159.25	254.30	221.44	312.74	361.83	189.13	302.10	198.71	159.99	227.50	198.15
MEX-1125M & EC-900M	154.61	218.37	252.55	131.46	209.79	180.30	254.66	294.56	153.55	245.14	200.14	282.68	327.00	170.63	272.47	237.26	335.08	387.67	202.63	323.68	212.90	171.42	243.75	212.30
MEX-1200M & EC-960M	164.92	232.93	269.38	140.23	223.78	192.32	271.64	314.20	163.79	261.48	213.48	301.53	348.80	182.01	290.63	253.08	357.42	413.51	216.14	345.26	227.10	182.85	260.00	226.45
EX-80KLSb & EC-65L	10.99	15.53	17.96	9.35	14.92	12.82	18.11	20.95	10.92	17.43	14.23	20.10	23.25	12.13	19.38	16.87	23.83	27.57	14.41	23.02	15.14	12.19	17.33	15.10
EX-100KLSb & EC-80L	13.74	19.41	22.45	11.69	18.65	16.03	22.64	26.18	13.65	21.79	17.79	25.13	29.07	15.17	24.22	21.09	29.78	34.46	18.01	28.77	18.92	15.24	21.67	18.87
EX-112.5KLSb & EC-90L	15.46	21.84	25.25	13.15	20.98	18.03	25.47	29.46	15.35	24.51	20.01	28.27	32.70	17.06	27.25	23.73	33.51	38.77	20.26	32.37	21.29	17.14	24.38	21.23
EX-125KLSb & EC-100L	17.18	24.26	28.06	14.61	23.31	20.03	28.30	32.73	17.06	27.24	22.24	31.41	36.33	18.96	30.27	26.36	37.23	43.07	22.51	35.96	23.66	19.05	27.08	23.59
EX-150KLSb & EC-120L	20.62	29.12	33.67	17.53	27.97	24.04	33.95	39.28	20.47	32.68	26.69	37.69	43.60	22.75	36.33	31.63	44.68	51.69	27.02	43.16	28.39	22.86	32.50	28.31
EX-175KLSb & EC-140L	24.05	33.97	39.29	20.45	32.63	28.05	39.61	45.82	23.89	38.13	31.13	43.97	50.87	26.54	42.38	36.91	52.12	60.30	31.52	50.35	33.12	26.67	37.92	33.02
EX-200KLSb & EC-160L	27.49	38.82	44.90	23.37	37.30	32.05	45.27	52.37	27.30	43.58	35.58	50.25	58.13	30.33	48.44	42.18	59.57	68.92	36.02	57.54	37.85	30.47	43.33	37.74
MEX-250KLS & EC-200L	34.36	48.53	56.12	29.21	46.62	40.07	56.59	65.46	34.12	54.47	44.48	62.82	72.67	37.92	60.55	52.72	74.46	86.15	45.03	71.93	47.31	38.09	54.17	47.18
MEX-300KLS & EC-240L	41.23	58.23	67.35	35.06	55.94	48.08	67.91	78.55	40.95	65.37	53.37	75.38	87.20	45.50	72.66	63.27	89.35	103.38	54.04	86.31	56.77	45.71	65.00	56.61
MEX-350KLS & EC-280L	48.10	67.94	78.57	40.90	65.27	56.09	79.23	91.64	47.77	76.26	62.27	87.94	101.73	53.08	84.77	73.81	104.25	120.61	63.04	100.70	66.24	53.33	75.83	66.05
MEX-400KLS & EC-320L	54.97	77.64	89.79	46.74	74.59	64.11	90.55	104.73	54.60	87.16	71.16	100.51	116.27	60.67	96.88	84.36	119.14	137.84	72.05	115.09	75.70	60.95	86.67	75.48
MEX-500KLS & EC-400L	68.72	97.05	112.24	58.43	93.24	80.13	113.18	130.92	68.24	108.95	88.95	125.64	145.33	75.84	121.10	105.45	148.92	172.30	90.06	143.86	94.62	76.19	108.33	94.36
DYNA-1401	10.25	14.69	17.09	8.64	14.08	12.03	17.23	20.04	10.16	16.56	13.41	19.20	22.32	11.34	18.47	16.00	22.89	26.61	13.57	22.08	14.32	11.41	16.47	14.26
DYNA-1402	11.33	16.24	18.88	9.55	15.57	13.29	19.04	22.15	11.23	18.30	14.82	21.22	24.67	12.54	20.42	17.68	25.30	29.41	15.00	24.41	15.82	12.61	18.20	15.76
DYNA-1403	13.89	19.91	23.16	11.71	19.09	16.30	23.35	27.15	13.77	22.44	18.17	26.02	30.25	15.37	25.04	21.68	31.02	36.06	18.39	29.93	19.40	15.47	22.32	19.33
DYNA-1701	12.40	17.78	20.68	10.46	17.05	14.56	20.86	24.25	12.30	20.04	16.2													

STD-201RS Table 3b - SI Units - Cor

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	24	24	27	27	27	27	29	29	29	29	29	32	32.2	32.2	32.2	32.2	32.2	21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	5	5.56	5	5
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.2	44.2	45.2	44.2	47.2	32	35.00	37	37
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.2	38.2	39.2	36.2	39.2	27	29.44	32	32
<b>Model</b>																								
DYNA-2505	33.01	46.57	53.81	28.13	44.90	38.60	54.41	62.86	32.97	52.58	42.93	60.47	69.85	36.72	58.53	51.03	71.80	82.92	43.76	69.68	45.20	36.62	52.00	45.39
DYNA-2507	36.72	51.80	59.86	31.30	49.95	42.94	60.53	69.93	36.68	58.50	47.76	67.27	77.71	40.86	65.11	56.77	79.88	92.25	48.69	77.52	50.29	40.74	57.85	50.50
DYNA-2511	42.22	59.57	68.83	35.99	57.43	49.38	69.60	80.41	42.18	67.26	54.91	77.35	89.35	46.98	74.87	65.27	91.85	106.07	55.98	89.13	57.82	46.85	66.52	58.06
DYNA-2515	48.14	67.91	78.47	41.03	65.47	56.29	79.35	91.67	48.09	76.68	62.60	88.19	101.87	53.56	85.35	74.41	104.71	120.93	63.82	101.61	65.92	53.41	75.83	66.19
DYNA-2805	38.37	54.13	62.55	32.71	52.19	44.87	63.25	73.08	38.33	61.13	49.90	70.30	81.20	42.69	68.04	59.32	83.47	96.40	50.87	81.00	52.55	42.58	60.45	52.77
DYNA-2807	43.32	61.12	70.62	36.93	58.93	50.66	71.42	82.51	43.28	69.01	56.34	79.37	91.68	48.20	76.82	66.97	94.24	108.84	57.44	91.45	59.33	48.07	68.25	59.57
DYNA-2811	49.51	69.85	80.71	42.20	67.34	57.90	81.62	94.29	49.46	78.87	64.39	90.71	104.78	55.09	87.79	76.54	107.71	124.38	65.64	104.52	67.80	54.94	78.00	68.08
DYNA-2815	55.01	77.61	89.68	46.89	74.83	64.34	90.69	104.77	54.96	87.64	71.54	100.78	116.42	61.21	97.55	85.04	119.67	138.20	72.94	116.13	75.34	61.04	86.67	75.65
DYNA-2819	59.28	83.62	96.63	50.52	80.62	69.32	97.71	112.89	59.22	94.43	77.09	108.60	125.44	65.95	105.11	91.63	128.95	148.92	78.59	125.13	81.18	65.77	93.38	81.51
DYNA-2822	61.89	87.31	100.89	52.75	84.18	72.38	102.02	117.87	61.83	98.59	80.49	113.38	130.97	68.86	109.74	95.67	134.63	155.48	82.05	130.64	84.76	68.67	97.50	85.10
DYNA-2907	46.04	64.67	74.61	39.35	62.45	53.79	75.50	87.08	46.09	73.07	59.78	83.85	96.69	51.30	81.28	70.98	99.46	114.67	61.07	96.67	62.71	51.03	72.15	63.11
DYNA-2911	52.54	73.80	85.14	44.91	71.26	61.38	86.15	99.37	52.59	83.38	68.22	95.69	110.34	58.54	92.75	81.00	113.50	130.85	69.68	110.31	71.57	58.23	82.33	72.01
DYNA-2915	57.79	81.18	93.65	49.40	78.39	67.52	94.77	109.30	57.85	91.72	75.04	105.25	121.38	64.39	102.03	89.10	124.85	143.94	76.65	121.34	78.72	64.06	90.57	79.22
DYNA-2919	63.04	88.56	102.16	53.89	85.51	73.66	103.39	119.24	63.11	100.06	81.86	114.82	132.41	70.24	111.31	97.20	136.20	157.02	83.62	132.37	85.88	69.88	98.80	86.42
DYNA-2922	66.91	94.00	108.44	57.20	90.76	78.18	109.73	126.56	66.98	106.20	86.89	121.87	140.54	74.56	118.14	103.17	144.56	166.66	88.76	140.50	91.15	74.17	104.87	91.72
DYNA-3011	58.58	81.86	94.24	50.26	79.19	68.37	95.45	109.86	58.79	92.56	75.92	105.93	121.90	65.39	102.88	90.04	125.49	144.38	77.75	122.20	79.28	64.86	91.22	79.99
DYNA-3015	64.98	90.81	104.54	55.75	87.85	75.84	105.88	121.87	65.22	102.67	84.22	117.51	135.22	72.53	114.12	99.88	139.20	160.15	86.24	135.55	87.94	71.94	101.18	88.73
DYNA-3019	70.13	98.00	112.82	60.17	94.81	81.85	114.27	131.52	70.38	110.81	90.89	126.82	145.94	78.28	123.17	107.79	150.23	172.84	93.08	146.29	94.91	77.64	109.20	95.76
DYNA-3022	73.75	103.06	118.64	63.27	99.70	86.07	120.17	138.31	74.01	116.52	95.58	133.36	153.46	82.32	129.52	113.35	157.98	181.76	97.88	153.84	99.80	81.65	114.83	100.70
DYNA-3030	78.90	110.25	126.92	67.69	106.66	92.08	128.56	147.96	79.18	124.66	102.25	142.67	164.18	88.07	138.56	121.26	169.01	194.44	104.71	164.58	106.77	87.35	122.85	107.72
DYNA-3111	77.78	108.70	125.13	66.73	105.15	90.78	126.74	145.88	78.06	122.90	100.81	140.65	161.86	86.82	136.61	119.55	166.63	191.70	103.23	162.26	105.27	86.11	121.12	106.20
DYNA-3115	86.97	121.53	139.91	74.61	117.57	101.50	141.71	163.10	87.28	137.41	112.71	157.26	180.97	97.07	152.74	133.67	186.30	214.33	115.42	181.41	117.69	96.28	135.42	118.74
DYNA-3119	97.40	136.12	156.70	83.57	131.68	113.68	158.71	182.67	97.75	153.90	126.23	176.13	202.69	108.72	171.06	149.71	208.66	240.05	129.27	203.18	131.82	107.84	151.67	132.99
DYNA-3122	100.19	140.00	161.17	85.96	135.44	116.92	163.25	187.89	100.55	158.30	129.84	181.17	208.48	111.83	175.95	153.99	214.62	246.91	132.97	208.99	135.58	110.92	156.00	136.79
DYNA-3130	111.32	155.56	179.08	95.51	150.49	129.91	181.39	208.77	111.72	175.89	144.27	201.30	231.64	124.26	195.50	171.09	238.46	274.35	147.74	232.21	150.65	123.24	173.33	151.99
DYNA-3137	118.00	164.89	189.83	101.24	159.52	137.71	192.27	221.29	118.42	186.44	152.92	213.37	245.54	131.71	207.23	181.36	252.77	290.81	156.60	246.14	159.69	130.63	183.73	161.11
DYNA-3145	125.24	171.51	195.90	109.02	167.17	145.55	199.14	227.40	127.00	194.56	161.16	220.36	251.60	140.85	215.64	190.23	259.83	296.61	166.70	254.96	165.22	138.00	190.23	168.44
DYNA-3615	76.46	104.71	119.59	66.56	102.05	88.85	121.57	138.83	77.53	118.77	98.38	134.52	153.60	85.99	131.65	116.13	158.62	181.08	101.77	155.65	100.86	84.25	116.13	102.83
DYNA-3619	85.59	117.21	133.87	74.50	114.24	99.46	136.08	155.40	86.79	132.96	110.13	150.59	171.94	96.25	147.37	130.00	177.56	202.70	113.92	174.23	112.91	94.30	130.00	115.11
DYNA-3622	88.73	121.51	138.78	77.23	118.43	103.11	141.07	161.10	89.97	137.83	114.17	156.11	178.24	99.78	152.77	134.77	184.07	210.13	118.10	180.62	117.05	97.76	134.77	119.33
DYNA-3630	99.85	136.74	156.18	86.92	133.28	116.04	158.76	181.30	101.25	155.12	128.49	175.68	200.59	112.30	171.93	151.67	207.16	236.48	132.91	203.27	131.72	110.02	151.67	134.29
DYNA-3637	104.70	143.38	163.77	91.14	139.75	121.67	166.48	190.11	106.17	162.65	134.73	184.22	210.34	117.75	180.28	159.03	217.22	247.97	139.36	213.15	138.12	115.37	159.03	140.82
DYNA-3645	111.84	153.15	174.93	97.35	149.27	129.96	177.82	203.06	113.40	173.73	143.91	196.77	224.67	125.77	192.56	169.87	232.02	264.86	148.85	227.67	147.53	123.22	169.87	150.41
DYNA-3622	126.10	172.69	197.24	109.77	168.31	146.54	200.50	228.96	127.87	195.89	162.26	221.86	253.32	141.81	217.12	191.53	261.61	298.64	167.84	256.70	166.35	138.94	191.53	169.59
DYNA-3730	140.08	191.83	219.10	121.94	186.97	162.79	222.72	254.34	142.04	217.61	180.25	246.46	281.41	157.54	241.19	212.77	290.61	331.75	186.45	285.16	184.79	154.34	212.77	188.39
DYNA-3737	153.35	210.00	239.85	133.48	204.67	178.20	243.82	278.43	155.49	238.21	197.32	269.80	308.06	172.45	264.03	232.92	318.13	363.17	204.11	312.17	202.29	168.96	232.92	206.24
DYNA-3745	160.48	219.76	251.01	139.69	214.19	186.49	255.16	291.38	162.73	249.29	206.50	282.35	322.38	180.48	276.31	243.75	332.93	380.06	213.60	326.69	211.70	176.82	243.75	215.83
DYNA-3755	171.18	234.42	267.74	149.01	228.47	198.92	272.17	310.80	173.57	265.91	220.26	301.17	343.88	192.51	294.73	260.00	355.13	405.39	227.84	348.47	225.81	188.61	260.00	230.22
DYNA-3775	191.15	261.76	298.98	166.39	255.13	222.13	303.92	347.06	193.83	296.94	245.96	336.31	383.99	214.97	329.12	290.33	396.56	452.69	254.42	389.12	252.16	210.61	290.33	257.08

**KIMCO Cooling Tower - EnduraCool Line**

**STD-201RS Table 3a - IP Units - Cooling Towers (CT)**

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb *F	50	50	50	50	50	55	55	55	55	55	60	60	60	60	60	65	65	65	65	65	70	70	70	70	70
Range *F	10	10	10	15	15	10	10	10	15	15	10	10	10	15	15	10	10	10	15	15	10	10	10	15	15
Approach *F	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12
Inlet Water Temperature *F	67	70	72	72	77	72	75	77	77	82	77	80	82	82	87	82	85	87	87	92	87	90	92	92	97
Outlet Water Temperature *F	57	60	62	57	62	62	65	67	62	67	67	70	72	67	72	72	75	77	72	77	77	80	82	77	82
<b>Model</b>	<b>Water Flow, gpm</b>																								
EX-80Klb & EC-65	92.4	124.7	147.5	72.8	112.4	104.4	141.0	166.9	82.4	127.4	118.5	160.1	189.6	93.7	145.2	135.1	182.6	216.4	107.0	166.0	154.6	209.1	247.8	122.7	190.5
EX-100Klb & EC-80	115.5	155.9	184.4	90.9	140.5	130.5	176.2	208.6	102.9	159.3	148.1	200.2	237.1	117.1	181.4	168.8	228.3	270.5	133.8	207.5	193.2	261.3	309.7	153.4	238.1
EX-125Klb & EC-100	144.4	194.9	230.5	113.7	175.6	163.1	220.3	260.8	128.7	199.1	185.1	250.2	296.3	146.4	226.8	211.0	285.3	338.1	167.2	259.4	241.5	326.6	387.1	191.8	297.7
EX-150Klb & EC-120	173.2	233.8	276.6	136.4	210.7	195.7	264.3	312.9	154.4	239.0	222.1	300.2	355.6	175.6	272.2	253.2	342.4	405.7	200.6	311.2	289.8	392.0	464.5	230.1	357.2
EX-175Klb & EC-140	202.1	272.8	322.7	159.1	245.9	228.3	308.4	365.1	180.1	278.8	259.1	350.3	414.8	204.9	317.5	295.4	399.5	473.3	234.1	363.1	338.1	457.3	542.0	268.5	416.7
EX-200Klb & EC-160	231.0	311.8	368.8	181.9	281.0	260.9	352.5	417.2	205.9	318.6	296.2	400.3	474.1	234.2	362.9	337.6	456.5	540.9	267.5	415.0	386.4	522.6	619.4	306.8	476.3
EX-225Klb & EC-180	259.9	350.7	414.9	204.6	316.1	293.5	396.5	469.4	231.6	358.4	333.2	450.3	533.4	263.5	408.2	379.8	513.6	608.5	301.0	466.8	434.7	588.0	696.8	345.2	535.8
EX-250Klb & EC-200	288.7	389.7	461.0	227.3	351.2	326.1	440.6	521.5	257.4	398.3	370.2	500.4	592.6	292.7	453.6	422.0	570.7	676.1	334.4	518.7	483.0	653.3	774.2	383.5	595.3
MEX-300 & EC-240	346.5	467.6	553.3	272.8	421.5	391.4	528.7	625.8	308.8	477.9	444.2	600.5	711.2	351.3	544.3	506.5	684.8	811.4	401.3	622.5	579.6	784.0	929.1	460.2	714.4
MEX-350 & EC-280	404.2	545.6	645.5	318.3	491.7	456.6	616.8	730.2	360.3	557.6	518.3	700.5	829.7	409.8	635.1	590.9	799.0	946.6	468.2	726.2	676.2	914.6	1083.9	536.9	833.4
MEX-400 & EC-320	462.0	623.5	737.7	363.8	562.0	521.8	704.9	834.5	411.8	637.2	592.3	800.6	948.2	468.4	725.8	675.3	913.1	1081.8	535.0	829.9	772.9	1045.3	1238.8	613.6	952.5
MEX-450 & EC-360	519.7	701.5	829.9	409.2	632.2	587.1	793.0	938.8	463.2	716.9	666.4	900.7	1066.7	526.9	816.5	759.7	1027.2	1217.1	601.9	933.7	869.5	1175.9	1393.6	690.3	1071.6
MEX-500 & EC-400	577.5	779.4	922.1	454.7	702.5	652.3	881.1	1043.1	514.7	796.5	740.4	1000.8	1185.3	585.4	907.2	844.1	1141.4	1352.3	668.8	1037.4	966.1	1306.6	1548.5	767.0	1190.6
MEX-600 & EC-480	693.0	935.3	1106.5	545.6	843.0	782.7	1057.4	1251.7	617.6	955.8	888.5	1200.9	1422.3	702.5	1088.7	1012.9	1369.6	1622.7	802.6	1244.9	1159.3	1567.9	1858.1	920.4	1428.8
MEX-700 & EC-560	808.4	1091.2	1290.9	636.6	983.5	913.2	1233.6	1460.3	720.6	1115.1	1036.6	1401.1	1659.4	819.6	1270.1	1181.7	1597.9	1893.2	936.3	1452.4	1352.5	1829.2	2167.8	1073.8	1666.9
MEX-700M & EC-560M	808.4	1091.2	1290.9	636.6	983.5	913.2	1233.6	1460.3	720.6	1115.1	1036.6	1401.1	1659.4	819.6	1270.1	1181.7	1597.9	1893.2	936.3	1452.4	1352.5	1829.2	2167.8	1073.8	1666.9
MEX-800M & EC-640M	923.9	1247.0	1475.3	727.5	1124.0	1043.7	1409.8	1668.9	823.5	1274.4	1184.6	1601.2	1896.4	936.7	1451.5	1350.5	1826.2	2163.7	1070.1	1659.9	1545.7	2090.6	2477.5	1227.2	1905.0
MEX-900M & EC-720M	1039.4	1402.9	1659.8	818.4	1264.5	1174.1	1586.0	1877.5	926.5	1433.8	1332.7	1801.4	2133.5	1053.8	1633.0	1519.4	2054.5	2434.1	1203.9	1867.4	1738.9	2351.9	2787.2	1380.6	2143.1
MEX-1050M & EC-820M	1212.7	1636.7	1936.4	954.9	1475.2	1369.8	1850.4	2190.5	1080.9	1672.7	1554.9	2101.6	2489.1	1229.4	1905.2	1772.6	2396.9	2839.8	1404.5	2178.6	2028.7	2743.9	3251.7	1610.7	2500.3
MEX-1125M & EC-900M	1299.3	1753.7	2074.7	1023.1	1580.6	1467.7	1982.5	2346.9	1158.1	1792.2	1665.9	2251.7	2666.8	1317.3	2041.2	1899.2	2568.1	3042.7	1504.8	2334.2	2173.6	2939.8	3484.0	1725.8	2678.9
MEX-1200M & EC-960M	1385.9	1870.6	2213.0	1091.3	1686.0	1565.5	2114.7	2503.4	1235.3	1911.7	1777.0	2401.8	2844.6	1405.1	2177.3	2025.8	2739.3	3245.5	1605.1	2489.8	2318.6	3135.8	3716.3	1840.8	2857.5
EX-80KLSb & EC-65L	92.4	124.7	147.5	72.8	112.4	104.4	141.0	166.9	82.4	127.4	118.5	160.1	189.6	93.7	145.2	135.1	182.6	216.4	107.0	166.0	154.6	209.1	247.8	122.7	190.5
EX-100KLSb & EC-80L	115.5	155.9	184.4	90.9	140.5	130.5	176.2	208.6	102.9	159.3	148.1	200.2	237.1	117.1	181.4	168.8	228.3	270.5	133.8	207.5	193.2	261.3	309.7	153.4	238.1
EX-112.5KLSb & EC-90L	129.9	175.4	207.5	102.3	158.1	146.8	198.3	234.7	115.8	179.2	166.6	225.2	266.7	131.7	204.1	189.9	256.8	304.3	150.5	233.4	217.4	294.0	348.4	172.6	267.9
EX-125KLSb & EC-100L	144.4	194.9	230.5	113.7	175.6	163.1	220.3	260.8	128.7	199.1	185.1	250.2	296.3	146.4	226.8	211.0	285.3	338.1	167.2	259.4	241.5	326.6	387.1	191.8	297.7
EX-150KLSb & EC-120L	173.2	233.8	276.6	136.4	210.7	195.7	264.3	312.9	154.4	239.0	222.1	300.2	355.6	175.6	272.2	253.2	342.4	405.7	200.6	311.2	289.8	392.0	464.5	230.1	357.2
EX-175KLSb & EC-140L	202.1	272.8	322.7	159.1	245.9	228.3	308.4	365.1	180.1	278.8	259.1	350.3	414.8	204.9	317.5	295.4	399.5	473.3	234.1	363.1	338.1	457.3	542.0	268.5	416.7
EX-200KLSb & EC-160L	231.0	311.8	368.8	181.9	281.0	260.9	352.5	417.2	205.9	318.6	296.2	400.3	474.1	234.2	362.9	337.6	456.5	540.9	267.5	415.0	386.4	522.6	619.4	306.8	476.3
MEX-250KLS & EC-200L	288.7	389.7	461.0	227.3	351.2	326.1	440.6	521.5	257.4	398.3	370.2	500.4	592.6	292.7	453.6	422.0	570.7	676.1	334.4	518.7	483.0	653.3	774.2	383.5	595.3
MEX-300KLS & EC-240L	346.5	467.6	553.3	272.8	421.5	391.4	528.7	625.8	308.8	477.9	444.2	600.5	711.2	351.3	544.3	506.5	684.8	811.4	401.3	622.5	579.6	784.0	929.1	460.2	714.4
MEX-350KLS & EC-280L	404.2	545.6	645.5	318.3	491.7	456.6	616.8	730.2	360.3	557.6	518.3	700.5	829.7	409.8	635.1	590.9	799.0	946.6	468.2	726.2	676.2	914.6	1083.9	536.9	833.4
MEX-400KLS & EC-320L	462.0	623.5	737.7	363.8	562.0	521.8	704.9	834.5	411.8	637.2	592.3	800.6	948.2	468.4	725.8	675.3	913.1	1081.8	535.0	829.9	772.9	1045.3	1238.8	613.6	952.5
MEX-500KLS & EC-400L	577.5	779.4	922.1	454.7	702.5	652.3	881.1	1043.1	514.7	796.5	740.4	1000.8	1185.3	585.4	907.2	844.1	1141.4	1352.3	668.8	1037.4	966.1	1306.6	1548.5	767.0	1190.6
DYNA-1401	83.7	114.8	136.8	65.0	102.8	95.1	130.4	155.6	74.0	117.2	108.6	148.9	177.7	84.7	134.3	124.5	170.8	203.8	97.4	154.4	143.4	196.5	234.5	112.4	178.2
DYNA-1402	92.5	126.8	151.2	71.8	113.6	105.1	144.2	172.0	81.8	129.5	120.0	164.6	196.4	93.6	148.4	137.6	188.7	225.2	107.6	170.7	158.4	217.2	259.2	124.2	197.0
DYNA-1403	113.5	155.5	185.5	88.0	139.3	128.9	176.8	210.9	100.3	158.9	147.2														

## KIMCO Cooling Tower - EnduraCool Line

STD-201RS Table 3a - IP Units - Cooling Towers (CT)

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °F	50	50	50	50	50	55	55	55	55	55	60	60	60	60	60	65	65	65	65	65	70	70	70	70	70
Range °F	10	10	10	15	15	10	10	10	15	15	10	10	10	15	15	10	10	10	15	15	10	10	10	15	15
Approach °F	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12
Inlet Water Temperature °F	67	70	72	72	77	72	75	77	77	82	77	80	82	82	87	82	85	87	87	92	87	90	92	92	97
Outlet Water Temperature °F	57	60	62	57	62	62	65	67	62	67	67	70	72	67	72	72	75	77	72	77	80	82	82	77	82
<b>Model</b>	<b>Water Flow, gpm</b>																								
DYNA-2505	273.2	369.5	437.5	215.0	333.9	309.5	418.8	495.9	244.3	379.7	352.4	476.7	564.7	278.9	433.6	402.9	545.0	645.5	319.8	497.3	462.4	625.2	740.4	368.1	572.2
DYNA-2507	303.9	411.1	486.7	239.2	371.4	344.4	465.9	551.7	271.8	422.4	392.1	530.4	628.2	310.3	482.4	448.3	606.3	718.1	355.8	553.2	514.5	695.5	823.7	409.5	636.6
DYNA-2511	349.5	472.7	559.6	275.0	427.1	396.0	535.7	634.4	312.5	485.6	450.8	609.8	722.3	356.8	554.7	515.4	697.1	825.7	409.1	636.1	591.5	799.7	947.1	470.8	731.9
DYNA-2515	398.4	538.9	638.0	313.6	486.9	451.4	610.7	723.2	356.3	553.7	513.9	695.3	823.5	406.8	632.4	587.6	794.7	941.3	466.4	725.2	674.4	911.7	1079.8	536.8	834.4
DYNA-2805	317.6	429.6	508.5	250.0	388.1	359.8	486.8	576.5	284.0	441.3	409.7	554.2	656.4	324.2	504.1	468.4	633.5	750.4	371.8	578.1	537.6	726.8	860.7	427.9	665.2
DYNA-2807	358.6	485.0	574.2	282.2	438.2	406.3	549.6	650.9	320.6	498.3	462.5	625.7	741.1	366.1	569.2	528.8	715.3	847.2	419.7	652.6	607.0	820.6	971.8	483.1	751.0
DYNA-2811	409.8	554.3	656.2	322.5	500.8	464.3	628.1	743.9	366.5	569.5	528.6	715.1	847.0	418.4	650.5	604.4	817.4	968.2	479.7	745.9	693.7	937.8	1110.6	552.1	858.3
DYNA-2815	455.4	615.9	729.1	358.4	556.4	515.9	697.9	826.5	407.2	632.8	587.3	794.6	941.1	464.9	722.7	671.5	908.3	1075.8	533.0	828.8	770.7	1042.0	1234.0	613.5	953.7
DYNA-2819	490.6	663.6	785.6	386.1	599.5	555.9	752.0	890.6	438.7	681.8	632.9	856.2	1014.0	500.9	778.8	723.6	978.7	1159.1	574.3	893.0	830.5	1122.7	1329.7	661.0	1027.6
DYNA-2822	512.3	692.8	820.2	403.2	626.0	580.4	785.2	929.8	458.1	711.9	660.8	893.9	1058.7	523.0	813.1	755.5	1021.8	1210.2	599.6	932.3	867.1	1172.2	1388.3	690.1	1072.9
DYNA-2907	382.4	515.3	608.9	302.1	466.6	432.9	583.5	689.7	343.0	530.3	492.5	663.8	784.7	391.3	605.2	562.6	758.2	896.2	448.4	693.5	645.2	869.1	1027.2	515.7	797.4
DYNA-2911	436.3	588.0	694.8	344.7	532.5	494.0	665.9	787.0	391.4	605.1	562.0	757.5	895.4	446.6	690.7	642.1	865.2	1022.7	511.6	791.4	736.3	991.7	1172.2	588.4	909.9
DYNA-2915	480.0	646.8	764.3	379.2	585.8	543.4	732.5	865.7	430.6	665.7	618.2	833.3	985.0	491.2	759.7	706.3	951.7	1125.0	562.8	870.5	809.9	1090.9	1289.4	647.3	1000.9
DYNA-2919	523.6	705.6	833.8	413.7	639.0	592.8	799.1	944.5	469.7	726.2	674.4	909.0	1074.5	535.9	828.8	770.5	1038.2	1227.3	614.0	949.6	883.6	1190.1	1406.6	706.1	1091.9
DYNA-2922	555.7	748.9	884.9	439.1	678.3	629.2	848.1	1002.4	498.5	770.8	715.8	964.8	1140.5	568.8	879.7	817.8	1102.0	1302.7	651.7	1008.0	937.8	1263.1	1493.0	749.5	1158.9
DYNA-3011	488.6	655.5	772.7	387.9	595.4	552.7	741.6	874.4	440.0	676.0	628.1	842.8	993.9	501.6	770.8	716.9	961.7	1134.1	574.2	882.3	821.4	1101.2	1298.5	659.8	1013.5
DYNA-3015	541.9	727.1	857.1	430.3	660.4	613.0	822.6	970.0	488.1	749.8	696.8	934.9	1102.5	556.4	855.0	795.3	1066.8	1258.0	636.9	978.7	911.1	1221.6	1440.3	731.8	1124.2
DYNA-3019	584.9	784.7	925.0	464.3	712.7	661.6	887.8	1046.8	526.8	809.2	752.0	1009.0	1189.9	600.5	922.8	858.3	1151.3	1357.7	687.4	1056.3	983.3	1318.4	1554.5	789.8	1213.3
DYNA-3022	615.0	825.2	972.7	488.3	749.5	695.7	933.6	1100.8	554.0	851.0	790.8	1061.1	1251.3	631.5	970.4	902.6	1210.7	1427.7	722.9	1110.8	1034.0	1386.4	1634.6	830.6	1275.9
DYNA-3030	658.0	882.8	1040.6	522.4	801.8	744.3	998.8	1177.7	592.7	910.4	846.0	1135.1	1338.6	675.6	1038.1	965.6	1295.2	1527.4	773.3	1188.3	1106.2	1483.1	1748.8	888.6	1364.9
DYNA-3111	648.7	870.3	1025.9	515.0	790.5	733.8	984.7	1161.1	584.3	897.5	834.0	1119.1	1319.7	666.0	1023.5	952.0	1277.0	1505.8	762.4	1171.5	1090.6	1462.2	1724.1	876.0	1345.7
DYNA-3115	725.3	973.1	1147.1	575.8	883.8	820.5	1101.0	1298.2	653.3	1003.5	932.5	1251.3	1475.5	744.7	1144.3	1064.3	1427.7	1683.6	852.4	1309.9	1219.4	1634.9	1927.6	979.5	1504.6
DYNA-3119	812.3	1089.9	1284.7	644.9	989.9	918.9	1233.1	1453.9	731.7	1123.9	1044.4	1401.4	1652.6	834.0	1281.6	1192.1	1599.1	1885.7	954.7	1467.0	1365.7	1831.0	2159.0	1097.0	1685.1
DYNA-3122	835.5	1121.0	1321.4	663.3	1018.2	945.2	1268.3	1495.5	752.6	1156.0	1074.3	1441.4	1699.8	857.9	1318.2	1226.1	1644.7	1939.5	982.0	1509.0	1404.7	1883.4	2220.6	1128.3	1733.2
DYNA-3130	928.4	1245.6	1468.2	737.0	1131.3	1050.2	1409.2	1661.7	836.2	1284.5	1193.6	1601.6	1888.7	953.2	1464.7	1362.4	1827.5	2155.0	1091.1	1676.6	1560.8	2092.6	2467.4	1253.7	1925.8
DYNA-3137	984.1	1320.3	1556.3	781.3	1199.2	1113.2	1493.8	1761.4	886.4	1361.5	1265.2	1697.7	2002.0	1010.4	1552.6	1444.1	1937.1	2284.3	1156.6	1777.2	1654.4	2218.2	2615.4	1328.9	2041.4
DYNA-3145	1061.0	1398.8	1633.7	859.1	1285.6	1196.2	1577.2	1842.6	971.5	1454.8	1354.9	1786.1	2086.8	1103.8	1653.1	1540.8	2030.5	2372.3	1259.1	1885.5	1758.6	2316.3	2705.9	1441.5	2157.8
DYNA-3615	647.7	853.9	997.3	524.4	784.8	730.3	962.8	1124.8	593.1	888.1	827.1	1090.4	1274.0	673.8	1009.2	940.6	1239.6	1448.3	768.6	1151.1	1073.6	1414.0	1651.9	880.0	1317.3
DYNA-3619	725.1	955.9	1116.4	587.1	878.5	817.5	1077.8	1259.2	663.9	994.2	925.9	1220.6	1426.1	754.3	1129.7	1053.0	1387.6	1621.2	860.4	1288.5	1201.8	1582.9	1849.1	985.1	1474.6
DYNA-3622	751.6	990.9	1157.4	608.6	910.7	847.4	1117.3	1305.3	688.3	1030.6	959.8	1265.3	1478.4	781.9	1171.1	1091.6	1438.5	1680.6	892.0	1335.8	1245.9	1640.9	1916.9	1021.2	1528.6
DYNA-3630	845.9	1115.2	1302.5	684.9	1024.9	953.7	1257.4	1469.0	774.6	1159.9	1080.2	1424.0	1663.8	880.0	1318.0	1228.4	1618.9	1891.4	1003.8	1503.3	1402.1	1846.7	2157.3	1149.2	1720.3
DYNA-3637	887.0	1169.3	1365.8	718.2	1074.7	1000.0	1318.5	1540.4	812.2	1216.2	1132.7	1493.2	1744.6	922.7	1382.0	1288.1	1697.5	1983.2	1052.6	1576.3	1470.2	1936.4	2262.1	1205.1	1803.9
DYNA-3645	947.4	1249.0	1458.8	767.1	1147.9	1068.2	1408.3	1645.3	867.5	1299.0	1209.8	1594.9	1863.4	985.6	1476.2	1375.9	1813.1	2118.3	1124.3	1683.7	1570.3	2068.3	2416.2	1287.1	1926.8
DYNA-3622	1068.3	1408.3	1644.9	864.9	1294.4	1204.4	1588.0	1855.2	978.2	1464.7	1364.1	1798.3	2101.1	1111.3	1664.4	1551.4	2044.4	2388.5	1267.7	1898.4	1770.6	2332.1	2724.3	1451.3	2172.5
DYNA-3730	1186.7	1564.4	1827.2	960.8	1437.8	1337.9	1764.0	2060.8	1086.6	1627.1	1515.4	1997.7	2334.0	1234.5	1849.0	1723.3	2271.0	2653.3	1408.2	2108.9	1966.9	2590.6	3026.4	1612.2	2413.4
DYNA-3737	1299.1	1712.6	2000.3	1051.8	1574.0	1464.6	1931.1	2256.0	1189.5	1781.2	1658.9	2186.9	2555.1	1351.4	2024.1	1886.5	2486.1	2904.6							

# KIMCO Cooling Tower

STD-201RS Table 3a - IP Units - Co

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb *F	75	75	75	75	75	80	80	80	80	80	85	85	85	85	85	90	90	90	90	90	69.8	78	80.6	82.4
Range *F	10	10	10	15	15	10	10	10	15	15	10	10	10	15	15	10	10	10	15	15	9	10	9	9
Approach *F	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	10.8	7	9	7.2
Inlet Water Temperature *F	92	95	97	97	102	97	100	102	102	107	102	105	107	107	112	107	110	112	112	117	89.6	95	98.6	98.6
Outlet Water Temperature *F	82	85	87	82	87	87	90	92	87	92	92	95	97	92	97	97	100	102	97	102	80.6	85	89.6	89.6
<b>Model</b>																								
EX-80Klb & EC-65	177.5	240.1	284.6	141.2	219.4	204.6	276.7	328.0	163.1	253.4	236.4	319.7	379.0	188.9	293.5	274.0	370.5	439.3	219.4	341.0	240.0	193.2	274.7	239.3
EX-100Klb & EC-80	221.9	300.2	355.8	176.5	274.2	255.7	345.8	410.0	203.8	316.7	295.5	399.6	473.8	236.1	366.9	342.5	463.1	549.1	274.2	426.2	300.0	241.5	343.4	299.1
EX-125Klb & EC-100	277.4	375.2	444.7	220.7	342.7	319.6	432.3	512.5	254.8	395.9	369.4	499.5	592.2	295.1	458.6	428.1	578.9	686.4	342.7	532.8	374.9	301.9	429.3	373.9
EX-150Klb & EC-120	332.9	450.2	533.7	264.8	411.3	383.5	518.8	615.0	305.8	475.0	443.2	599.5	710.7	354.1	550.3	513.7	694.7	823.6	411.3	639.3	449.9	362.3	515.1	448.7
EX-175Klb & EC-140	388.3	525.3	622.6	309.0	479.8	447.5	605.2	717.5	356.7	554.2	517.1	699.4	829.1	413.1	642.0	599.3	810.4	960.9	479.8	745.9	524.9	422.6	601.0	523.4
EX-200Klb & EC-160	443.8	600.3	711.6	353.1	548.4	511.4	691.7	820.0	407.7	633.4	591.0	799.3	947.6	472.1	733.7	684.9	926.2	1098.2	548.4	852.4	599.9	483.0	686.8	598.2
EX-225Klb & EC-180	499.3	675.4	800.5	397.2	616.9	575.3	778.1	922.5	458.6	712.6	664.9	899.2	1066.0	531.2	825.4	770.6	1042.0	1235.4	616.9	959.0	674.9	543.4	772.7	673.0
EX-250Klb & EC-200	554.8	750.4	889.5	441.4	685.5	639.2	864.6	1024.9	509.6	791.7	738.7	999.1	1184.5	590.2	917.2	856.2	1157.8	1372.7	685.5	1065.5	749.9	603.8	858.5	747.8
MEX-300 & EC-240	665.7	900.5	1067.3	529.6	822.6	767.1	1037.5	1229.9	611.5	950.1	886.5	1198.9	1421.4	708.2	1100.6	1027.4	1389.3	1647.2	822.6	1278.6	899.9	724.5	1030.3	897.3
MEX-350 & EC-280	776.7	1050.6	1245.2	617.9	959.7	894.9	1210.4	1434.9	713.4	1108.4	1034.2	1398.7	1658.3	826.2	1284.0	1198.7	1620.9	1921.8	959.7	1491.7	1049.9	845.3	1202.0	1046.9
MEX-400 & EC-320	887.6	1200.6	1423.1	706.2	1096.8	1022.8	1383.4	1639.9	815.4	1266.8	1182.0	1598.5	1895.2	944.3	1467.5	1369.9	1852.4	2196.3	1096.8	1704.9	1199.8	966.1	1373.7	1196.4
MEX-450 & EC-360	998.6	1350.7	1601.0	794.5	1233.9	1150.6	1556.3	1844.9	917.3	1425.1	1329.7	1798.4	2132.1	1062.3	1650.9	1541.1	2084.0	2470.9	1233.9	1918.0	1349.8	1086.8	1545.4	1346.0
MEX-500 & EC-400	1109.6	1500.8	1778.9	882.7	1371.0	1278.5	1729.2	2049.9	1019.2	1583.5	1477.5	1998.2	2369.0	1180.3	1834.3	1712.4	2315.5	2745.4	1370.9	2131.1	1499.8	1207.6	1717.1	1495.5
MEX-600 & EC-480	1331.5	1801.0	2134.7	1059.3	1645.2	1534.1	2075.0	2459.9	1223.1	1900.2	1773.0	2397.8	2842.8	1416.4	2201.2	2054.8	2778.6	3294.5	1645.1	2557.3	1799.8	1449.1	2060.5	1794.7
MEX-700 & EC-560	1553.4	2101.1	2490.5	1235.8	1919.4	1789.8	2420.9	2869.9	1426.9	2216.9	2068.5	2797.5	3316.5	1652.5	2568.1	2397.3	3241.7	3843.6	1919.3	2983.5	2099.7	1690.6	2403.9	2093.8
MEX-700M & EC-560M	1553.4	2101.1	2490.5	1235.8	1919.4	1789.8	2420.9	2869.9	1426.9	2216.9	2068.5	2797.5	3316.5	1652.5	2568.1	2397.3	3241.7	3843.6	1919.3	2983.5	2099.7	1690.6	2403.9	2093.8
MEX-800M & EC-640M	1775.3	2401.3	2846.3	1412.4	2193.6	2045.5	2766.7	3279.8	1630.7	2533.6	2364.0	3197.1	3790.3	1888.6	2934.9	2739.8	3704.8	4392.6	2193.5	3409.7	2399.7	1932.1	2747.3	2392.9
MEX-900M & EC-720M	1997.2	2701.4	3202.0	1588.9	2467.8	2301.2	3112.6	3689.8	1834.6	2850.3	2659.4	3596.7	4264.1	2124.6	3301.8	3082.3	4168.0	4941.7	2467.7	3835.9	2699.6	2173.6	3090.8	2692.0
MEX-1050M & EC-820M	2330.1	3151.7	3735.7	1853.8	2879.1	2684.8	3631.3	4304.8	2140.3	3325.3	3102.7	4196.2	4974.8	2478.7	3852.1	3596.0	4862.6	5765.3	2879.0	4475.2	3149.6	2535.9	3605.9	3140.6
MEX-1125M & EC-900M	2496.5	3376.8	4002.6	1986.2	3084.7	2876.5	3890.7	4612.3	2293.2	3562.9	3324.3	4495.9	5330.2	2655.8	4127.2	3852.8	5209.9	6177.2	3084.6	4794.9	3374.5	2717.0	3863.4	3365.0
MEX-1200M & EC-960M	2662.9	3601.9	4269.4	2118.6	3290.4	3068.3	4150.1	4919.8	2446.1	3800.4	3545.9	4795.6	5685.5	2832.8	4402.4	4109.7	5557.3	6589.0	3290.3	5114.6	3599.5	2898.2	4121.0	3589.3
EX-80KLSb & EC-65L	177.5	240.1	284.6	141.2	219.4	204.6	276.7	328.0	163.1	253.4	236.4	319.7	379.0	188.9	293.5	274.0	370.5	439.3	219.4	341.0	240.0	193.2	274.7	239.3
EX-100KLSb & EC-80L	221.9	300.2	355.8	176.5	274.2	255.7	345.8	410.0	203.8	316.7	295.5	399.6	473.8	236.1	366.9	342.5	463.1	549.1	274.2	426.2	300.0	241.5	343.4	299.1
EX-112.5KLSb & EC-90L	249.6	337.7	400.3	198.6	308.5	287.7	389.1	461.2	229.3	356.3	332.4	449.6	533.0	265.6	412.7	385.3	521.0	617.7	308.5	479.5	337.5	271.7	386.3	336.5
EX-125KLSb & EC-100L	277.4	375.2	444.7	220.7	342.7	319.6	432.3	512.5	254.8	395.9	369.4	499.5	592.2	295.1	458.6	428.1	578.9	686.4	342.7	532.8	374.9	301.9	429.3	373.9
EX-150KLSb & EC-120L	332.9	450.2	533.7	264.8	411.3	383.5	518.8	615.0	305.8	475.0	443.2	599.5	710.7	354.1	550.3	513.7	694.7	823.6	411.3	639.3	449.9	362.3	515.1	448.7
EX-175KLSb & EC-140L	388.3	525.3	622.6	309.0	479.8	447.5	605.2	717.5	356.7	554.2	517.1	699.4	829.1	413.1	642.0	599.3	810.4	960.9	479.8	745.9	524.9	422.6	601.0	523.4
EX-200KLSb & EC-160L	443.8	600.3	711.6	353.1	548.4	511.4	691.7	820.0	407.7	633.4	591.0	799.3	947.6	472.1	733.7	684.9	926.2	1098.2	548.4	852.4	599.9	483.0	686.8	598.2
MEX-250KLS & EC-200L	554.8	750.4	889.5	441.4	685.5	639.2	864.6	1024.9	509.6	791.7	738.7	999.1	1184.5	590.2	917.2	856.2	1157.8	1372.7	685.5	1065.5	749.9	603.8	858.5	747.8
MEX-300KLS & EC-240L	665.7	900.5	1067.3	529.6	822.6	767.1	1037.5	1229.9	611.5	950.1	886.5	1198.9	1421.4	708.2	1100.6	1027.4	1389.3	1647.2	822.6	1278.6	899.9	724.5	1030.3	897.3
MEX-350KLS & EC-280L	776.7	1050.6	1245.2	617.9	959.7	894.9	1210.4	1434.9	713.4	1108.4	1034.2	1398.7	1658.3	826.2	1284.0	1198.7	1620.9	1921.8	959.7	1491.7	1049.9	845.3	1202.0	1046.9
MEX-400KLS & EC-320L	887.6	1200.6	1423.1	706.2	1096.8	1022.8	1383.4	1639.9	815.4	1266.8	1182.0	1598.5	1895.2	944.3	1467.5	1369.9	1852.4	2196.3	1096.8	1704.9	1199.8	966.1	1373.7	1196.4
MEX-500KLS & EC-400L	1109.6	1500.8	1778.9	882.7	1371.0	1278.5	1729.2	2049.9	1019.2	1583.5	1477.5	1998.2	2369.0	1180.3	1834.3	1712.4	2315.5	2745.4	1370.9	2131.1	1499.8	1207.6	1717.1	1495.5
DYNA-1401	165.6	227.0	270.8	130.2	206.4	192.0	262.9	313.6	151.3	239.8	223.1	305.4	364.2	176.3	279.3	260.1	355.7	424.1	206.1	326.3	226.9	180.9	261.0	226.0
DYNA-1402	183.1	250.9	299.3	143.9	228.2	212.2	290.6	346.6	167.2	262.5	246.6	337.5	402.5	194.9	308.7	287.5	393.1	468.7	227.8	360.7	250.8	199.9	288.5	249.8
DYNA-1403	224.5	307.6	367.0	176.4	279.8	260.1	356.3	425.0	205.0	325.0	302.4	413.9	493.6	239.0	378.6	352.5	482.0	574.7	279.4	442.3	307.5	24		

**KIMCO Cooling Tower**

**STD-201RS Table 3a - IP Units - Co**

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb *F	75	75	75	75	75	80	80	80	80	80	85	85	85	85	85	90	90	90	90	90	69.8	78	80.6	82.4
Range *F	10	10	10	15	15	10	10	10	15	15	10	10	10	15	15	10	10	10	15	15	9	10	9	9
Approach *F	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	7	10	12	7	12	10.8	7	9	7.2
Inlet Water Temperature *F	92	95	97	97	102	97	100	102	102	107	102	105	107	107	112	107	110	112	112	117	89.6	95	98.6	98.6
Outlet Water Temperature *F	82	85	87	82	87	87	90	92	87	92	92	95	97	92	97	97	100	102	97	102	80.6	85	89.6	89.6
<b>Model</b>																								
DYNA-2505	532.6	719.5	852.0	425.1	660.5	615.2	830.6	983.2	492.5	764.7	712.6	961.3	1137.6	572.2	887.8	827.8	1115.7	1319.8	666.6	1033.5	716.5	580.5	824.2	719.4
DYNA-2507	592.5	800.5	947.8	472.9	734.8	684.4	924.0	1093.8	547.9	850.7	792.8	1069.5	1265.6	636.5	987.6	920.9	1241.2	1468.3	741.6	1149.7	797.1	645.8	916.9	800.4
DYNA-2511	681.2	920.4	1089.8	543.8	844.9	786.9	1062.4	1257.7	629.9	978.2	911.6	1229.7	1455.2	731.9	1135.6	1058.9	1427.1	1688.3	852.7	1322.0	916.5	742.5	1054.3	920.3
DYNA-2515	776.6	1049.3	1242.5	619.9	963.2	897.1	1211.2	1433.8	718.2	1115.2	1039.3	1401.9	1659.1	834.4	1294.7	1207.2	1627.0	1924.8	972.2	1507.2	1044.9	846.5	1202.0	1049.2
DYNA-2805	619.1	836.5	990.4	494.2	767.8	715.2	965.5	1142.9	572.5	889.0	828.5	1117.6	1322.5	665.1	1032.0	962.3	1296.9	1534.3	775.0	1201.4	832.9	674.8	958.1	836.3
DYNA-2807	699.0	944.4	1118.2	557.9	866.9	807.4	1090.1	1290.4	646.4	1003.7	935.4	1261.8	1493.2	751.0	1165.2	1086.5	1464.3	1732.3	874.9	1356.4	940.4	761.9	1081.8	944.2
DYNA-2811	798.8	1079.3	1278.0	637.6	990.8	922.8	1245.8	1474.8	738.7	1147.0	1069.0	1442.0	1706.5	858.3	1331.7	1241.7	1673.5	1979.8	999.9	1550.2	1074.7	870.7	1236.3	1079.1
DYNA-2815	887.6	1199.2	1420.0	708.5	1100.8	1025.3	1384.3	1638.6	820.8	1274.5	1187.7	1602.2	1896.1	953.6	1479.6	1379.6	1859.4	2199.7	1111.0	1722.5	1194.1	967.5	1373.7	1199.0
DYNA-2819	956.4	1292.2	1530.0	763.4	1186.2	1104.8	1491.5	1765.6	884.4	1373.3	1279.8	1726.4	2043.0	1027.5	1594.3	1486.6	2003.5	2370.2	1197.2	1856.0	1286.7	1042.5	1480.1	1292.0
DYNA-2822	998.5	1349.1	1597.5	797.0	1238.5	1153.5	1557.3	1843.5	923.4	1433.8	1336.2	1802.5	2133.1	1072.8	1664.6	1552.1	2091.9	2474.7	1249.9	1937.8	1343.4	1088.4	1545.4	1348.9
DYNA-2907	742.4	999.4	1181.0	595.1	919.7	856.9	1152.5	1361.6	688.8	1063.8	991.8	1332.8	1574.1	799.6	1233.9	1151.0	1545.3	1824.5	930.8	1435.2	994.0	808.8	1143.6	1000.2
DYNA-2911	847.2	1140.4	1347.6	679.0	1049.5	977.8	1315.2	1553.8	786.0	1214.0	1131.8	1520.9	1796.3	912.5	1408.1	1313.4	1763.4	2082.0	1062.2	1637.7	1134.3	923.0	1305.0	1141.4
DYNA-2915	931.9	1254.4	1482.4	746.9	1154.4	1075.6	1446.7	1709.2	864.6	1335.3	1244.9	1673.0	1975.9	1003.7	1548.9	1444.8	1939.8	2290.2	1168.4	1801.5	1247.8	1015.3	1435.5	1255.6
DYNA-2919	1016.7	1368.5	1617.2	814.9	1259.4	1173.4	1578.2	1864.5	943.2	1456.7	1358.1	1825.1	2155.5	1095.0	1689.7	1576.1	2116.1	2498.4	1274.7	1965.3	1361.2	1107.6	1566.0	1369.7
DYNA-2922	1079.1	1452.5	1716.5	864.9	1336.7	1245.4	1675.2	1979.0	1001.2	1546.2	1441.5	1937.2	2287.9	1162.2	1793.5	1672.9	2246.1	2651.8	1352.9	2086.0	1444.8	1175.6	1662.1	1453.8
DYNA-3011	944.1	1265.0	1491.2	760.6	1167.7	1088.5	1457.3	1717.5	879.6	1349.3	1258.5	1683.4	1983.3	1020.0	1563.5	1458.9	1949.7	2296.2	1186.1	1816.5	1256.6	1028.0	1445.8	1267.8
DYNA-3015	1047.3	1403.2	1654.2	843.7	1295.3	1207.5	1616.6	1905.1	975.7	1496.8	1396.0	1867.4	2200.0	1131.5	1734.3	1618.3	2162.7	2547.1	1315.7	2015.0	1393.9	1140.3	1603.8	1406.3
DYNA-3019	1130.3	1514.4	1785.2	910.6	1397.9	1303.2	1744.6	2056.1	1053.0	1615.4	1506.7	2015.3	2374.3	1221.1	1871.7	1746.6	2334.1	2749.0	1420.0	2174.6	1504.3	1230.6	1730.8	1517.7
DYNA-3022	1188.6	1592.5	1877.3	957.5	1470.1	1370.4	1834.7	2162.1	1107.3	1698.7	1584.4	2119.3	2496.8	1284.1	1968.3	1836.7	2454.5	2890.8	1493.2	2286.8	1581.9	1294.1	1820.1	1596.0
DYNA-3030	1271.6	1703.7	2008.4	1024.4	1572.7	1466.0	1962.7	2313.1	1184.6	1817.3	1695.0	2267.2	2671.1	1373.8	2105.7	1964.9	2625.8	3092.6	1597.5	2446.4	1692.3	1384.4	1947.2	1707.4
DYNA-3111	1253.6	1679.7	1980.1	1009.9	1550.5	1445.4	1935.0	2280.5	1167.9	1791.7	1671.1	2235.3	2633.4	1354.4	2076.0	1937.2	2588.8	3048.9	1574.9	2411.9	1668.5	1364.9	1919.7	1683.3
DYNA-3115	1401.6	1878.0	2213.8	1129.2	1733.6	1616.0	2163.5	2549.7	1305.8	2003.2	1868.4	2499.2	2944.3	1514.3	2321.1	2165.9	2894.4	3408.9	1760.9	2696.7	1865.5	1526.1	2146.4	1882.1
DYNA-3119	1569.8	2103.3	2479.5	1264.7	1941.6	1809.9	2423.1	2855.7	1462.5	2243.6	2092.6	2799.1	3297.7	1696.0	2599.6	2425.8	3241.8	3818.0	1972.2	3020.3	2089.3	1709.2	2403.9	2107.9
DYNA-3122	1614.7	2163.4	2550.3	1300.8	1997.1	1861.6	2492.4	2937.3	1504.3	2307.7	2152.4	2879.0	3391.9	1744.5	2673.9	2495.1	3334.4	3927.1	2028.6	3106.6	2149.0	1758.0	2472.6	2168.2
DYNA-3130	1794.1	2403.8	2833.7	1445.3	2219.0	2068.5	2769.3	3263.6	1671.4	2564.1	2391.5	3198.9	3768.8	1938.3	2971.0	2772.3	3704.9	4363.4	2253.9	3451.8	2387.8	1953.4	2747.3	2409.1
DYNA-3137	1901.7	2548.0	3003.7	1532.1	2352.1	2192.6	2935.4	3459.4	1771.7	2717.9	2535.0	3390.9	3994.9	2054.6	3149.3	2938.7	3927.2	4625.2	2389.2	3658.9	2531.1	2070.6	2912.2	2553.6
DYNA-3145	2013.7	2650.4	3095.5	1655.6	2476.8	2312.5	3041.3	3551.2	1907.2	2850.9	2662.9	3499.0	4084.5	2203.1	3290.3	3074.3	4036.0	4710.1	2551.7	3807.6	2618.7	2187.3	3015.2	2669.8
DYNA-3615	1229.3	1618.0	1889.8	1010.7	1512.0	1411.7	1856.6	2167.9	1164.3	1740.4	1625.6	2136.1	2493.5	1345.0	2008.7	1876.8	2463.9	2875.4	1557.8	2324.5	1598.7	1335.3	1840.7	1629.9
DYNA-3619	1376.1	1811.2	2115.4	1131.4	1692.5	1580.3	2078.3	2426.8	1303.3	1948.2	1819.8	2391.1	2791.2	1505.6	2248.5	2100.9	2758.1	3218.7	1743.8	2602.0	1789.6	1494.7	2060.5	1824.5
DYNA-3622	1426.6	1877.6	2193.0	1172.9	1754.6	1638.3	2154.5	2515.7	1351.1	2019.6	1886.5	2478.8	2893.6	1560.8	2331.0	2177.9	2859.2	3336.7	1807.7	2697.4	1855.2	1549.5	2136.1	1891.4
DYNA-3630	1605.5	2113.1	2468.0	1320.0	1974.6	1843.7	2424.7	2831.2	1520.6	2272.9	2123.0	2789.7	3256.4	1756.5	2623.3	2451.1	3217.8	3755.2	2034.4	3035.7	2087.8	1743.8	2403.9	2128.6
DYNA-3637	1683.4	2215.7	2587.9	1384.1	2070.5	1933.3	2542.5	2968.7	1594.4	2383.3	2226.2	2925.2	3414.6	1841.8	2750.7	2570.1	3374.1	3937.6	2133.2	3183.1	2189.2	1828.5	2520.7	2231.9
DYNA-3645	1798.1	2366.7	2764.1	1478.4	2211.6	2064.9	2715.7	3171.0	1703.0	2545.7	2377.8	3124.4	3647.2	1967.3	2938.0	2745.2	3603.9	4205.8	2278.5	3399.9	2338.3	1953.1	2692.4	2384.0
DYNA-3622	2027.5	2668.5	3116.7	1666.9	2493.7	2328.3	3062.1	3575.4	1920.3	2870.4	2681.1	3523.0	4112.4	2218.2	3312.8	3095.3	4063.6	4742.2	2569.2	3833.6	2636.6	2202.2	3035.8	2688.1
DYNA-3730	2252.2	2964.4	3462.2	1851.7	2770.1	2586.4	3401.5	3971.8	2133.1	3188.6	2978.3	3913.5	4568.3	2464.1	3680.1	3438.5	4514.1	5268.0	2854.0	4258.6	2928.9	2446.4	3372.4	2986.1
DYNA-3737	2465.5	3245.1	3790.1	2027.1	3032.5	2831.4	3723.7	4348.0	2335.2	3490.5	3260.4	4284.1	5001.0	2										