

MITA PM Series R1

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28
PMS 6/65 K12 in l/s	1.0	1.4	1.6	0.9	1.3	1.1	1.5	1.7	1.0	1.4	1.3	1.7	1.9	1.1	1.6	1.4	1.9	2.1	1.2	1.8	1.6	2.1	2.4	1.3	2.0
PMS 9/85 K12 in l/s	2.0	2.7	3.0	1.7	2.6	2.2	3.0	3.4	1.9	2.9	2.5	3.4	3.8	2.2	3.2	2.7	3.6	4.1	2.4	3.5	3.1	4.1	4.6	2.6	3.9
PMS 9/110 K12 in l/s	3.3	4.3	4.9	2.8	4.1	3.6	4.8	5.4	3.1	4.6	4.1	5.4	6.1	3.5	5.2	4.4	5.9	6.6	3.8	5.6	4.9	6.6	7.5	4.3	6.3
PMS 9/130 K12 in l/s	4.7	6.2	7.0	4.1	5.9	5.2	6.9	7.9	4.5	6.7	5.8	7.8	8.8	5.1	7.5	6.3	8.4	9.5	5.5	8.1	7.1	9.5	10.8	6.2	9.1
PMS 10/180 K12 in l/s	7.3	9.7	11.0	6.3	9.3	8.1	10.9	12.3	7.1	10.4	9.1	12.2	13.8	7.9	11.7	9.9	13.2	14.9	8.6	12.6	11.1	14.9	16.8	9.7	14.3
PMS 10/240 K12 in l/s	9.3	12.4	14.1	8.1	11.9	10.4	13.9	15.7	9.0	13.3	11.7	15.6	17.6	10.1	14.9	12.6	16.9	19.1	11.0	16.2	14.2	19.0	21.5	12.4	18.3
PMS 10/260 K12 in l/s	11.6	15.6	17.6	10.1	14.9	13.0	17.4	19.6	11.3	16.6	14.6	19.5	22.0	12.7	18.7	15.8	21.1	23.8	13.7	20.2	17.8	23.8	26.9	15.5	22.8
PME-E 1803 K12 in l/s	9.4	12.8	14.6	8.1	12.2	10.6	14.4	16.4	9.1	13.8	11.9	16.3	18.5	10.3	15.6	13.0	17.7	20.1	11.2	16.9	14.8	20.1	22.8	12.7	19.2
PME-E 1804 K12 in l/s	11.0	14.8	16.8	9.5	14.2	12.4	16.6	18.8	10.7	15.9	13.9	18.7	21.2	12.1	18.0	15.1	20.3	23.0	13.2	19.5	17.2	23.0	26.0	14.9	22.1
PME-E 2053 K12 in l/s	13.6	18.5	21.1	11.6	17.6	15.3	20.8	23.7	13.1	19.9	17.3	23.5	26.8	14.8	22.5	18.8	25.5	29.1	16.1	24.4	21.3	29.0	32.9	18.4	27.8
PME-E 2054 K12 in l/s	15.0	20.2	22.9	13.0	19.3	16.9	22.7	25.6	14.6	21.7	19.0	25.5	28.9	16.5	24.5	20.6	27.7	31.3	17.9	26.6	23.4	31.3	35.4	20.4	30.2
PME-E 2403 K12 in l/s	15.9	21.6	24.6	13.6	20.6	17.8	24.3	27.7	15.3	23.2	20.2	27.4	31.3	17.3	26.3	21.9	29.8	33.9	18.9	28.6	24.9	33.9	38.5	21.5	32.5
PME-E 2404 K12 in l/s	16.7	22.4	25.4	14.4	21.5	18.8	25.2	28.5	16.3	24.2	21.1	28.4	32.1	18.3	27.3	22.9	30.8	34.8	19.9	29.6	26.0	34.8	39.4	22.6	33.5
PME-E 2853 K12 in l/s	19.4	26.4	29.8	16.6	25.2	21.8	29.7	33.8	18.7	28.4	24.7	33.6	38.2	21.2	32.1	26.8	36.5	41.5	23.1	34.9	30.5	41.4	47.1	26.3	39.7
PME-E 2854 K12 in l/s	21.5	28.9	32.6	18.6	27.6	24.1	32.4	36.6	20.9	31.1	27.2	36.5	41.3	23.6	35.0	29.5	39.6	44.8	25.6	38.0	33.4	44.8	50.6	29.1	43.1
PME-E 3103 K12 in l/s	21.1	28.8	32.8	18.1	27.4	23.8	32.4	36.9	20.4	30.9	26.9	36.6	41.6	23.1	35.0	29.2	39.7	45.2	25.1	38.0	33.2	45.1	51.3	28.6	43.2
PME-E 3104 K12 in l/s	23.4	31.4	35.6	20.2	30.1	26.3	35.3	39.9	22.8	33.8	29.6	39.7	44.9	25.7	38.2	32.1	43.1	48.8	27.9	41.4	36.4	48.8	55.2	31.7	46.9
PME-E 3353 K12 in l/s	22.9	31.1	35.4	19.6	29.7	25.7	35.0	39.9	22.1	33.4	29.1	39.6	45.0	25.0	37.8	31.6	43.0	48.9	27.2	41.2	35.9	48.8	55.5	30.9	46.8
PME-E 3354 K12 in l/s	25.3	34.0	38.5	21.9	32.5	28.4	38.1	43.2	24.6	36.6	32.0	43.0	48.6	27.8	41.3	34.8	46.6	52.8	30.2	44.8	39.4	52.8	59.7	34.3	50.8
PME-E 3603 K12 in l/s	24.6	33.5	38.1	21.1	31.9	27.7	37.7	42.9	23.7	36.0	31.3	42.6	48.4	26.9	40.7	34.0	46.3	52.6	29.3	44.3	38.6	52.5	59.7	33.3	50.3
PME-E 3604 K12 in l/s	27.2	36.6	41.4	23.5	35.0	30.6	41.1	46.4	26.5	39.4	34.4	46.2	52.3	29.9	44.4	37.4	50.1	56.7	32.5	48.2	42.4	56.8	64.2	36.9	54.6
PME-E 4103 K12 in l/s	27.8	37.8	43.1	23.8	36.1	31.3	42.6	48.4	26.8	40.6	35.3	48.1	54.7	30.4	46.0	38.4	52.3	59.4	33.0	50.0	43.6	59.3	67.4	37.6	56.8
PME-E 4104 K12 in l/s	30.8	41.3	46.8	26.6	39.5	34.5	46.4	52.5	29.9	44.5	38.9	52.2	59.1	33.8	50.2	42.2	56.6	64.1	36.7	54.5	47.9	64.1	72.5	41.6	61.7
PME-E 4803 K12 in l/s	32.4	44.2	50.3	27.8	42.1	36.5	49.7	56.6	31.3	47.4	41.2	56.1	63.9	35.4	53.7	44.8	61.0	69.4	38.6	58.4	50.9	69.2	78.7	43.9	66.3
PME-E 4804 K12 in l/s	35.9	48.2	54.6	31.0	46.1	40.3	54.1	61.3	34.9	51.9	45.4	60.9	69.0	39.4	58.6	49.3	66.1	74.8	42.8	63.6	55.9	74.8	84.6	48.6	72.0
PME-E 5703 K12 in l/s	39.5	53.8	61.2	33.8	51.3	44.4	60.5	68.9	38.1	57.8	50.2	68.3	77.8	43.1	65.4	54.6	74.3	84.5	46.9	71.1	62.0	84.3	95.8	53.4	80.8
PME-E 5704 K12 in l/s	43.7	58.7	66.5	37.8	56.2	49.1	65.9	74.6	42.5	63.2	55.3	74.3	84.0	48.0	71.3	60.0	80.5	91.1	52.1	77.4	62.5	91.1	103.1	59.2	87.7
PME-E 6203 K12 in l/s	42.9	58.5	66.6	36.8	55.8	48.3	65.8	74.9	41.4	62.9	54.6	74.3	84.6	46.9	71.1	59.4	80.8	91.9	51.1	77.3	67.4	91.7	104.3	58.1	87.9
PME-E 6204 K12 in l/s	47.5	63.9	72.3	41.1	61.1	53.4	71.7	81.1	46.2	68.8	60.2	80.8	91.4	52.2	77.6	65.3	87.6	99.1	56.7	84.2	74.0	99.1	112.1	64.4	95.4
PME-E 6703 K12 in l/s	46.4	63.2	72.0	39.8	60.3	52.2	71.1	80.9	44.8	67.9	59.0	80.3	91.4	50.7	76.8	64.1	87.3	99.3	55.2	83.6	72.9	99.1	112.7	62.8	95.0
PME-E 6704 K12 in l/s	51.4	69.0	78.1	44.4	66.1	57.7	77.5	87.7	49.9	74.3	65.0	87.3	98.8	56.4	83.8	70.6	94.6	107.1	61.3	91.0	80.0	107.1	121.2	69.6	103.1
PME-E 7203 K12 in l/s	49.9	67.9	77.3	42.7	64.8	56.1	76.4	87.0	48.1	73.0	63.4	86.3	98.2	54.5	82.6	68.9	93.8	106.7	59.3	89.8	78.3	106.5	121.1	67.5	102.1
PME-E 7204 K12 in l/s	55.2	74.2	83.9	47.7	71.0	62.0	83.3	94.2	53.7	79.8	69.9	93.8	106.1	60.6	90.1	75.8	101.7	115.1	65.9	97.8	85.9	115.1	130.2	74.8	110.8

MITA PM Series R1

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	24	24	27	27	27	27	27	29	29	29	29	29	32.2	32.2	32.2	32.2	32.2	21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	5	5.56	5	5
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.2	44.2	45.2	44.2	47.2	32	35.00	37	37
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.2	38.2	39.2	36.2	39.2	27	29.44	32	32
PMS 6/65 K12 in l/s	1.8	2.4	2.7	1.5	2.3	2.0	2.7	NC	1.7	2.6	2.2	NC	NC	1.9	NC	2.5	NC	NC	2.1	NC	2.4	1.9	2.6	2.3
PMS 9/85 K12 in l/s	3.4	4.6	5.3	3.0	4.4	3.9	5.3	NC	3.4	5.1	4.3	NC	NC	3.7	NC	4.9	NC	NC	4.3	NC	4.6	3.8	5.1	4.5
PMS 9/110 K12 in l/s	5.6	7.9	8.4	4.9	7.2	6.3	8.4	NC	5.5	8.1	6.9	NC	NC	6.0	NC	7.9	NC	NC	6.9	NC	7.4	6.1	8.2	7.3
PMS 9/130 K12 in l/s	8.0	10.8	12.1	7.0	10.3	9.1	12.2	NC	7.9	11.7	9.9	NC	NC	8.6	NC	11.3	NC	NC	9.9	NC	10.6	8.7	11.8	10.4
PMS 10/180 K12 in l/s	12.6	16.8	19.0	10.9	16.1	14.2	19.0	NC	12.4	18.3	15.5	NC	NC	13.5	NC	17.7	NC	NC	15.5	NC	16.6	13.6	18.4	16.3
PMS 10/240 K12 in l/s	16.1	21.5	24.3	14.0	20.6	18.2	24.3	NC	15.9	23.4	19.8	NC	NC	17.3	NC	22.7	NC	NC	19.8	NC	21.2	17.5	23.5	20.9
PMS 10/260 K12 in l/s	20.1	26.8	30.4	17.5	25.8	22.8	30.4	NC	19.8	29.3	24.8	NC	NC	21.6	NC	28.4	NC	NC	24.8	NC	26.5	21.8	29.4	26.1
PME-E 1803 K12 in l/s	16.8	22.8	25.9	14.5	21.9	19.2	26.0	NC	16.6	25.0	20.5	NC	NC	18.1	NC	25.2	NC	NC	21.9	NC	23.9	19.2	26.1	22.8
PME-E 1804 K12 in l/s	19.5	26.1	29.5	17.0	25.1	22.2	29.6	NC	19.4	28.6	24.1	NC	NC	21.1	NC	28.7	NC	NC	25.6	NC	27.7	23.0	30.1	26.8
PME-E 2053 K12 in l/s	24.3	33.0	37.5	21.0	31.6	27.7	37.6	NC	24.0	36.1	31.6	NC	NC	26.1	NC	35.2	NC	NC	32.1	NC	35.0	30.3	37.4	34.1
PME-E 2054 K12 in l/s	26.6	35.6	40.2	23.2	34.3	30.3	40.4	NC	26.4	38.9	34.5	NC	NC	28.5	NC	37.6	NC	NC	34.5	NC	37.4	32.7	39.8	36.5
PME-E 2403 K12 in l/s	28.4	38.5	43.8	24.5	37.0	32.4	43.9	NC	28.0	42.1	37.7	NC	NC	30.2	NC	39.3	NC	NC	36.2	NC	39.0	34.3	41.4	38.1
PME-E 2404 K12 in l/s	29.6	39.5	44.7	25.8	38.1	33.6	44.9	NC	29.3	43.3	38.9	NC	NC	31.4	NC	40.5	NC	NC	37.4	NC	40.2	35.5	42.6	39.3
PME-E 2853 K12 in l/s	34.7	47.1	53.5	30.0	45.2	39.6	53.7	NC	34.3	51.5	45.9	NC	NC	36.4	NC	45.5	NC	NC	42.4	NC	45.2	40.5	47.6	44.3
PME-E 2854 K12 in l/s	38.0	50.8	57.4	33.1	48.9	43.2	57.7	NC	37.7	55.6	49.9	NC	NC	40.0	NC	49.1	NC	NC	45.0	NC	47.8	43.1	50.2	46.9
PME-E 3103 K12 in l/s	37.8	51.3	58.3	32.6	49.2	43.2	58.4	NC	37.3	56.1	50.1	NC	NC	39.2	NC	48.4	NC	NC	44.3	NC	47.0	42.3	49.4	46.1
PME-E 3104 K12 in l/s	41.4	55.3	62.5	36.0	53.3	47.1	62.9	NC	41.1	60.6	54.6	NC	NC	43.7	NC	52.9	NC	NC	48.8	NC	51.5	46.8	53.9	50.6
PME-E 3353 K12 in l/s	40.9	55.5	63.1	35.3	53.3	46.7	63.3	NC	40.4	60.8	54.8	NC	NC	42.9	NC	52.1	NC	NC	47.2	NC	49.9	45.2	52.3	49.0
PME-E 3354 K12 in l/s	44.8	59.9	67.6	39.0	57.7	50.9	68.0	NC	44.4	65.6	59.6	NC	NC	47.5	NC	56.7	NC	NC	51.0	NC	53.7	49.0	56.1	52.8
PME-E 3603 K12 in l/s	44.0	59.7	67.9	38.0	57.3	50.2	68.0	NC	43.4	65.3	59.3	NC	NC	46.5	NC	55.7	NC	NC	50.0	NC	52.7	48.0	55.1	51.8
PME-E 3604 K12 in l/s	48.1	64.4	72.8	41.9	62.0	54.8	73.2	NC	47.8	70.5	64.5	NC	NC	50.9	NC	60.1	NC	NC	54.6	NC	57.3	52.6	59.7	56.4
PME-E 4103 K12 in l/s	49.7	67.4	76.6	42.9	64.7	56.8	76.9	NC	49.1	73.8	67.7	NC	NC	53.1	NC	62.3	NC	NC	56.8	NC	59.5	54.8	61.9	58.6
PME-E 4104 K12 in l/s	54.4	72.7	82.2	47.4	70.1	61.9	82.6	NC	54.0	79.7	73.6	NC	NC	58.7	NC	67.9	NC	NC	61.6	NC	64.3	59.6	66.7	63.4
PME-E 4803 K12 in l/s	58.0	78.7	89.5	50.1	75.5	66.2	89.7	NC	57.3	86.1	79.9	NC	NC	62.1	NC	71.3	NC	NC	65.0	NC	67.7	63.0	70.1	66.8
PME-E 4804 K12 in l/s	63.4	84.9	95.9	55.3	81.8	72.2	96.4	NC	63.0	93.0	86.8	NC	NC	67.7	NC	76.9	NC	NC	70.8	NC	73.5	68.8	75.9	72.6
PME-E 5703 K12 in l/s	70.7	95.9	108.9	61.0	92.0	80.7	109.3	NC	69.8	104.9	98.7	NC	NC	74.7	NC	83.9	NC	NC	77.6	NC	80.3	75.6	82.7	79.4
PME-E 5704 K12 in l/s	77.3	103.4	116.9	67.4	99.6	88.0	117.5	NC	76.8	113.3	107.1	NC	NC	81.8	NC	91.0	NC	NC	84.7	NC	87.4	82.7	89.8	86.5
PME-E 6203 K12 in l/s	76.9	104.3	118.5	66.4	100.1	87.7	118.8	NC	75.9	114.1	107.9	NC	NC	80.8	NC	90.0	NC	NC	83.7	NC	86.4	81.7	88.8	85.5
PME-E 6204 K12 in l/s	84.1	112.4	127.1	73.3	108.4	95.7	127.8	NC	83.5	123.2	117.0	NC	NC	88.4	NC	97.6	NC	NC	90.5	NC	93.2	88.5	95.6	92.3
PME-E 6703 K12 in l/s	83.1	112.7	128.1	71.7	108.1	94.8	128.4	NC	82.0	123.3	117.1	NC	NC	86.9	NC	96.1	NC	NC	89.0	NC	91.7	87.0	94.1	90.8
PME-E 6704 K12 in l/s	90.9	121.5	137.4	79.2	117.1	103.4	138.1	NC	90.3	133.1	126.9	NC	NC	95.2	NC	104.4	NC	NC	97.3	NC	100.0	95.3	102.4	99.1
PME-E 7203 K12 in l/s	89.3	121.1	137.6	77.1	116.2	101.9	138.0	NC	88.1	132.5	126.3	NC	NC	93.4	NC	102.6	NC	NC	95.5	NC	98.2	93.5	100.6	97.3
PME-E 7204 K12 in l/s	97.6	130.6	147.6	85.1	125.8	111.1	148.4	NC	97.0	143.1	136.9	NC	NC	102.0	NC	111.2	NC	NC	104.1	NC	106.8	102.1	109.2	105.9