

**Rosemex ROS/D Selection R2**

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28
ROD-821D in m3/h	31.6	44.5	51.4	26.7	42.3	36.1	50.8	58.7	30.5	48.5	41.4	58.4	67.5	35.0	55.8	45.5	64.2	74.2	38.6	61.5	52.7	74.4	86.0	44.7	71.3
ROD-821P in m3/h	35.0	49.3	56.9	29.5	46.8	39.9	56.3	65.0	33.8	53.7	45.8	64.7	74.7	38.8	61.8	50.4	71.1	82.2	42.7	68.0	58.3	82.3	95.2	49.5	78.9
ROD-821G in m3/h	39.1	55.1	63.6	33.0	52.4	44.6	62.9	72.7	37.7	60.0	51.2	72.3	83.6	43.4	69.1	56.3	79.5	91.9	47.8	76.1	65.2	92.1	106.4	55.3	88.3
ROD-822D in m3/h	39.9	56.2	64.8	33.6	53.4	45.5	64.2	74.1	38.5	61.2	52.2	73.7	85.2	44.2	70.4	57.4	81.1	93.7	48.7	77.6	66.4	93.8	108.5	56.4	90.0
ROD-822P in m3/h	44.4	62.5	72.2	37.5	59.4	50.7	71.4	82.5	42.8	68.1	58.1	82.0	94.8	49.2	78.4	63.9	90.2	104.3	54.2	86.3	74.0	104.5	120.8	62.8	100.1
ROD-822G in m3/h	49.6	69.9	80.7	41.9	66.5	56.7	79.9	92.3	47.9	76.2	65.0	91.8	106.1	55.1	87.7	71.5	100.9	116.7	60.6	96.6	82.7	116.8	135.1	70.2	112.0
ROD-832D in m3/h	55.7	78.4	90.5	47.0	74.5	63.5	89.6	103.5	53.7	85.4	72.9	102.9	118.9	61.7	98.3	80.2	113.2	130.8	68.0	108.3	92.8	131.0	151.5	78.8	125.6
ROD-832P in m3/h	60.2	84.8	97.8	50.8	80.6	68.7	96.8	111.9	58.1	92.3	78.8	111.2	128.6	66.8	106.3	86.7	122.4	141.4	73.5	117.1	100.3	141.6	163.7	85.1	135.8
ROD-832G in m3/h	68.5	96.4	111.3	57.8	91.7	78.1	110.2	127.3	66.1	105.0	89.7	126.5	146.2	75.9	120.9	98.6	139.2	160.9	83.6	133.2	114.1	161.1	186.3	96.9	154.5
ROD-842D in m3/h	79.0	111.2	128.4	66.7	105.8	90.1	127.1	146.8	76.2	121.2	103.5	146.0	168.7	87.6	139.5	113.8	160.6	185.6	96.4	153.7	131.6	185.9	214.9	111.8	178.2
ROD-842P in m3/h	90.3	127.1	146.8	76.2	120.9	103.0	145.3	167.8	87.1	138.5	118.3	166.9	192.9	100.1	159.4	130.0	183.5	212.1	110.2	175.6	150.4	212.4	245.6	127.7	203.7
ROD-842G in m3/h	99.7	140.4	162.0	84.1	133.5	113.8	160.4	185.3	96.2	152.9	130.6	184.3	212.9	110.6	176.0	143.6	202.7	234.2	121.7	193.9	166.1	234.6	271.2	141.0	224.9
ROD-852D in m3/h	85.8	120.8	139.4	72.4	114.8	97.9	138.0	159.4	82.7	131.6	112.4	158.5	183.2	95.1	151.5	123.5	174.4	201.5	104.7	166.8	142.9	201.8	233.3	121.3	193.5
ROD-852P in m3/h	97.0	136.7	157.8	81.9	129.9	110.8	156.2	180.4	93.6	148.9	127.1	179.4	207.3	107.6	171.4	139.8	197.3	228.1	118.5	188.8	161.7	228.4	264.0	137.3	219.0
ROD-852G in m3/h	108.3	152.6	176.1	91.4	145.1	123.6	174.3	201.4	104.5	166.2	141.9	200.2	231.4	120.2	191.3	156.0	220.2	254.6	132.3	210.7	180.5	254.9	294.7	153.3	244.4
ROD-854D in m3/h	131.3	184.9	213.4	110.8	175.8	149.8	211.2	244.0	126.7	201.4	172.0	242.7	280.4	145.6	231.8	189.1	266.9	308.5	160.3	255.4	218.8	308.9	357.2	185.7	296.2
ROD-854P in m3/h	141.8	199.7	230.5	119.7	189.9	161.8	228.2	263.6	136.8	217.5	185.8	262.1	302.9	157.3	250.4	204.3	288.3	333.2	173.1	275.8	236.3	333.7	385.8	200.6	320.0
ROD-854G in m3/h	149.7	210.8	243.4	126.3	200.5	170.9	240.9	278.3	144.4	229.7	196.1	276.7	319.8	166.1	264.4	215.6	304.4	351.8	182.8	291.2	249.5	352.3	407.3	211.8	337.8
ROD-873D in m3/h	144.8	203.9	235.4	122.2	193.9	165.3	233.0	269.2	139.7	222.2	189.7	267.7	309.4	160.6	255.8	208.6	294.4	340.3	176.8	281.7	241.3	340.8	394.0	204.9	326.7
ROD-873P in m3/h	154.2	217.2	250.7	130.2	206.5	176.0	248.2	286.7	148.8	236.6	202.0	285.1	329.5	171.1	272.4	222.1	313.5	362.4	188.3	300.0	257.0	362.9	419.6	218.2	348.0
ROD-873U in m3/h	164.7	232.0	267.8	139.0	220.6	188.0	265.1	306.2	159.0	252.7	215.8	304.5	352.0	182.7	291.0	237.3	335.0	387.2	201.1	320.5	274.6	387.7	448.3	233.1	371.7
ROD-873U in m3/h	182.4	256.9	296.6	154.0	244.3	208.2	293.6	339.1	176.0	279.9	239.0	337.2	389.7	202.4	322.2	262.8	370.9	428.7	222.7	354.9	304.0	429.3	496.4	258.1	411.6
ROD-873L in m3/h	194.8	274.4	316.7	164.4	260.9	222.4	313.5	362.2	188.0	298.9	255.3	360.2	416.2	216.1	344.1	280.6	396.1	457.9	237.9	379.0	324.7	458.5	530.1	275.7	439.6
ROD-873G in m3/h	208.4	293.5	338.8	175.9	279.0	237.8	335.3	387.4	201.1	319.7	273.0	385.2	445.2	231.1	368.0	300.2	423.7	489.7	254.4	405.4	347.3	490.4	567.0	294.8	470.2
ROD-874P in m3/h	188.8	265.9	307.0	159.4	252.8	215.5	303.9	351.0	182.2	289.7	247.4	349.0	403.4	209.4	333.5	272.0	383.9	443.7	230.5	367.3	314.7	444.4	513.8	267.1	426.0
ROD-874U in m3/h	209.5	295.1	340.6	176.8	280.5	239.1	337.1	389.5	202.1	321.4	274.5	387.3	447.6	232.4	370.0	301.8	426.0	492.3	255.8	407.6	349.2	493.1	570.0	296.4	472.7
ROD-874L in m3/h	224.9	316.8	365.7	189.8	301.2	256.7	362.0	418.1	217.0	345.1	294.7	415.8	480.5	249.5	397.2	324.0	457.3	528.6	274.6	437.5	374.9	529.3	612.0	318.2	507.5
ROD-874G in m3/h	239.6	337.4	389.5	202.2	320.8	273.4	385.6	445.4	231.2	367.6	313.9	442.9	511.9	265.8	423.2	345.1	487.1	563.1	292.5	466.1	399.3	563.9	651.9	339.0	540.6
ROD-875P in m3/h	231.3	325.8	376.1	195.2	309.8	264.0	372.2	430.0	223.2	354.9	303.1	427.6	494.2	256.6	408.5	333.2	470.3	543.6	282.4	450.0	385.5	544.4	629.4	327.3	521.9
ROD-875U in m3/h	248.2	349.6	403.6	209.5	332.4	283.3	399.5	461.5	239.5	380.8	325.2	458.9	530.3	275.4	438.4	357.6	504.7	583.4	303.1	482.9	413.7	584.2	675.5	351.2	560.1
ROD-875L in m3/h	263.7	371.3	428.6	222.5	353.1	300.9	424.3	490.1	254.4	404.5	345.4	487.4	563.3	292.5	465.7	379.8	536.1	619.6	321.9	512.9	439.4	620.5	717.4	373.0	594.9
ROD-875G in m3/h	282.8	398.4	459.8	238.7	378.8	322.8	455.2	525.8	272.9	433.9	370.6	522.9	604.3	313.8	499.5	407.4	575.1	664.7	345.4	550.2	471.4	665.7	769.6	400.2	638.2
ROD-893D in m3/h	159.9	225.1	259.9	134.9	214.1	182.4	257.2	297.2	154.2	245.2	209.4	295.5	341.5	177.3	282.3	230.3	325.0	375.7	195.2	311.0	266.4	376.2	435.0	226.2	360.7
ROD-893P in m3/h	171.5	241.6	278.8	144.8	229.7	195.8	276.0	318.8	165.5	263.1	224.7	317.1	366.4	190.3	302.9	247.1	348.7	403.1	209.4	333.6	285.9	403.6	466.7	242.7	387.0
ROD-893S in m3/h	182.8	257.5	297.2	154.3	244.8	208.6	294.2	339.8	176.4	280.4	239.5	337.9	390.5	202.8	322.8	263.3	371.7	429.6	223.2	355.6	304.7	430.2	497.4	258.6	412.5
ROD-893U in m3/h	201.6	283.9	327.8	170.2	270.0	230.1	324.4	374.8	194.5	309.3	264.1	372.7	430.7	223.6	356.1	290.4	409.9	473.8	246.2	392.2	336.0	474.5	548.6	285.2	454.9
ROD-893L in m3/h	216.3	304.6	351.6	182.5	289.6	246.8	348.0	402.0	208.7	331.8	283.3	399.8	462.0	239.9	382.0	311.5	439.7	508.3	264.1	420.7	360.4	509.0	588.5	306.0	488.0
ROD-893G in m3/h	229.4	323.1	373.0	193.6	307.2	261.9	369.2	426.5	221.4	352.0	300.6	424.1	490.2	254.5	405.2										

**Rosemex ROS/D Selection R2**

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28
ROS-713P in m3/h	23.3	32.8	37.9	19.7	31.2	26.6	37.5	43.4	22.5	35.8	30.6	43.1	49.8	25.9	41.2	33.6	47.4	54.8	28.5	45.4	38.9	54.9	63.5	33.0	52.6
ROS-713G in m3/h	26.0	36.6	42.2	21.9	34.8	29.6	41.8	48.2	25.0	39.8	34.0	48.0	55.4	28.8	45.8	37.4	52.8	61.0	31.7	50.5	43.3	61.1	70.6	36.7	58.6
ROS-723D in m3/h	24.8	35.0	40.4	21.0	33.2	28.3	39.9	46.1	24.0	38.1	32.5	45.9	53.0	27.5	43.8	35.8	50.5	58.3	30.3	48.3	41.4	58.4	67.5	35.1	56.0
ROS-723P in m3/h	27.1	38.1	44.0	22.9	36.3	30.9	43.6	50.3	26.1	41.5	35.5	50.1	57.9	30.0	47.8	39.0	55.1	63.6	33.1	52.7	45.1	63.7	73.7	38.3	61.1
ROS-723G in m3/h	31.2	44.0	50.8	26.3	41.8	35.6	50.2	58.0	30.1	47.9	40.9	57.7	66.7	34.6	55.1	45.0	63.5	73.4	38.1	60.7	52.0	73.5	84.9	44.2	70.4
ROS-734D in m3/h	29.7	41.8	48.3	25.1	39.8	33.9	47.8	55.2	28.7	45.6	38.9	54.9	63.5	33.0	52.5	42.8	60.4	69.8	36.3	57.8	49.5	69.9	80.9	42.0	67.0
ROS-734P in m3/h	33.9	47.7	55.0	28.6	45.3	38.6	54.5	62.9	32.7	51.9	44.3	62.6	72.3	37.5	59.8	48.8	68.8	79.6	41.3	65.9	56.4	79.7	92.1	47.9	76.4
ROS-734G in m3/h	37.6	53.0	61.1	31.7	50.4	42.9	60.5	69.9	36.3	57.7	49.3	69.5	80.4	41.7	66.4	54.2	76.5	88.4	45.9	73.2	62.7	88.5	102.3	53.2	84.9
ROS-744D in m3/h	42.1	59.3	68.5	35.6	56.4	48.1	67.8	78.3	40.6	64.6	55.2	77.9	90.0	46.7	74.4	60.7	85.7	99.0	51.4	81.9	70.2	99.1	114.6	59.6	95.1
ROS-744P in m3/h	47.0	66.2	76.4	39.7	63.0	53.7	75.7	87.4	45.4	72.1	61.6	86.9	100.4	52.2	83.0	67.7	95.6	110.5	57.4	91.5	78.4	110.6	127.9	66.5	106.1
ROS-744G in m3/h	53.8	75.8	87.4	45.4	72.0	61.4	86.6	100.0	51.9	82.5	70.5	99.4	114.9	59.7	95.0	77.5	109.4	126.4	65.7	104.6	89.6	126.6	146.3	76.1	121.4

**Rosemex ROS/D Selection R2**

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	24	24	27	27	27	27	27	29	29	29	29	29	32.2	32.2	32.2	32.2	32.2	21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	5	5.56	5	5
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.2	44.2	45.2	44.2	47.2	32	35.00	37	37
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.2	38.2	39.2	36.2	39.2	27	29.44	32	32
ROD-821D in m3/h	61.2	86.4	99.9	52.0	83.0	71.3	100.8	116.5	60.7	97.0	79.2	111.8	129.4	67.5	107.8	93.9	132.6	153.4	80.2	128.1	84.2	67.7	96.4	84
ROD-821P in m3/h	67.7	95.7	110.6	57.6	91.9	79.0	111.6	129.0	67.3	107.4	87.7	123.8	143.2	74.7	119.4	103.9	146.8	169.8	88.8	141.8	93.3	74.9	106.8	93
ROD-821G in m3/h	75.7	107.0	123.7	64.4	102.8	88.3	124.8	144.3	75.2	120.1	98.0	138.5	160.2	83.6	133.5	116.2	164.1	189.9	99.3	158.6	104.3	83.8	119.4	104
ROD-822D in m3/h	77.2	109.0	126.1	65.6	104.7	90.0	127.2	147.1	76.7	122.4	99.9	141.1	163.3	85.2	136.0	118.5	167.3	193.6	101.2	161.6	106.3	85.4	121.7	106
ROD-822P in m3/h	85.9	121.4	140.4	73.1	116.6	100.2	141.5	163.7	85.3	136.2	111.2	157.1	181.7	94.8	151.4	131.9	186.2	215.5	112.6	179.9	118.3	95.1	135.5	118
ROD-822G in m3/h	96.1	135.8	157.0	81.7	130.4	112.1	158.3	183.1	95.5	152.4	124.4	175.8	203.3	106.1	169.4	147.5	208.3	241.0	126.0	201.2	132.4	106.4	151.5	132
ROD-832D in m3/h	107.8	152.2	176.1	91.6	146.2	125.7	177.5	205.3	107.0	170.9	139.5	197.1	227.9	118.9	189.9	165.4	233.6	270.2	141.3	225.6	148.4	119.2	169.9	148
ROD-832P in m3/h	116.5	164.6	190.3	99.1	158.1	135.9	191.9	222.0	115.7	184.7	150.8	213.0	246.4	128.6	205.3	178.8	252.5	292.2	152.7	243.9	160.5	128.9	183.7	160
ROD-832G in m3/h	132.5	187.2	216.5	112.7	179.8	154.6	218.3	252.5	131.6	210.1	171.6	242.3	280.3	146.3	233.6	203.4	287.3	332.3	173.7	277.5	182.5	146.6	209.0	182
ROD-842D in m3/h	152.9	216.0	249.8	130.0	207.5	178.3	251.9	291.4	151.9	242.5	198.0	279.6	323.4	168.8	269.5	234.7	331.4	383.4	200.4	320.2	210.6	169.2	241.1	210
ROD-842P in m3/h	174.8	246.9	285.5	148.6	237.2	203.8	287.9	333.0	173.6	277.1	226.3	319.5	369.6	192.9	308.0	268.2	378.8	438.2	229.1	365.9	240.7	193.4	275.5	240
ROD-842G in m3/h	193.0	272.6	315.2	164.1	261.9	225.1	317.9	367.7	191.6	306.0	249.8	352.8	408.1	213.0	340.1	296.2	418.2	483.9	252.9	404.0	265.8	213.5	304.2	265
ROD-852D in m3/h	166.0	234.5	271.2	141.2	225.3	193.6	273.5	316.3	164.9	263.3	214.9	303.6	351.2	183.2	292.6	254.8	359.9	416.3	217.6	347.6	228.7	183.7	261.8	228
ROD-852P in m3/h	187.9	265.4	306.9	159.7	254.9	219.1	309.5	358.0	186.6	297.9	243.2	343.5	397.4	207.3	331.1	288.3	407.2	471.1	246.2	393.3	258.7	207.9	296.2	258
ROD-852G in m3/h	209.7	296.2	342.6	178.3	284.6	244.6	345.5	399.6	208.3	332.5	271.5	383.5	443.6	231.5	369.6	321.9	454.6	525.9	274.9	439.1	288.8	232.1	330.7	288
ROD-854D in m3/h	254.2	359.0	415.2	216.1	344.9	296.4	418.6	484.2	252.4	403.0	329.0	464.7	537.5	280.5	447.9	390.0	550.8	637.3	333.1	532.1	350.0	281.2	400.7	349
ROD-854P in m3/h	274.5	387.8	448.5	233.4	372.5	320.2	452.2	523.1	272.6	433.3	355.4	502.0	580.6	303.0	483.8	421.3	595.0	688.4	359.8	574.8	378.1	303.8	432.8	377
ROD-854G in m3/h	289.8	409.4	473.4	246.4	393.3	338.0	477.4	552.2	287.8	459.6	375.2	529.9	613.0	319.9	510.8	444.8	628.2	726.7	379.9	606.8	399.1	320.7	456.9	398
ROD-873D in m3/h	280.4	396.0	458.0	238.4	380.4	327.0	461.8	534.2	278.4	444.5	362.9	512.6	593.0	309.4	494.1	430.3	607.6	703.0	367.5	587.0	386.1	310.2	442.0	385
ROD-873P in m3/h	298.6	421.7	487.7	253.9	405.2	348.2	491.8	568.9	296.5	473.4	386.5	545.9	631.5	329.5	526.2	458.2	647.1	748.6	391.3	625.1	411.2	330.4	470.7	410
ROD-873U in m3/h	319.0	450.5	521.0	271.2	432.8	372.0	525.4	607.7	316.8	505.7	412.9	583.2	674.6	352.0	562.1	489.5	691.3	799.8	418.0	667.8	439.3	352.9	502.9	438
ROD-873U in m3/h	353.2	498.9	576.9	300.3	479.3	411.9	581.8	672.9	350.7	560.0	475.2	645.8	747.0	389.8	622.4	542.0	765.5	885.6	462.9	739.4	486.4	390.8	556.8	485
ROD-873L in m3/h	377.2	532.8	616.2	320.7	511.9	439.9	621.4	718.7	374.6	598.1	488.3	689.7	797.8	416.3	664.8	578.9	817.6	945.8	494.4	789.7	519.5	417.4	594.7	518
ROD-873G in m3/h	403.4	569.8	659.0	343.0	547.4	470.5	664.5	768.7	400.6	639.7	522.3	737.6	853.3	445.2	711.0	619.1	874.4	1011.6	528.7	844.6	555.6	446.4	636.1	554
ROD-874P in m3/h	365.6	516.4	597.2	310.8	496.1	426.3	602.2	696.5	363.0	579.6	473.2	668.4	773.2	403.4	644.2	561.0	792.3	916.6	479.1	765.3	503.4	404.5	576.3	502
ROD-874U in m3/h	405.6	572.9	662.6	344.9	550.4	473.0	668.1	772.8	402.8	643.1	525.1	741.6	857.9	447.6	714.8	622.5	879.1	1017.1	531.6	849.2	558.6	448.8	639.5	557
ROD-874L in m3/h	435.5	615.1	711.4	370.3	590.9	507.9	717.3	829.7	432.5	690.5	563.7	796.2	921.0	480.6	767.4	668.3	943.8	1091.9	570.7	911.7	599.7	481.8	686.6	598
ROD-874G in m3/h	463.9	655.2	757.7	394.4	629.5	541.0	764.1	883.8	460.7	735.5	600.5	848.1	981.1	511.9	817.5	711.9	1005.4	1163.1	608.0	971.2	638.8	513.3	731.3	637
ROD-875P in m3/h	447.9	632.6	731.6	380.8	607.7	522.3	737.7	853.3	444.8	710.1	579.8	818.8	947.2	494.3	789.3	687.3	970.7	1123.0	587.0	937.6	616.8	495.5	706.1	615
ROD-875U in m3/h	480.6	678.9	785.1	408.7	652.2	560.5	791.7	915.7	477.3	762.1	622.2	878.8	1016.5	530.4	847.0	737.6	1041.7	1205.1	629.9	1006.2	661.9	531.8	757.7	660
ROD-875L in m3/h	510.5	721.0	833.9	434.0	692.7	595.3	840.9	972.6	507.0	809.4	660.8	933.4	1079.7	563.4	899.6	783.4	1106.4	1280.0	669.0	1068.7	703.0	564.8	804.8	701
ROD-875G in m3/h	547.6	773.5	894.5	465.6	743.1	638.6	902.1	1043.4	543.8	868.3	708.9	1001.3	1158.2	604.4	965.1	840.4	1186.9	1373.1	717.7	1146.5	754.2	605.9	863.4	752
ROD-893D in m3/h	309.5	437.1	505.6	263.1	420.0	360.9	509.8	589.7	307.4	490.7	400.7	565.9	654.6	341.6	545.4	475.0	670.8	776.0	405.6	647.9	426.2	342.4	487.9	425
ROD-893P in m3/h	332.1	469.0	542.4	282.3	450.6	387.3	547.0	632.7	329.8	526.5	429.9	607.1	702.3	366.5	585.2	509.6	719.7	832.6	435.2	695.2	457.3	367.4	523.5	456
ROD-893S in m3/h	353.9	499.9	578.1	300.9	480.3	412.7	583.0	674.3	351.5	561.2	458.2	647.1	748.5	390.6	623.7	543.1	767.1	887.4	463.8	740.9	487.4	391.6	558.0	486
ROD-893U in m3/h	390.3	551.3	637.6	331.9	529.7	455.2	643.0	743.7	387.6	618.9	505.3	713.7	825.5	430.8	687.9	599.0	846.0	978.7	511.6	817.2	537.5	431.9	615.4	536
ROD-893L in m3/h	418.7	591.4	684.0	356.0	568.2	488.3	689.7	793.8	415.8	663.9	542.1	765.6	885.6	462.1	737.9	642.6	907.5	1049.9	548.8	876.6	576.7	463.3	660.2	575
ROD-893G in m3/h	444.2	627.4	725.6	377.7	602.8	518.0	731.7	846.4	441.1	704.3	575.1	812.2	939.5	490.2	782.8	681.7	962.8	1113.8	582.2	930.0	611.8	491.5	700.3	610
ROD-894P in m3/h	450.1	635.7	735.1	382.6	610.7	524.8	741.3	857.5	446.9	713.6	582.6	822.8	951.8	496.7	793.1	690.7	9							

**Rosemex ROS/D Selection R2**

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	24	24	27	27	27	27	27	29	29	29	29	29	32.2	32.2	32.2	32.2	32.2	21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	5	5.56	5	5
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.2	44.2	45.2	44.2	47.2	32	35.00	37	37
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.2	38.2	39.2	36.2	39.2	27	29.44	32	32
ROS-713P in m3/h	45.2	63.8	73.8	38.4	61.3	52.7	74.4	86.0	44.8	71.6	58.4	82.6	95.5	49.8	79.6	69.3	97.9	113.2	59.2	94.5	62.2	50.0	71.2	62
ROS-713G in m3/h	50.2	71.0	82.1	42.7	68.2	58.6	82.8	95.7	49.9	79.7	65.0	91.9	106.3	55.5	88.6	77.1	108.9	126.0	65.9	105.2	69.2	55.6	79.2	69
ROS-723D in m3/h	48.1	67.9	78.5	40.9	65.2	56.1	79.2	91.6	47.7	76.2	62.2	87.9	101.7	53.0	84.7	73.8	104.2	120.5	63.0	100.6	66.2	53.2	75.8	66
ROS-723P in m3/h	52.4	74.1	85.6	44.6	71.1	61.1	86.4	99.9	52.1	83.1	67.9	95.9	110.9	57.9	92.4	80.5	113.6	131.5	68.7	109.8	72.2	58.0	82.7	72
ROS-723G in m3/h	60.4	85.4	98.7	51.4	82.0	70.5	99.6	115.2	60.0	95.8	78.2	110.5	127.8	66.7	106.5	92.8	131.0	151.6	79.2	126.5	83.2	66.9	95.3	83
ROS-734D in m3/h	57.5	81.3	94.0	48.9	78.1	67.1	94.8	109.6	57.1	91.2	74.5	105.2	121.7	63.5	101.4	88.3	124.7	144.2	75.4	120.4	79.2	63.7	90.7	79
ROS-734P in m3/h	65.5	92.6	107.1	55.7	88.9	76.4	108.0	124.9	65.1	103.9	84.8	119.8	138.6	72.3	115.5	100.6	142.0	164.3	85.9	137.2	90.3	72.5	103.3	90
ROS-734G in m3/h	72.8	102.9	119.0	61.9	98.8	84.9	120.0	138.7	72.3	115.5	94.3	133.1	154.0	80.4	128.3	111.8	157.8	182.6	95.4	152.5	100.3	80.6	114.8	100
ROS-744D in m3/h	81.6	115.2	133.2	69.3	110.7	95.1	134.3	155.4	81.0	129.3	105.6	149.1	172.5	90.0	143.7	125.2	176.8	204.5	106.9	170.8	112.3	90.2	128.6	112
ROS-744P in m3/h	91.0	128.6	148.7	77.4	123.5	106.2	149.9	173.4	90.4	144.3	117.8	166.4	192.5	100.5	160.4	139.7	197.3	228.2	119.3	190.6	125.4	100.7	143.5	125
ROS-744G in m3/h	104.1	147.1	170.1	88.5	141.3	121.4	171.5	198.4	103.4	165.1	134.8	190.4	220.2	114.9	183.5	159.8	225.7	261.1	136.5	218.0	143.4	115.2	164.2	143