



无锡方舟流体科技有限公司
Wuxi ARK Fluid Science Technology Co.,Ltd.

WUXI ARK FLUID SCIENCE TECHNOLOGY CO., LTD.

No.58 Xinfeng Rd,New District, Wuxi City, Jiangshu Province, China.

TEL: +86 510-8855 2288

FAX: +86 510-8115 2626

URL: <http://www.wxark.cn>

MAIL: 199601@wxark.cn



FBF SERIES Closed Cooling Tower(Mixed Flow)

Design Information





I. Outline of models

(Closed type, Mixed Flow, and induced draft)

Models	Water rate (m ³ /h)	Fan		Spray pump		Diameter of host machine (mm)			Outline dimension (mm)			Weight	
	37-32 208	Power kw	Air flow m ³ /h	Power kw	Flow rate m ³ /h	Inlet and outlet	Make up	Overflow and Drain	Length (L)	Width (W)	Height (H)	Weight of host machine kg	Operating weight kg
FBF-103A	16	1.5	25600	0.75	20	80	32	40	2000	1500	2700	920	2230
FBF-104A	24	2.2	38400	0.75	30	80	32	40	2300	1700	3000	1200	2960
FBF-105A	32	3	51200	1.1	40	100	32	40	2600	1900	3200	1380	3200
FBF-106A	40	4.4	64000	1.5	50	100	32	40	3100	1900	3300	1720	3980
FBF-107A	52	6	83200	1.5	65	125	32	40	3300	2300	3400	2280	5330
FBF-108A	64	8	102400	2.2	80	125	40	40	3300	2500	3500	2800	7150
FBF-110A	80	8	128000	2.2	100	150	40	40	3600	2900	3500	3110	7780
FBF-212A	100	11	160000	4	125	125×2	40	40	2600	4900	3500	3250	7970
FBF-215A	120	11	192000	4	150	125×2	40	40	3100	5100	3600	3320	9050
FBF-217A	140	15	224000	5.5	175	125×2	40	40	3100	5700	3900	3550	9450
FBF-220A	161	15	256000	4×2	200	150×2	40	40	3300	6000	4200	5420	10200
FBF-222A	181	18.5	288000	4×2	225	150×2	40	40	3600	6300	4400	6280	12740
FBF-225A	201	22	320000	4×2	250	150×2	50	80	3600	6600	4400	7860	16400
FBF-230A	241	30	384000	5.5×2	300	200×2	50	80	4200	7300	4700	11790	20660
FBF-232A	281	30	448000	5.5×2	350	200×2	50	80	4200	7700	5300	12800	22800
FBF-234A	322	37	512000	5.5×2	400	200×2	50	80	4200	8200	5300	13200	23600



* Significance of the model names:

FBF	-	110A
Mixed flow, Closed Cooling tower		Model Code

II. Drawings:

