

Wuxi Fangzhou FNB R1, 2016

| Condition Reference #       | 1     | 2     | 3     | 4    | 5     | 6     | 7     | 8     | 9     | 10    | 11    | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20    | 21    | 22    | 23    | 24    | 25    |
|-----------------------------|-------|-------|-------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Wet Bulb °C                 | 10    | 10    | 10    | 10   | 10    | 13    | 13    | 13    | 13    | 13    | 16    | 16    | 16    | 16    | 16    | 18    | 18    | 18    | 18    | 18    | 21    | 21    | 21    | 21    | 21    |
| Range °C                    | 6     | 6     | 6     | 8    | 8     | 6     | 6     | 6     | 8     | 8     | 6     | 6     | 6     | 8     | 8     | 6     | 6     | 6     | 8     | 8     | 6     | 6     | 6     | 8     | 8     |
| Approach °C                 | 4     | 6     | 7     | 4    | 7     | 4     | 6     | 7     | 4     | 7     | 4     | 6     | 7     | 4     | 7     | 4     | 6     | 7     | 4     | 7     | 4     | 6     | 7     | 4     | 7     |
| Inlet Water Temperature °C  | 20    | 22    | 23    | 22   | 25    | 23    | 25    | 26    | 25    | 28    | 26    | 28    | 29    | 28    | 31    | 28    | 30    | 31    | 30    | 33    | 31    | 33    | 34    | 33    | 36    |
| Outlet Water Temperature °C | 14    | 16    | 17    | 14   | 17    | 17    | 19    | 20    | 17    | 20    | 20    | 22    | 23    | 20    | 23    | 22    | 24    | 25    | 22    | 25    | 25    | 27    | 28    | 25    | 28    |
| FNB-5 in m3/h               | 1.7   | 2.4   | 2.8   | 1.4  | 2.3   | 1.9   | 2.7   | 3.1   | 1.6   | 2.6   | 2.2   | 3.1   | 3.6   | 1.9   | 3.0   | 2.4   | 3.4   | 4.0   | 2.1   | 3.3   | 2.8   | 4.0   | 4.6   | 2.4   | 3.8   |
| FNB-10 in m3/h              | 3.4   | 4.8   | 5.5   | 2.9  | 4.5   | 3.9   | 5.4   | 6.3   | 3.3   | 5.2   | 4.4   | 6.3   | 7.2   | 3.8   | 6.0   | 4.9   | 6.9   | 8.0   | 4.1   | 6.6   | 5.6   | 8.0   | 9.2   | 4.8   | 7.6   |
| FNB-20 in m3/h              | 6.8   | 9.5   | 11.0  | 5.7  | 9.1   | 7.7   | 10.9  | 12.6  | 6.5   | 10.4  | 8.9   | 12.5  | 14.5  | 7.5   | 12.0  | 9.8   | 13.8  | 15.9  | 8.3   | 13.2  | 11.3  | 15.9  | 18.4  | 9.6   | 15.3  |
| FNB-30 in m3/h              | 11.0  | 15.5  | 17.9  | 9.3  | 14.7  | 12.5  | 17.7  | 20.4  | 10.6  | 16.8  | 14.4  | 20.3  | 23.5  | 12.2  | 19.4  | 15.8  | 22.3  | 25.8  | 13.4  | 21.4  | 18.3  | 25.8  | 29.9  | 15.5  | 24.8  |
| FNB-40 in m3/h              | 14.4  | 20.3  | 23.4  | 12.2 | 19.3  | 16.4  | 23.2  | 26.8  | 13.9  | 22.1  | 18.9  | 26.6  | 30.8  | 16.0  | 25.4  | 20.8  | 29.3  | 33.9  | 17.6  | 28.0  | 24.0  | 33.9  | 39.2  | 20.4  | 32.5  |
| FNB-50 in m3/h              | 17.0  | 24.0  | 27.7  | 14.4 | 22.8  | 19.4  | 27.4  | 31.7  | 16.4  | 26.1  | 22.3  | 31.5  | 36.4  | 18.9  | 30.1  | 24.5  | 34.6  | 40.0  | 20.8  | 33.1  | 28.4  | 40.1  | 46.4  | 24.1  | 38.4  |
| FNB-65 in m3/h              | 22.5  | 31.7  | 36.6  | 19.0 | 30.1  | 25.7  | 36.2  | 41.8  | 21.7  | 34.5  | 29.5  | 41.6  | 48.1  | 24.9  | 39.7  | 32.4  | 45.7  | 52.9  | 27.5  | 43.8  | 37.5  | 52.9  | 61.2  | 31.8  | 50.8  |
| FNB-80 in m3/h              | 31.5  | 44.3  | 51.2  | 26.6 | 42.2  | 35.9  | 50.7  | 58.5  | 30.4  | 48.3  | 41.2  | 58.2  | 67.3  | 34.9  | 55.6  | 45.3  | 64.0  | 74.0  | 38.4  | 61.2  | 52.5  | 74.1  | 85.7  | 44.5  | 71.0  |
| FNB-100 in m3/h             | 36.0  | 50.7  | 58.5  | 30.4 | 48.2  | 41.1  | 57.9  | 66.9  | 34.7  | 55.2  | 47.2  | 66.5  | 76.9  | 39.9  | 63.6  | 51.8  | 73.2  | 84.6  | 43.9  | 70.0  | 60.0  | 84.7  | 97.9  | 50.9  | 81.2  |
| FNB-125 in m3/h             | 45.0  | 63.4  | 73.1  | 38.0 | 60.2  | 51.3  | 72.4  | 83.6  | 43.4  | 69.0  | 58.9  | 83.2  | 96.1  | 49.9  | 79.4  | 64.8  | 91.5  | 105.7 | 54.9  | 87.5  | 75.0  | 105.9 | 122.4 | 63.6  | 101.5 |
| FNB-150 in m3/h             | 54.0  | 76.1  | 87.8  | 45.6 | 72.3  | 61.6  | 86.9  | 100.4 | 52.1  | 82.9  | 70.8  | 99.8  | 115.4 | 59.9  | 95.4  | 77.8  | 109.8 | 126.9 | 65.9  | 105.1 | 90.0  | 127.1 | 147.0 | 76.4  | 121.9 |
| FNB-200 in m3/h             | 72.0  | 101.4 | 117.0 | 60.8 | 96.4  | 82.2  | 115.9 | 133.8 | 69.5  | 110.4 | 94.3  | 133.1 | 153.8 | 79.9  | 127.1 | 103.7 | 146.4 | 169.2 | 87.9  | 140.0 | 120.0 | 169.4 | 195.9 | 101.9 | 162.4 |
| FNB-250 in m3/h             | 90.0  | 126.8 | 146.3 | 76.0 | 120.5 | 102.7 | 144.8 | 167.3 | 86.8  | 138.1 | 117.9 | 166.4 | 192.3 | 99.8  | 159.0 | 129.7 | 183.0 | 211.5 | 109.9 | 175.1 | 150.0 | 211.8 | 244.9 | 127.3 | 203.1 |
| FNB-300 in m3/h             | 108.0 | 152.1 | 175.6 | 91.1 | 144.6 | 123.2 | 173.8 | 200.7 | 104.2 | 165.7 | 141.5 | 199.6 | 230.7 | 119.8 | 190.7 | 155.5 | 219.6 | 253.8 | 131.8 | 210.1 | 180.0 | 254.1 | 293.8 | 152.8 | 243.7 |

| Condition Reference #       | 1    | 2    | 3    | 4    | 5    | 6    | 7    | 8    | 9    | 10   | 11   | 12   | 13   | 14   | 15   | 16   | 17   | 18   | 19   | 20   | 21   | 22   | 23   | 24   | 25   |
|-----------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| Wet Bulb °C                 | 10   | 10   | 10   | 10   | 10   | 13   | 13   | 13   | 13   | 13   | 16   | 16   | 16   | 16   | 16   | 18   | 18   | 18   | 18   | 18   | 21   | 21   | 21   | 21   | 21   |
| Range °C                    | 6    | 6    | 6    | 8    | 8    | 6    | 6    | 6    | 8    | 8    | 6    | 6    | 6    | 8    | 8    | 6    | 6    | 6    | 8    | 8    | 6    | 6    | 6    | 8    | 8    |
| Approach °C                 | 4    | 6    | 7    | 4    | 7    | 4    | 6    | 7    | 4    | 7    | 4    | 6    | 7    | 4    | 7    | 4    | 6    | 7    | 4    | 7    | 4    | 6    | 7    | 4    | 7    |
| Inlet Water Temperature °C  | 20   | 22   | 23   | 22   | 25   | 23   | 25   | 26   | 25   | 28   | 26   | 28   | 29   | 28   | 31   | 28   | 30   | 31   | 30   | 33   | 31   | 33   | 34   | 33   | 36   |
| Outlet Water Temperature °C | 14   | 16   | 17   | 14   | 17   | 17   | 19   | 20   | 17   | 20   | 20   | 22   | 23   | 20   | 23   | 22   | 24   | 25   | 22   | 25   | 25   | 27   | 28   | 25   | 28   |
| FNB-5 in l/s                | 0.5  | 0.7  | 0.8  | 0.4  | 0.6  | 0.5  | 0.8  | 0.9  | 0.5  | 0.7  | 0.6  | 0.9  | 1.0  | 0.5  | 0.8  | 0.7  | 1.0  | 1.1  | 0.6  | 0.9  | 0.8  | 1.1  | 1.3  | 0.7  | 1.1  |
| FNB-10 in l/s               | 0.9  | 1.3  | 1.5  | 0.8  | 1.3  | 1.1  | 1.5  | 1.7  | 0.9  | 1.4  | 1.2  | 1.7  | 2.0  | 1.0  | 1.7  | 1.4  | 1.9  | 2.2  | 1.1  | 1.8  | 1.6  | 2.2  | 2.6  | 1.3  | 2.1  |
| FNB-20 in l/s               | 1.9  | 2.6  | 3.1  | 1.6  | 2.5  | 2.1  | 3.0  | 3.5  | 1.8  | 2.9  | 2.5  | 3.5  | 4.0  | 2.1  | 3.3  | 2.7  | 3.8  | 4.4  | 2.3  | 3.7  | 3.1  | 4.4  | 5.1  | 2.7  | 4.2  |
| FNB-30 in l/s               | 3.1  | 4.3  | 5.0  | 2.6  | 4.1  | 3.5  | 4.9  | 5.7  | 2.9  | 4.7  | 4.0  | 5.6  | 6.5  | 3.4  | 5.4  | 4.4  | 6.2  | 7.2  | 3.7  | 5.9  | 5.1  | 7.2  | 8.3  | 4.3  | 6.9  |
| FNB-40 in l/s               | 4.0  | 5.6  | 6.5  | 3.4  | 5.4  | 4.6  | 6.4  | 7.4  | 3.9  | 6.1  | 5.2  | 7.4  | 8.5  | 4.4  | 7.1  | 5.8  | 8.1  | 9.4  | 4.9  | 7.8  | 6.7  | 9.4  | 10.9 | 5.7  | 9.0  |
| FNB-50 in l/s               | 4.7  | 6.7  | 7.7  | 4.0  | 6.3  | 5.4  | 7.6  | 8.8  | 4.6  | 7.3  | 6.2  | 8.7  | 10.1 | 5.3  | 8.4  | 6.8  | 9.6  | 11.1 | 5.8  | 9.2  | 7.9  | 11.1 | 12.9 | 6.7  | 10.7 |
| FNB-65 in l/s               | 6.2  | 8.8  | 10.2 | 5.3  | 8.4  | 7.1  | 10.1 | 11.6 | 6.0  | 9.6  | 8.2  | 11.5 | 13.3 | 6.9  | 11.0 | 9.0  | 12.7 | 14.7 | 7.6  | 12.2 | 10.4 | 14.7 | 17.0 | 8.8  | 14.1 |
| FNB-80 in l/s               | 8.7  | 12.3 | 14.2 | 7.4  | 11.7 | 10.0 | 14.1 | 16.3 | 8.4  | 13.4 | 11.5 | 16.2 | 18.7 | 9.7  | 15.4 | 12.6 | 17.8 | 20.6 | 10.7 | 17.0 | 14.6 | 20.6 | 23.8 | 12.4 | 19.7 |
| FNB-100 in l/s              | 10.0 | 14.1 | 16.3 | 8.4  | 13.4 | 11.4 | 16.1 | 18.6 | 9.6  | 15.3 | 13.1 | 18.5 | 21.4 | 11.1 | 17.7 | 14.4 | 20.3 | 23.5 | 12.2 | 19.5 | 16.7 | 23.5 | 27.2 | 14.1 | 22.6 |
| FNB-125 in l/s              | 12.5 | 17.6 | 20.3 | 10.5 | 16.7 | 14.3 | 20.1 | 23.2 | 12.1 | 19.2 | 16.4 | 23.1 | 26.7 | 13.9 | 22.1 | 18.0 | 25.4 | 29.4 | 15.3 | 24.3 | 20.8 | 29.4 | 34.0 | 17.7 | 28.2 |
| FNB-150 in l/s              | 15.0 | 21.1 | 24.4 | 12.7 | 20.1 | 17.1 | 24.1 | 27.9 | 14.5 | 23.0 | 19.7 | 27.7 | 32.1 | 16.6 | 26.5 | 21.6 | 30.5 | 35.3 | 18.3 | 29.2 | 25.0 | 35.3 | 40.8 | 21.2 | 33.9 |
| FNB-200 in l/s              | 20.0 | 28.2 | 32.5 | 16.9 | 26.8 | 22.8 | 32.2 | 37.2 | 19.3 | 30.7 | 26.2 | 37.0 | 42.7 | 22.2 | 35.3 | 28.8 | 40.7 | 47.0 | 24.4 | 38.9 | 33.3 | 47.1 | 54.4 | 28.3 | 45.1 |
| FNB-250 in l/s              | 25.0 | 35.2 | 40.6 | 21.1 | 33.5 | 28.5 | 40.2 | 46.5 | 24.1 | 38.4 | 32.8 | 46.2 | 53.4 | 27.7 | 44.2 | 36.0 | 50.8 | 58.8 | 30.5 | 48.6 | 41.7 | 58.8 | 68.0 | 35.4 | 56.4 |
| FNB-300 in l/s              | 30.0 | 42.2 | 48.8 | 25.3 | 40.2 | 34.2 | 48.3 | 55.8 | 28.9 | 46.0 | 39.3 | 55.4 | 64.1 | 33.3 | 53.0 | 43.2 | 61.0 | 70.5 | 36.6 | 58.4 | 50.0 | 70.6 | 81.6 | 42.4 | 67.7 |

Wuxi Fangzhou FNB R1, 2016

| Condition Reference #       | 26    | 27    | 28    | 29    | 30    | 31    | 32    | 33    | 34    | 35    | 36    | 37    | 38    | 39    | 40    | 41    | 42    | 43    | 44    | 45    | 46    | 47    | 48    | 49    |
|-----------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Wet Bulb °C                 | 24    | 24    | 24    | 24    | 24    | 27    | 27    | 27    | 27    | 27    | 29    | 29    | 29    | 29    | 29    | 32.2  | 32.2  | 32.2  | 32.2  | 32.2  | 21    | 25.56 | 27    | 28    |
| Range °C                    | 6     | 6     | 6     | 8     | 8     | 6     | 6     | 6     | 8     | 8     | 6     | 6     | 8     | 8     | 8     | 6     | 6     | 6     | 8     | 8     | 5     | 5.56  | 5     | 5     |
| Approach °C                 | 4     | 6     | 7     | 4     | 7     | 4     | 6     | 7     | 4     | 7     | 4     | 6     | 7     | 4     | 7     | 4     | 6     | 7     | 4     | 7     | 6     | 3.89  | 5     | 4     |
| Inlet Water Temperature °C  | 34    | 36    | 37    | 36    | 39    | 37    | 39    | 40    | 39    | 42    | 39    | 41    | 42    | 41    | 44    | 42.2  | 44.2  | 45.2  | 44.2  | 47.2  | 32    | 35.00 | 37    | 37    |
| Outlet Water Temperature °C | 28    | 30    | 31    | 28    | 31    | 31    | 33    | 34    | 31    | 34    | 33    | 35    | 36    | 33    | 36    | 36.2  | 38.2  | 39.2  | 36.2  | 39.2  | 27    | 29.44 | 32    | 32    |
| FNB-5 in m3/h               | 3.3   | 4.6   | 5.4   | 2.8   | 4.4   | 3.8   | 5.4   | 6.2   | 3.3   | 5.2   | 4.2   | 6.0   | 6.9   | 3.6   | 5.8   | 5.0   | 7.1   | 8.2   | 4.3   | 6.9   | 4.5   | 3.6   | 5.2   | 4.5   |
| FNB-10 in m3/h              | 6.6   | 9.3   | 10.7  | 5.6   | 8.9   | 7.6   | 10.8  | 12.5  | 6.5   | 10.4  | 8.5   | 12.0  | 13.9  | 7.2   | 11.6  | 10.1  | 14.2  | 16.4  | 8.6   | 13.7  | 9.0   | 7.3   | 10.3  | 9.0   |
| FNB-20 in m3/h              | 13.1  | 18.5  | 21.4  | 11.1  | 17.8  | 15.3  | 21.6  | 25.0  | 13.0  | 20.8  | 17.0  | 24.0  | 27.7  | 14.5  | 23.1  | 20.1  | 28.4  | 32.9  | 17.2  | 27.4  | 18.1  | 14.5  | 20.7  | 18.0  |
| FNB-30 in m3/h              | 21.3  | 30.0  | 34.7  | 18.1  | 28.9  | 24.8  | 35.0  | 40.5  | 21.1  | 33.7  | 27.5  | 38.9  | 45.0  | 23.5  | 37.5  | 32.6  | 46.1  | 53.3  | 27.9  | 44.5  | 29.3  | 23.5  | 33.5  | 29.2  |
| FNB-40 in m3/h              | 27.9  | 39.4  | 45.6  | 23.7  | 37.8  | 32.5  | 45.9  | 53.1  | 27.7  | 44.2  | 36.1  | 51.0  | 59.0  | 30.8  | 49.2  | 42.8  | 60.4  | 69.9  | 36.6  | 58.4  | 38.4  | 30.9  | 44.0  | 38.3  |
| FNB-50 in m3/h              | 33.0  | 46.6  | 53.9  | 28.0  | 44.8  | 38.5  | 54.3  | 62.9  | 32.8  | 52.3  | 42.7  | 60.3  | 69.8  | 36.4  | 58.1  | 50.6  | 71.5  | 82.7  | 43.2  | 69.1  | 45.4  | 36.5  | 52.0  | 45.3  |
| FNB-65 in m3/h              | 43.5  | 61.5  | 71.1  | 37.0  | 59.1  | 50.8  | 71.7  | 83.0  | 43.2  | 69.0  | 56.4  | 79.6  | 92.1  | 48.1  | 76.7  | 66.8  | 94.4  | 109.2 | 57.1  | 91.2  | 60.0  | 48.2  | 68.7  | 59.8  |
| FNB-80 in m3/h              | 61.0  | 86.1  | 99.6  | 51.8  | 82.7  | 71.1  | 100.4 | 116.1 | 60.5  | 96.6  | 78.9  | 111.4 | 128.9 | 67.3  | 107.4 | 93.5  | 132.1 | 152.8 | 79.9  | 127.6 | 83.9  | 67.4  | 96.1  | 83.7  |
| FNB-100 in m3/h             | 69.7  | 98.4  | 113.8 | 59.3  | 94.6  | 81.3  | 114.8 | 132.8 | 69.2  | 110.5 | 90.2  | 127.4 | 147.4 | 76.9  | 122.8 | 107.0 | 151.0 | 174.7 | 91.3  | 145.9 | 96.0  | 77.1  | 109.9 | 95.7  |
| FNB-125 in m3/h             | 87.1  | 123.0 | 142.3 | 74.1  | 118.2 | 101.6 | 143.5 | 165.9 | 86.5  | 138.1 | 112.7 | 159.2 | 184.2 | 96.1  | 153.5 | 133.7 | 188.8 | 218.4 | 114.1 | 182.3 | 119.9 | 96.4  | 137.3 | 119.6 |
| FNB-150 in m3/h             | 104.6 | 147.7 | 170.8 | 88.9  | 141.9 | 122.0 | 172.3 | 199.2 | 103.9 | 165.8 | 135.4 | 191.2 | 221.2 | 115.4 | 184.3 | 160.5 | 226.6 | 262.2 | 137.1 | 218.9 | 144.0 | 115.7 | 164.9 | 143.6 |
| FNB-200 in m3/h             | 139.4 | 196.9 | 227.7 | 118.5 | 189.1 | 162.5 | 229.6 | 265.6 | 138.4 | 221.0 | 180.4 | 254.8 | 294.8 | 153.8 | 245.6 | 213.9 | 302.1 | 349.5 | 182.7 | 291.8 | 191.9 | 154.2 | 219.7 | 191.4 |
| FNB-250 in m3/h             | 174.3 | 246.1 | 284.7 | 148.2 | 236.5 | 203.2 | 287.1 | 332.0 | 173.1 | 276.3 | 225.6 | 318.6 | 368.6 | 192.3 | 307.1 | 267.4 | 377.7 | 436.9 | 228.4 | 364.8 | 240.0 | 192.8 | 274.7 | 239.3 |
| FNB-300 in m3/h             | 209.1 | 295.3 | 341.5 | 177.8 | 283.7 | 243.8 | 344.4 | 398.3 | 207.6 | 331.5 | 270.7 | 382.3 | 442.2 | 230.7 | 368.5 | 320.9 | 453.1 | 524.2 | 274.0 | 437.7 | 287.9 | 231.3 | 329.6 | 287.1 |

| Condition Reference #       | 26   | 27   | 28   | 29   | 30   | 31   | 32   | 33    | 34   | 35   | 36   | 37    | 38    | 39   | 40    | 41   | 42    | 43    | 44   | 45    | 46   | 47    | 48   | 49   |
|-----------------------------|------|------|------|------|------|------|------|-------|------|------|------|-------|-------|------|-------|------|-------|-------|------|-------|------|-------|------|------|
| Wet Bulb °C                 | 24   | 24   | 24   | 24   | 24   | 27   | 27   | 27    | 27   | 27   | 29   | 29    | 29    | 29   | 29    | 32.2 | 32.2  | 32.2  | 32.2 | 32.2  | 21   | 25.56 | 27   | 28   |
| Range °C                    | 6    | 6    | 6    | 8    | 8    | 6    | 6    | 6     | 8    | 8    | 6    | 6     | 8     | 8    | 8     | 6    | 6     | 6     | 8    | 8     | 5    | 5.56  | 5    | 5    |
| Approach °C                 | 4    | 6    | 7    | 4    | 7    | 4    | 6    | 7     | 4    | 7    | 4    | 6     | 7     | 4    | 7     | 4    | 6     | 7     | 4    | 7     | 6    | 3.89  | 5    | 4    |
| Inlet Water Temperature °C  | 34   | 36   | 37   | 36   | 39   | 37   | 39   | 40    | 39   | 42   | 39   | 41    | 42    | 41   | 44    | 42.2 | 44.2  | 45.2  | 44.2 | 47.2  | 32   | 35.00 | 37   | 37   |
| Outlet Water Temperature °C | 28   | 30   | 31   | 28   | 31   | 31   | 33   | 34    | 31   | 34   | 33   | 35    | 36    | 33   | 36    | 36.2 | 38.2  | 39.2  | 36.2 | 39.2  | 27   | 29.44 | 32   | 32   |
| FNB-5 in l/s                | 0.9  | 1.3  | 1.5  | 0.8  | 1.2  | 1.1  | 1.5  | 1.7   | 0.9  | 1.4  | 1.2  | 1.7   | 1.9   | 1.0  | 1.6   | 1.4  | 2.0   | 2.3   | 1.2  | 1.9   | 1.3  | 1.0   | 1.4  | 1.3  |
| FNB-10 in l/s               | 1.8  | 2.6  | 3.0  | 1.5  | 2.5  | 2.1  | 3.0  | 3.5   | 1.8  | 2.9  | 2.4  | 3.3   | 3.9   | 2.0  | 3.2   | 2.8  | 3.9   | 4.6   | 2.4  | 3.8   | 2.5  | 2.0   | 2.9  | 2.5  |
| FNB-20 in l/s               | 3.6  | 5.1  | 5.9  | 3.1  | 4.9  | 4.2  | 6.0  | 6.9   | 3.6  | 5.8  | 4.7  | 6.7   | 7.7   | 4.0  | 6.4   | 5.6  | 7.9   | 9.1   | 4.8  | 7.6   | 5.0  | 4.0   | 5.7  | 5.0  |
| FNB-30 in l/s               | 5.9  | 8.3  | 9.6  | 5.0  | 8.0  | 6.9  | 9.7  | 11.3  | 5.9  | 9.4  | 7.6  | 10.8  | 12.5  | 6.5  | 10.4  | 9.1  | 12.8  | 14.8  | 7.7  | 12.4  | 8.1  | 6.5   | 9.3  | 8.1  |
| FNB-40 in l/s               | 7.7  | 10.9 | 12.7 | 6.6  | 10.5 | 9.0  | 12.8 | 14.8  | 7.7  | 12.3 | 10.0 | 14.2  | 16.4  | 8.6  | 13.7  | 11.9 | 16.8  | 19.4  | 10.2 | 16.2  | 10.7 | 8.6   | 12.2 | 10.6 |
| FNB-50 in l/s               | 9.2  | 12.9 | 15.0 | 7.8  | 12.4 | 10.7 | 15.1 | 17.5  | 9.1  | 14.5 | 11.9 | 16.8  | 19.4  | 10.1 | 16.1  | 14.1 | 19.9  | 23.0  | 12.0 | 19.2  | 12.6 | 10.1  | 14.4 | 12.6 |
| FNB-65 in l/s               | 12.1 | 17.1 | 19.8 | 10.3 | 16.4 | 14.1 | 19.9 | 23.0  | 12.0 | 19.2 | 15.7 | 22.1  | 25.6  | 13.3 | 21.3  | 18.6 | 26.2  | 30.3  | 15.9 | 25.3  | 16.7 | 13.4  | 19.1 | 16.6 |
| FNB-80 in l/s               | 16.9 | 23.9 | 27.7 | 14.4 | 23.0 | 19.7 | 27.9 | 32.3  | 16.8 | 26.8 | 21.9 | 31.0  | 35.8  | 18.7 | 29.8  | 26.0 | 36.7  | 42.5  | 22.2 | 35.4  | 23.3 | 18.7  | 26.7 | 23.3 |
| FNB-100 in l/s              | 19.4 | 27.3 | 31.6 | 16.5 | 26.3 | 22.6 | 31.9 | 36.9  | 19.2 | 30.7 | 25.1 | 35.4  | 40.9  | 21.4 | 34.1  | 29.7 | 42.0  | 48.5  | 25.4 | 40.5  | 26.7 | 21.4  | 30.5 | 26.6 |
| FNB-125 in l/s              | 24.2 | 34.2 | 39.5 | 20.6 | 32.8 | 28.2 | 39.9 | 46.1  | 24.0 | 38.4 | 31.3 | 44.2  | 51.2  | 26.7 | 42.6  | 37.1 | 52.4  | 60.7  | 31.7 | 50.6  | 33.3 | 26.8  | 38.1 | 33.2 |
| FNB-150 in l/s              | 29.0 | 41.0 | 47.4 | 24.7 | 39.4 | 33.9 | 47.8 | 55.3  | 28.8 | 46.1 | 37.6 | 53.1  | 61.4  | 32.1 | 51.2  | 44.6 | 63.0  | 72.8  | 38.1 | 60.8  | 40.0 | 32.1  | 45.8 | 39.9 |
| FNB-200 in l/s              | 38.7 | 54.7 | 63.2 | 32.9 | 52.5 | 45.2 | 63.8 | 73.8  | 38.4 | 61.4 | 50.1 | 70.8  | 81.9  | 42.7 | 68.2  | 59.4 | 83.9  | 97.1  | 50.7 | 81.1  | 53.3 | 42.8  | 61.0 | 53.2 |
| FNB-250 in l/s              | 48.4 | 68.4 | 79.1 | 41.2 | 65.7 | 56.5 | 79.7 | 92.2  | 48.1 | 76.8 | 62.7 | 88.5  | 102.4 | 53.4 | 85.3  | 74.3 | 104.9 | 121.4 | 63.4 | 101.3 | 66.7 | 53.6  | 76.3 | 66.5 |
| FNB-300 in l/s              | 58.1 | 82.0 | 94.9 | 49.4 | 78.8 | 67.7 | 95.7 | 110.7 | 57.7 | 92.1 | 75.2 | 106.2 | 122.8 | 64.1 | 102.3 | 89.1 | 125.9 | 145.6 | 76.1 | 121.6 | 80.0 | 64.3  | 91.6 | 79.8 |