



**Yantai Ebara Air Conditioning Equipment Co.Ltd**

No.720,Yongda Road,Fushan High-tech Industrial Zone,Yantai ,Shandong Province

TEL: +86-0535-6988668

FAX: +86-0535-6325372

URL: <http://www.ytebara.com.cn/>

MAIL: [market@ytebara.com.cn](mailto:market@ytebara.com.cn)



## **CXW Cross-Flow Induced-draft Cooling Tower**

### Design Information





**Selection Tables**

Wet Bulb Tem.°C	13°C					14°C																							
	6			8		4				5					6					7				8					
Range°C																													
Approach °C	4	6	7	4	7	4	5	6	7	3	4	5	6	7	3	4	5	6	7	4	5	6	7	4	5	6	7		
Inlet water tem.°C	23	25	26	25	28	22	23	24	25	22	23	24	25	26	23	24	25	26	27	25	26	27	28	26	27	28	29		
Outlet water tem.°C	17	19	20	17	20	18	19	20	21	17	18	19	20	21	17	18	19	20	21	18	19	20	21	18	19	20	21		
CXW-35ASSW*1	14.6	20.6	23.8	12.3	19.6	20.0	24.3	28.9	33.6	13.7	17.2	20.7	24.5	28.4	12.3	15.3	18.3	21.5	24.9	13.9	16.6	19.5	22.4	12.9	15.4	17.9	20.6		
CXW-40ASSW*1	16.3	23.0	26.6	13.8	21.9	22.3	27.2	32.3	37.6	15.3	19.2	23.2	27.3	31.7	13.8	17.1	20.5	24.1	27.8	15.6	18.6	21.7	25.0	14.4	17.2	20.0	23.0		
CXW-55ASSW*1	22.8	32.1	37.1	19.2	30.6	31.1	37.9	45.0	52.5	21.4	26.7	32.3	38.1	44.2	19.2	23.8	28.6	33.6	38.8	21.7	25.9	30.3	34.9	20.1	24.0	27.9	32.0		
CXW-65ASSW*1	27.9	39.3	45.4	23.6	37.5	38.2	46.5	55.2	64.3	26.2	32.8	39.6	46.8	54.3	23.5	29.2	35.1	41.2	47.6	26.6	31.8	37.2	42.8	24.7	29.4	34.2	39.3		
CXW-70ASSW*1	30.0	42.4	48.9	25.4	40.4	41.1	50.1	59.4	69.3	28.2	35.3	42.7	50.4	58.4	25.3	31.4	37.8	44.3	51.2	28.7	34.3	40.1	46.1	26.6	31.6	36.9	42.3		
CXW-80ASSW*1	34.3	48.4	55.9	29.0	46.2	47.0	57.2	67.9	79.2	32.2	40.4	48.8	57.6	66.8	29.0	35.9	43.2	50.7	58.6	32.8	39.2	45.8	52.7	30.4	36.2	42.1	48.4		
CXW-90ASSW*1	38.6	54.5	62.9	32.7	51.9	52.8	64.4	76.4	89.1	36.3	45.4	54.9	64.8	75.1	32.6	40.4	48.6	57.0	65.9	36.9	44.0	51.5	59.3	34.2	40.7	47.4	54.4		
CXW-100ASSW*1	42.9	60.5	69.9	36.3	57.7	58.7	71.5	84.9	99.0	40.3	50.4	61.0	72.0	83.5	36.2	44.9	53.9	63.4	73.2	41.0	48.9	57.2	65.9	38.0	45.2	52.7	60.4		
CXW-110ASSW*1	47.2	66.6	76.9	39.9	63.5	64.6	78.7	93.4	108.9	44.3	55.5	67.1	79.1	91.8	39.8	49.4	59.3	69.7	80.5	45.1	53.8	63.0	72.5	41.8	49.7	57.9	66.5		
CXW-120ASSW*1	51.5	72.6	83.9	43.5	69.2	70.5	85.8	101.9	118.8	48.4	60.5	73.2	86.3	100.2	43.4	53.9	64.7	76.0	87.8	49.2	58.7	68.7	79.1	45.6	54.2	63.2	72.5		
CXW-130ASSW*1	55.8	78.7	90.9	47.2	75.0	76.3	93.0	110.4	128.7	52.4	65.6	79.3	93.5	108.5	47.1	58.4	70.1	82.4	95.1	53.3	63.6	74.4	85.7	49.4	58.7	68.4	78.6		
CXW-140ASSW*1	60.1	84.7	97.9	50.8	80.8	82.2	100.1	118.9	138.6	56.4	70.6	85.4	100.7	116.9	50.7	62.9	75.5	88.7	102.5	57.4	68.5	80.1	92.2	53.2	63.3	73.7	84.6		
CXW-150ASSW*1	64.4	90.8	104.9	54.4	86.6	88.1	107.3	127.4	148.5	60.5	75.7	91.4	107.9	125.2	54.3	67.4	80.9	95.0	109.8	61.5	73.4	85.8	98.8	57.0	67.8	79.0	90.7		
CXW-160ASSW*1	68.7	96.8	111.9	58.1	92.3	93.9	114.4	135.9	158.3	64.5	80.7	97.5	115.1	133.5	57.9	71.9	86.3	101.4	117.1	65.6	78.3	91.6	105.4	60.8	72.3	84.2	96.7		
CXW-350ASSW*1	147.7	208.2	240.5	124.8	198.5	202.0	246.0	292.1	340.4	138.7	173.5	209.7	247.5	287.1	124.5	154.5	185.6	217.9	251.8	141.0	168.4	196.9	226.7	130.7	155.5	181.1	207.9		
CXW-400ASSW*1	177.3	250.0	288.8	149.9	238.3	242.5	295.4	350.7	408.7	166.5	208.3	251.8	297.2	344.7	149.5	185.5	222.8	261.6	302.3	169.2	202.1	236.4	272.1	156.9	186.6	217.5	249.6		



CXW-450ASSW*1	191.9	270.6	312.5	162.2	257.9	262.5	319.7	379.6	442.4	180.2	225.5	272.5	321.6	373.1	161.8	200.8	241.2	283.2	327.2	183.2	218.8	255.8	294.5	169.9	202.0	235.4	270.2
CXW-500ASSW*1	214.6	302.6	349.6	181.5	288.5	293.6	357.6	424.6	494.8	201.5	252.2	304.8	359.8	417.3	181.0	224.6	269.7	316.8	366.0	204.9	244.7	286.2	329.4	190.0	225.9	263.3	302.2
CXW-550ASSW*1	239.5	337.7	390.2	202.5	322.0	327.6	399.1	473.8	552.2	224.9	281.5	340.2	401.5	465.7	202.0	250.7	301.0	353.5	408.4	228.6	273.1	319.4	367.7	212.1	252.2	293.8	337.3



Wet Bulb Tem. °C	16°C																					
Range °C	4				5					6					7				8			
Approach °C	4	5	6	7	3	4	5	6	7	3	4	5	6	7	4	5	6	7	4	5	6	7
Inlet water tem. °C	24	25	26	27	24	25	26	27	28	25	26	27	28	29	27	28	29	30	28	29	30	31
Outlet water tem. °C	20	21	22	23	19	20	21	22	23	19	20	21	22	23	20	21	22	23	20	21	22	23
CXW-35ASSW*1	21.9	26.7	31.7	36.9	15.1	18.9	22.8	26.8	31.2	13.5	16.8	20.1	23.7	27.4	15.3	18.3	21.4	24.6	14.2	16.9	19.7	22.6
CXW-40ASSW*1	24.5	29.8	35.4	41.2	16.8	21.1	25.4	30.0	34.8	15.1	18.8	22.5	26.4	30.6	17.1	20.5	23.9	27.5	15.9	18.9	22.0	25.2
CXW-55ASSW*1	34.1	41.6	49.3	57.5	23.5	29.4	35.5	41.8	48.6	21.1	26.2	31.4	36.9	42.7	23.9	28.5	33.3	38.4	22.1	26.3	30.7	35.2
CXW-65ASSW*1	41.9	51.0	60.5	70.5	28.8	36.0	43.5	51.3	59.6	25.8	32.1	38.5	45.2	52.3	29.3	35.0	40.9	47.1	27.1	32.3	37.6	43.2
CXW-70ASSW*1	45.1	54.9	65.2	75.9	31.0	38.8	46.9	55.2	64.1	27.8	34.6	41.5	48.7	56.3	31.6	37.7	44.0	50.7	29.2	34.7	40.5	46.5
CXW-80ASSW*1	51.5	62.7	74.5	86.8	35.5	44.4	53.5	63.1	73.3	31.8	39.5	47.4	55.7	64.4	36.1	43.1	50.3	58.0	33.4	39.7	46.3	53.1
CXW-90ASSW*1	58.0	70.6	83.8	97.6	39.9	49.9	60.2	71.0	82.5	35.8	44.4	53.3	62.6	72.4	40.6	48.5	56.6	65.2	37.5	44.7	52.1	59.8
CXW-100ASSW*1	64.4	78.4	93.1	108.5	44.3	55.5	66.9	78.9	91.6	39.7	49.4	59.2	69.6	80.5	45.1	53.8	62.9	72.4	41.7	49.6	57.9	66.4
CXW-110ASSW*1	70.8	86.3	102.4	119.3	48.7	61.0	73.6	86.8	100.8	43.7	54.3	65.2	76.5	88.5	49.6	59.2	69.2	79.7	45.9	54.6	63.6	73.1
CXW-120ASSW*1	77.3	94.1	111.7	130.2	53.2	66.5	80.3	94.6	109.9	47.7	59.2	71.1	83.5	96.6	54.1	64.6	75.5	86.9	50.1	59.6	69.4	79.7
CXW-130ASSW*1	83.7	101.9	121.0	141.0	57.6	72.1	87.0	102.5	119.1	51.6	64.2	77.0	90.4	104.6	58.7	70.0	81.8	94.2	54.2	64.5	75.2	86.4
CXW-140ASSW*1	90.2	109.8	130.4	151.9	62.0	77.6	93.7	110.4	128.3	55.6	69.1	82.9	97.4	112.7	63.2	75.4	88.1	101.4	58.4	69.5	81.0	93.0
CXW-150ASSW*1	96.6	117.6	139.7	162.7	66.5	83.2	100.4	118.3	137.4	59.6	74.1	88.9	104.4	120.7	67.7	80.8	94.4	108.7	62.6	74.4	86.8	99.6
CXW-160ASSW*1	103.1	125.5	149.0	173.6	70.9	88.7	107.1	126.2	146.6	63.6	79.0	94.8	111.3	128.8	72.2	86.2	100.7	115.9	66.8	79.4	92.6	106.3
CXW-350ASSW*1	221.6	269.7	320.3	373.2	152.5	190.8	230.3	271.3	315.2	136.7	169.8	203.8	239.3	276.9	155.2	185.2	216.4	249.2	143.5	170.7	199.0	228.5
CXW-400ASSW*1	266.0	323.9	384.5	448.1	183.0	229.0	276.4	325.8	378.4	164.1	203.9	244.7	287.3	332.4	186.3	222.4	259.8	299.2	172.3	205.0	238.9	274.4



CXW-450ASSW*1	287.9	350.5	416.2	485.0	198.1	247.9	299.2	352.6	409.5	177.6	220.7	264.8	311.0	359.8	201.7	240.7	281.2	323.8	186.5	221.9	258.6	296.9
CXW-500ASSW*1	322.0	392.1	465.6	542.5	221.6	277.3	334.7	394.4	458.1	198.6	246.8	296.2	347.9	402.4	225.6	269.2	314.6	362.2	208.6	248.2	289.3	332.1
CXW-550ASSW*1	359.4	437.6	519.6	605.4	247.3	309.4	373.5	440.1	511.2	221.7	275.5	330.6	388.2	449.1	251.8	300.5	351.1	404.2	232.8	276.9	322.8	370.7



Wet Bulb Tem. °C	18°C																					
Range °C	4				5					6					7				8			
Approach °C	4	5	6	7	3	4	5	6	7	3	4	5	6	7	4	5	6	7	4	5	6	7
Inlet water tem. °C	26	27	28	29	26	27	28	29	30	27	28	29	30	31	29	30	31	32	30	31	32	33
Outlet water tem. °C	22	23	24	25	21	22	23	24	25	21	22	23	24	25	22	23	24	25	22	23	24	25
CXW-35ASSW*1	24.0	29.2	34.7	40.5	16.5	20.7	25.0	29.5	34.2	14.9	18.4	22.2	26.0	30.1	16.8	20.1	23.5	27.1	15.6	18.6	21.7	24.9
CXW-40ASSW*1	26.9	32.7	38.8	45.3	18.5	23.1	27.9	33.0	38.3	16.6	20.6	24.8	29.1	33.6	18.8	22.5	26.3	30.3	17.5	20.8	24.2	27.8
CXW-55ASSW*1	37.5	45.6	54.2	63.2	25.7	32.3	38.9	46.0	53.4	23.2	28.7	34.6	40.5	46.9	26.2	31.4	36.7	42.2	24.3	29.0	33.8	38.8
CXW-65ASSW*1	46.0	55.9	66.4	77.5	31.6	39.6	47.8	56.4	65.4	28.4	35.2	42.4	49.7	57.5	32.2	38.5	45.0	51.8	29.9	35.5	41.4	47.6
CXW-70ASSW*1	49.5	60.2	71.5	83.4	34.0	42.6	51.4	60.8	70.5	30.6	37.9	45.6	53.5	62.0	34.6	41.5	48.5	55.8	32.1	38.2	44.6	51.2
CXW-80ASSW*1	56.6	68.8	81.7	95.3	38.9	48.7	58.8	69.4	80.6	35.0	43.3	52.2	61.2	70.8	39.6	47.4	55.4	63.7	36.7	43.7	51.0	58.5
CXW-90ASSW*1	63.7	77.4	92.0	107.3	43.7	54.8	66.1	78.1	90.6	39.4	48.8	58.7	68.8	79.7	44.5	53.3	62.3	71.7	41.3	49.2	57.3	65.9
CXW-100ASSW*1	70.7	86.0	102.2	119.2	48.6	60.8	73.5	86.8	100.7	43.7	54.2	65.2	76.5	88.5	49.5	59.2	69.2	79.7	45.9	54.6	63.7	73.2
CXW-110ASSW*1	77.8	94.6	112.4	131.1	53.4	66.9	80.8	95.5	110.8	48.1	59.6	71.7	84.1	97.4	54.4	65.2	76.2	87.6	50.5	60.1	70.1	80.5
CXW-120ASSW*1	84.9	103.2	122.6	143.0	58.3	73.0	88.2	104.2	120.8	52.5	65.0	78.3	91.8	106.2	59.4	71.1	83.1	95.6	55.1	65.6	76.4	87.8
CXW-130ASSW*1	91.9	111.8	132.8	154.9	63.1	79.1	95.5	112.8	130.9	56.9	70.4	84.8	99.4	115.1	64.3	77.0	90.0	103.6	59.7	71.0	82.8	95.1
CXW-140ASSW*1	99.0	120.4	143.1	166.8	68.0	85.2	102.9	121.5	141.0	61.2	75.9	91.3	107.0	123.9	69.3	82.9	96.9	111.5	64.3	76.5	89.2	102.4
CXW-150ASSW*1	106.1	129.0	153.3	178.8	72.8	91.3	110.2	130.2	151.0	65.6	81.3	97.8	114.7	132.8	74.2	88.9	103.8	119.5	68.9	82.0	95.5	109.8
CXW-160ASSW*1	113.2	137.6	163.5	190.7	77.7	97.4	117.6	138.9	161.1	70.0	86.7	104.3	122.3	141.6	79.2	94.8	110.8	127.5	73.5	87.4	101.9	117.1
CXW-350ASSW*1	243.3	295.8	351.5	410.0	167.1	209.3	252.8	298.6	346.4	150.5	186.4	224.3	263.0	304.5	170.2	203.8	238.2	274.1	158.0	188.0	219.1	251.7
CXW-400ASSW*1	292.1	355.2	422.0	492.2	200.6	251.3	303.5	358.5	415.8	180.7	223.8	269.3	315.8	365.6	204.4	244.7	285.9	329.1	189.7	225.7	263.1	302.2



CXW-450ASSW*1	316.1	384.4	456.8	532.7	217.1	272.0	328.5	388.0	450.1	195.5	242.2	291.5	341.8	395.7	221.2	264.8	309.5	356.2	205.3	244.2	284.7	327.1
CXW-500ASSW*1	353.6	430.0	510.9	595.9	242.8	304.2	367.4	434.0	503.4	218.7	270.9	326.1	382.3	442.6	247.4	296.2	346.2	398.4	229.6	273.2	318.5	365.8
CXW-550ASSW*1	394.6	479.8	570.2	665.0	271.0	339.5	410.0	484.3	561.8	244.1	302.3	363.9	426.7	493.9	276.1	330.6	386.3	444.6	256.3	304.9	355.4	408.3



Wet Bulb Tem.°C	20°C																											21°C						
Range°C	4				5					6					7					8					5	6			8					
Approach °C	4	5	6	7	3	4	5	6	7	8	3	4	5	6	7	8	4	5	6	7	8	9	4	5	6	7	8	9	6	4	6	7	4	7
Inlet water tem.°C	28	29	30	31	28	29	30	31	32	33	29	30	31	32	33	34	31	32	33	34	35	36	32	33	34	35	36	37	32	31	33	34	33	36
Outlet water tem.°C	24	25	26	27	23	24	25	26	27	28	23	24	25	26	27	28	24	25	26	27	28	29	24	25	26	27	28	29	27	25	27	28	25	28
CXW-35ASSW*1	26.4	32.2	38.2	44.6	18.2	22.8	27.5	32.5	37.7	43.2	16.4	20.3	24.4	28.7	33.1	37.8	18.6	22.2	26.0	29.9	34.0	38.4	17.2	20.5	23.9	27.4	31.2	35.1	34.1	21.3	30.1	34.8	18.1	28.9
CXW-40ASSW*1	29.5	35.9	42.7	49.9	20.3	25.4	30.8	36.3	42.1	48.3	18.3	22.7	27.3	32.0	37.0	42.3	20.8	24.8	29.0	33.4	38.0	42.9	19.2	22.9	26.7	30.7	34.9	39.2	38.1	23.8	33.6	38.9	20.2	32.2
CXW-55ASSW*1	41.2	50.1	59.6	69.6	28.4	35.5	42.9	50.6	58.8	67.3	25.5	31.7	38.0	44.7	51.7	59.0	29.0	34.6	40.5	46.6	53.0	59.8	26.8	31.9	37.2	42.8	48.6	54.7	53.2	33.2	46.9	54.3	28.2	45.0
CXW-65ASSW*1	50.5	61.5	73.1	85.3	34.8	43.5	52.6	62.1	72.1	82.5	31.3	38.9	46.6	54.8	63.4	72.3	35.5	42.4	49.6	57.2	65.0	73.4	32.9	39.2	45.7	52.5	59.6	67.1	65.2	40.7	57.5	66.6	34.6	55.2
CXW-70ASSW*1	54.4	66.2	78.7	91.9	37.5	46.9	56.7	66.9	77.6	88.9	33.7	41.9	50.2	59.0	68.2	77.9	38.3	45.6	53.4	61.6	70.0	79.0	35.5	42.2	49.2	56.5	64.2	72.3	70.2	43.9	62.0	71.7	37.3	59.4
CXW-80ASSW*1	62.2	75.7	89.9	105.0	42.8	53.5	64.8	76.4	88.7	101.6	38.5	47.9	57.4	67.4	78.0	89.0	43.7	52.2	61.1	70.4	80.0	90.3	40.5	48.2	56.2	64.6	73.4	82.6	80.3	50.1	70.8	81.9	42.6	67.9
CXW-90ASSW*1	70.0	85.1	101.2	118.1	48.2	60.2	72.8	86.0	99.8	114.3	43.3	53.8	64.6	75.8	87.7	100.1	49.2	58.7	68.7	79.2	90.1	101.6	45.6	54.2	63.2	72.7	82.5	92.9	90.3	56.4	79.7	92.2	47.9	76.4
CXW-100ASSW*1	77.7	94.6	112.4	131.2	53.5	66.9	80.9	95.5	110.9	127.0	48.1	59.8	71.8	84.3	97.5	111.3	54.6	65.2	76.3	87.9	100.1	112.9	50.6	60.3	70.3	80.7	91.7	103.2	100.3	62.7	88.5	102.4	53.2	84.9
CXW-110ASSW*1	85.5	104.1	123.6	144.4	58.9	73.6	89.0	105.1	122.0	139.7	52.9	65.8	78.9	92.7	107.2	122.4	60.1	71.7	84.0	96.7	110.1	124.1	55.7	66.3	77.3	88.8	100.9	113.5	110.4	69.0	97.4	112.7	58.5	93.4
CXW-120ASSW*1	93.3	113.5	134.9	157.5	64.2	80.3	97.1	114.6	133.1	152.4	57.7	71.8	86.1	101.1	117.0	133.5	65.6	78.3	91.6	105.5	120.1	135.4	60.8	72.3	84.3	96.9	110.1	123.9	120.4	75.2	106.2	122.9	63.9	101.8
CXW-130ASSW*1	101.0	123.0	146.1	170.6	69.6	87.0	105.2	124.2	144.2	165.1	62.5	77.8	93.3	109.6	126.7	144.6	71.0	84.8	99.3	114.3	130.1	146.7	65.8	78.3	91.4	105.0	119.2	134.2	130.4	81.5	115.1	133.1	69.2	110.3
CXW-140ASSW*1	108.8	132.4	157.4	183.7	74.9	93.7	113.3	133.7	155.3	177.8	67.3	83.7	100.5	118.0	136.5	155.8	76.5	91.3	106.9	123.1	140.1	158.0	70.9	84.4	98.4	113.0	128.4	144.5	140.5	87.8	123.9	143.4	74.5	118.8
CXW-150ASSW*1	116.6	141.9	168.6	196.8	80.3	100.4	121.4	143.3	166.4	190.5	72.2	89.7	107.6	126.4	146.2	166.9	82.0	97.8	114.5	131.9	150.1	169.3	76.0	90.4	105.4	121.1	137.6	154.8	150.5	94.0	132.8	153.6	79.8	127.3
CXW-160ASSW*1	124.4	151.4	179.8	210.0	85.6	107.1	129.5	152.8	177.5	203.2	77.0	95.7	114.8	134.8	156.0	178.0	87.4	104.3	122.2	140.7	160.1	180.6	81.0	96.4	112.4	129.2	146.7	165.2	160.6	100.3	141.6	163.9	85.1	135.8
CXW-350ASSW*1	267.4	325.4	386.7	451.4	184.0	230.3	278.4	328.6	381.5	436.8	165.5	205.8	246.8	289.9	335.3	382.7	188.0	224.3	262.6	302.5	344.2	388.2	174.2	207.3	241.7	277.7	315.5	355.1	345.2	215.6	304.5	352.3	183.1	291.9
CXW-400ASSW*1	321.0	390.7	464.2	542.0	221.0	276.4	334.3	394.5	458.0	524.4	198.7	247.0	296.4	348.0	402.6	459.5	225.7	269.3	315.3	363.2	413.2	466.1	209.2	248.9	290.2	333.4	378.8	426.3	414.4	258.9	365.6	423.0	219.8	350.5
CXW-450ASSW*1	347.4	422.9	502.4	586.6	239.2	299.2	361.8	427.0	495.8	567.6	215.0	267.4	320.8	376.7	435.7	497.3	244.3	291.5	341.3	393.1	447.3	504.5	226.4	269.4	314.1	360.9	409.9	461.4	448.5	280.2	395.7	457.8	237.9	379.4
CXW-500ASSW*1	388.6	473.0	562.0	656.1	267.5	334.7	404.7	477.6	554.5	634.9	240.5	299.1	358.8	421.4	487.4	556.3	273.2	326.1	381.7	439.7	500.3	564.3	253.2	301.3	351.4	403.7	458.6	516.1	501.7	313.4	442.6	512.1	266.1	424.3
CXW-550ASSW*1	433.7	527.9	627.2	732.3	298.5	373.5	451.7	533.0	618.9	708.6	268.4	333.8	400.4	470.2	543.9	620.8	304.9	363.9	426.0	490.7	558.3	629.8	282.6	336.3	392.1	450.5	511.7	576.0	559.9	349.8	493.9	571.5	296.9	473.6





Wet Bulb Tem. °C	22°C																											
Range °C	4				5					6					7					8								
Approach °C	4	5	6	7	3	4	5	6	7	8	3	4	5	6	7	8	4	5	6	7	8	9	4	5	6	7	8	9
Inlet water tem. °C	30	31	32	33	30	31	32	33	34	35	31	32	33	34	35	36	33	34	35	36	37	38	34	35	36	37	38	39
Outlet water tem. °C	26	27	28	29	25	26	27	28	29	30	25	26	27	28	29	30	26	27	28	29	30	31	26	27	28	29	30	31
CXW-35ASSW*1	29.1	35.5	42.1	49.1	20.1	25.1	30.3	35.8	41.6	47.7	18.1	22.4	26.9	31.7	36.6	41.8	20.5	24.5	28.7	33.0	37.6	42.4	19.0	22.7	26.4	30.4	34.5	38.8
CXW-40ASSW*1	32.5	39.7	47.1	54.9	22.4	28.1	33.9	40.1	46.5	53.3	20.2	25.0	30.1	35.4	40.9	46.7	22.9	27.4	32.0	36.9	42.0	47.4	21.3	25.3	29.5	33.9	38.5	43.4
CXW-55ASSW*1	45.4	55.3	65.7	76.6	31.3	39.1	47.3	55.9	64.9	74.3	28.2	34.9	42.0	49.3	57.0	65.1	31.9	38.2	44.7	51.5	58.6	66.1	29.7	35.4	41.2	47.3	53.7	60.5
CXW-65ASSW*1	55.7	67.8	80.5	94.0	38.4	48.0	58.0	68.5	79.6	91.1	34.6	42.8	51.5	60.5	69.9	79.9	39.2	46.8	54.8	63.1	71.9	81.1	36.4	43.4	50.5	58.1	65.9	74.2
CXW-70ASSW*1	60.0	73.1	86.7	101.2	41.3	51.7	62.4	73.8	85.7	98.1	37.2	46.1	55.5	65.2	75.3	86.0	42.2	50.4	59.0	68.0	77.4	87.3	39.2	46.7	54.4	62.5	71.0	79.9
CXW-80ASSW*1	68.5	83.5	99.1	115.6	47.2	59.1	71.4	84.3	97.9	112.1	42.5	52.7	63.4	74.5	86.1	98.3	48.2	57.6	67.4	77.7	88.5	99.8	44.8	53.4	62.2	71.5	81.1	91.3
CXW-90ASSW*1	77.1	93.9	111.5	130.1	53.1	66.4	80.3	94.9	110.1	126.2	47.8	59.3	71.3	83.8	96.8	110.6	54.2	64.8	75.8	87.4	99.5	112.3	50.4	60.0	70.0	80.4	91.3	102.8
CXW-100ASSW*1	85.6	104.4	123.9	144.5	59.0	73.8	89.2	105.4	122.4	140.2	53.2	65.9	79.2	93.1	107.6	122.8	60.3	72.0	84.3	97.1	110.6	124.7	56.0	66.7	77.7	89.3	101.4	114.2
CXW-110ASSW*1	94.2	114.8	136.3	159.0	64.9	81.2	98.1	115.9	134.6	154.2	58.5	72.5	87.1	102.4	118.3	135.1	66.3	79.2	92.7	106.8	121.6	137.2	61.6	73.4	85.5	98.3	111.5	125.6
CXW-120ASSW*1	102.8	125.2	148.7	173.5	70.8	88.6	107.0	126.5	146.9	168.2	63.8	79.1	95.1	111.7	129.1	147.4	72.3	86.4	101.1	116.6	132.7	149.7	67.2	80.0	93.3	107.2	121.7	137.0
CXW-130ASSW*1	111.3	135.7	161.0	187.9	76.7	96.0	116.0	137.0	159.1	182.2	69.1	85.7	103.0	121.0	139.9	159.7	78.4	93.6	109.6	126.3	143.7	162.2	72.8	86.7	101.0	116.1	131.8	148.4
CXW-140ASSW*1	119.9	146.1	173.4	202.4	82.6	103.4	124.9	147.6	171.3	196.3	74.4	92.3	110.9	130.4	150.6	172.0	84.4	100.8	118.0	136.0	154.8	174.6	78.4	93.4	108.8	125.1	142.0	159.8
CXW-150ASSW*1	128.5	156.5	185.8	216.8	88.5	110.7	133.8	158.1	183.6	210.3	79.7	98.9	118.8	139.7	161.4	184.3	90.4	108.0	126.4	145.7	165.8	187.1	84.0	100.1	116.6	134.0	152.1	171.3
CXW-160ASSW*1	137.0	167.0	198.2	231.3	94.4	118.1	142.7	168.6	195.8	224.3	85.1	105.4	126.8	149.0	172.1	196.6	96.4	115.2	134.8	155.4	176.9	199.6	89.6	106.7	124.4	142.9	162.2	182.7
CXW-350ASSW*1	294.6	359.0	426.1	497.2	203.0	254.0	306.9	362.6	421.0	482.2	182.9	226.7	272.5	320.3	370.1	422.6	207.3	247.6	289.9	334.1	380.3	429.1	192.7	229.5	267.4	307.3	348.8	392.7
CXW-400ASSW*1	353.7	431.0	511.6	597.0	243.7	304.9	368.4	435.3	505.5	579.0	219.5	272.2	327.2	384.5	444.3	507.4	248.9	297.3	348.0	401.1	456.6	515.2	231.4	275.5	321.0	368.9	418.8	471.5



CXW-450ASSW*1	382.8	466.5	553.7	646.1	263.8	330.0	398.8	471.1	547.1	626.6	237.6	294.6	354.1	416.2	480.9	549.1	269.4	321.8	376.7	434.2	494.2	557.6	250.4	298.2	347.4	399.3	453.3	510.3
CXW-500ASSW*1	428.2	521.8	619.4	722.7	295.1	369.1	446.0	527.0	611.9	700.9	265.8	329.5	396.1	465.6	537.9	614.2	301.4	359.9	421.4	485.6	552.8	623.7	280.1	333.5	388.6	446.6	507.0	570.8
CXW-550ASSW*1	477.9	582.3	691.3	806.6	329.3	411.9	497.8	588.1	682.9	782.2	296.6	367.7	442.0	519.6	600.3	685.5	336.3	401.7	470.2	542.0	616.9	696.1	312.6	372.2	433.7	498.4	565.8	637.1



Wet Bulb Tem.°C	24°C																								25.56°C		
Range°C	4				5						6						7						8				5.56
Approach °C	4	5	6	7	3	4	5	6	7	8	3	4	5	6	7	8	4	5	6	7	8	4	5	6	7	8	3.89
Inlet water tem.°C	32	33	34	35	32	33	34	35	36	37	33	34	35	36	37	38	35	36	37	38	39	36	37	38	39	40	35
Outlet water tem.°C	28	29	30	31	27	28	29	30	31	32	27	28	29	30	31	32	28	29	30	31	32	28	29	30	31	32	29.44
CXW-35ASSW*1	32.2	39.0	46.5	54.3	22.2	27.8	33.5	39.6	45.9	52.7	19.9	24.8	29.7	35.0	40.4	46.2	22.7	27.1	31.7	36.5	41.6	21.0	25.1	29.2	33.6	38.2	27.4
CXW-40ASSW*1	35.9	43.6	52.0	60.6	24.8	31.0	37.5	44.2	51.4	58.9	22.3	27.7	33.2	39.1	45.2	51.6	25.3	30.3	35.4	40.8	46.5	23.5	28.0	32.7	37.6	42.7	30.6
CXW-55ASSW*1	50.1	60.8	72.5	84.6	34.6	43.3	52.3	61.7	71.6	82.1	31.1	38.6	46.4	54.5	63.0	72.0	35.4	42.2	49.4	57.0	64.9	32.8	39.1	45.6	52.4	59.5	42.7
CXW-65ASSW*1	61.5	74.6	89.0	103.7	42.4	53.1	64.1	75.7	87.8	100.7	38.1	47.4	56.9	66.9	77.3	88.3	43.4	51.8	60.6	69.9	79.5	40.2	47.9	55.9	64.2	73.0	52.4
CXW-70ASSW*1	66.2	80.4	95.8	111.7	45.6	57.1	69.0	81.5	94.6	108.4	41.1	51.0	61.2	72.0	83.3	95.1	46.7	55.8	65.3	75.2	85.7	43.3	51.6	60.2	69.2	78.6	56.4
CXW-80ASSW*1	75.7	91.8	109.5	127.7	52.2	65.3	78.9	93.1	108.1	123.9	46.9	58.3	70.0	82.3	95.2	108.7	53.4	63.7	74.6	86.0	97.9	49.5	59.0	68.8	79.1	89.8	64.5
CXW-90ASSW*1	85.1	103.3	123.2	143.6	58.7	73.5	88.8	104.8	121.6	139.4	52.8	65.6	78.7	92.6	107.0	122.3	60.0	71.7	83.9	96.7	110.1	55.7	66.3	77.4	88.9	101.1	72.5
CXW-100ASSW*1	94.6	114.8	136.9	159.6	65.2	81.6	98.6	116.4	135.1	154.9	58.7	72.9	87.5	102.9	118.9	135.9	66.7	79.7	93.2	107.5	122.4	61.9	73.7	86.0	98.8	112.3	80.6
CXW-110ASSW*1	104.1	126.3	150.5	175.5	71.7	89.8	108.5	128.1	148.6	170.4	64.5	80.2	96.2	113.2	130.8	149.5	73.4	87.6	102.5	118.2	134.6	68.1	81.1	94.6	108.7	123.5	88.6
CXW-120ASSW*1	113.5	137.8	164.2	191.5	78.3	98.0	118.3	139.7	162.2	185.9	70.4	87.5	105.0	123.4	142.7	163.1	80.0	95.6	111.9	129.0	146.8	74.3	88.5	103.2	118.6	134.7	96.7
CXW-130ASSW*1	123.0	149.3	177.9	207.5	84.8	106.1	128.2	151.3	175.7	201.4	76.3	94.8	113.7	133.7	154.6	176.6	86.7	103.6	121.2	139.7	159.1	80.4	95.8	111.8	128.5	146.0	104.7
CXW-140ASSW*1	132.4	160.7	191.6	223.4	91.3	114.3	138.1	163.0	189.2	216.9	82.1	102.1	122.5	144.0	166.5	190.2	93.4	111.5	130.5	150.4	171.3	86.6	103.2	120.4	138.3	157.2	112.8
CXW-150ASSW*1	141.9	172.2	205.3	239.4	97.8	122.4	147.9	174.6	202.7	232.4	88.0	109.4	131.2	154.3	178.4	203.8	100.1	119.5	139.8	161.2	183.5	92.8	110.6	129.0	148.2	168.4	120.9
CXW-160ASSW*1	151.4	183.7	219.0	255.3	104.3	130.6	157.8	186.3	216.2	247.8	93.9	116.6	140.0	164.6	190.3	217.4	106.7	127.5	149.2	171.9	195.8	99.0	117.9	137.6	158.1	179.7	128.9
CXW-350ASSW*1	325.4	394.9	470.8	549.0	224.3	280.8	339.3	400.5	464.9	532.9	201.8	250.8	301.0	353.9	409.2	467.4	229.5	274.1	320.7	369.7	420.9	212.9	253.6	295.8	339.9	386.3	277.2
CXW-400ASSW*1	390.7	474.2	565.2	659.1	269.3	337.1	407.3	480.8	558.1	639.7	242.3	301.1	361.3	424.9	491.2	561.2	275.5	329.1	385.0	443.8	505.4	255.6	304.4	355.1	408.1	463.7	332.8



CXW-450ASSW*1	422.9	513.2	611.7	713.4	291.5	364.9	440.8	520.4	604.0	692.4	262.2	325.9	391.1	459.8	531.7	607.4	298.2	356.2	416.7	480.4	547.0	276.6	329.5	384.3	441.7	501.9	360.2
CXW-500ASSW*1	473.0	574.1	684.3	797.9	326.1	408.2	493.1	582.1	675.7	774.5	293.3	364.5	437.4	514.4	594.7	679.4	333.5	398.4	466.1	537.3	611.8	309.4	368.5	429.9	494.1	561.4	402.9
CXW-550ASSW*1	527.9	640.6	763.6	890.5	363.9	455.5	550.3	649.6	754.0	864.4	327.4	406.8	488.2	574.0	663.7	758.2	372.2	444.6	520.2	599.6	682.8	345.3	411.3	479.8	551.4	626.5	449.6



Wet Bulb Tem. °C	26°C																								27°C						
Range °C	4				5					6					7					8					5	6			8		
Approach °C	4	5	6	7	3	4	5	6	7	3	4	5	6	7	4	5	6	7	4	5	6	7	5	4	6	7	4	7			
Inlet water tem. °C	34	35	36	37	34	35	36	37	38	35	36	37	38	39	37	38	39	40	38	39	40	41	37	37	39	40	39	42			
Outlet water tem. °C	30	31	32	33	29	30	31	32	33	29	30	31	32	33	30	31	32	33	30	31	32	33	32	31	33	34	31	34			
CXW-35ASSW*1	35.6	43.3	51.4	60.0	24.6	30.7	37.1	43.8	50.9	22.1	27.4	32.9	38.7	44.8	25.1	30.0	35.1	40.5	23.3	27.8	32.4	37.3	39.0	28.9	40.8	47.2	24.6	39.3			
CXW-40ASSW*1	39.7	48.4	57.5	67.1	27.4	34.3	41.5	49.0	56.8	24.7	30.7	36.8	43.3	50.1	28.1	33.5	39.3	45.2	26.1	31.1	36.2	41.6	43.6	32.3	45.6	52.7	27.5	43.9			
CXW-55ASSW*1	55.4	67.5	80.1	93.5	38.3	47.8	57.9	68.3	79.3	34.4	42.8	51.4	60.4	69.9	39.1	46.8	54.8	63.1	36.4	43.3	50.5	58.1	60.8	45.0	63.6	73.6	38.3	61.2			
CXW-65ASSW*1	68.0	82.8	98.3	114.7	46.9	58.7	71.0	83.8	97.2	42.2	52.5	63.0	74.0	85.7	48.0	57.4	67.2	77.4	44.6	53.1	62.0	71.2	74.6	55.2	78.0	90.2	47.0	75.1			
CXW-70ASSW*1	73.2	89.1	105.8	123.5	50.6	63.2	76.4	90.3	104.7	45.5	56.5	67.8	79.7	92.3	51.7	61.8	72.3	83.3	48.1	57.2	66.7	76.7	80.4	59.5	84.0	97.2	50.6	80.8			
CXW-80ASSW*1	83.7	101.9	121.0	141.2	57.8	72.2	87.3	103.1	119.7	52.0	64.6	77.5	91.1	105.4	59.1	70.6	82.7	95.2	54.9	65.4	76.3	87.7	91.8	68.0	96.0	111.0	57.9	92.4			
CXW-90ASSW*1	94.1	114.6	136.1	158.8	65.0	81.2	98.3	116.0	134.6	58.5	72.6	87.2	102.5	118.6	66.4	79.5	93.0	107.2	61.8	73.5	85.8	98.6	103.3	76.5	108.0	124.9	65.1	103.9			
CXW-100ASSW*1	104.6	127.3	151.2	176.5	72.2	90.2	109.2	128.9	149.6	65.0	80.7	96.9	113.9	131.8	73.8	88.3	103.3	119.1	68.6	81.7	95.3	109.6	114.8	85.0	120.0	138.8	72.3	115.5			
CXW-110ASSW*1	115.1	140.1	166.3	194.1	79.4	99.3	120.1	141.8	164.6	71.5	88.8	106.6	125.3	145.0	81.2	97.1	113.7	131.0	75.5	89.9	104.9	120.5	126.3	93.5	132.0	152.7	79.6	127.0			
CXW-120ASSW*1	125.5	152.8	181.4	211.8	86.7	108.3	131.0	154.7	179.5	78.0	96.9	116.3	136.7	158.2	88.6	105.9	124.0	142.9	82.4	98.1	114.4	131.5	137.8	102.0	144.0	166.6	86.8	138.6			
CXW-130ASSW*1	136.0	165.5	196.6	229.4	93.9	117.3	141.9	167.6	194.5	84.5	104.9	126.0	148.1	171.3	96.0	114.8	134.3	154.8	89.2	106.2	123.9	142.5	149.3	110.4	156.0	180.4	94.0	150.1			
CXW-140ASSW*1	146.4	178.3	211.7	247.0	101.1	126.3	152.9	180.5	209.4	91.0	113.0	135.7	159.4	184.5	103.4	123.6	144.7	166.7	96.1	114.4	133.5	153.4	160.7	118.9	168.0	194.3	101.2	161.7			
CXW-150ASSW*1	156.9	191.0	226.8	264.7	108.3	135.4	163.8	193.4	224.4	97.5	121.1	145.4	170.8	197.7	110.7	132.4	155.0	178.6	103.0	122.6	143.0	164.4	172.2	127.4	180.0	208.2	108.5	173.2			
CXW-160ASSW*1	167.3	203.7	241.9	282.3	115.5	144.4	174.7	206.3	239.4	104.0	129.1	155.0	182.2	210.9	118.1	141.3	165.3	190.5	109.8	130.8	152.5	175.3	183.7	135.9	192.0	222.1	115.7	184.7			
CXW-350ASSW*1	359.8	438.0	520.1	607.0	248.4	310.4	375.6	443.5	514.6	223.5	277.6	333.3	391.8	453.4	254.0	303.7	355.5	409.6	236.1	281.1	327.9	377.0	394.9	292.3	412.7	477.5	248.8	397.2			
CXW-400ASSW*1	432.0	525.9	624.5	728.8	298.3	372.7	450.9	532.5	617.8	268.4	333.3	400.2	470.4	544.3	304.9	364.6	426.8	491.7	283.5	337.5	393.7	452.6	474.2	350.9	495.5	573.3	298.7	476.9			



CXW-450ASSW*1	467.5	569.1	675.9	788.8	322.8	403.4	488.1	576.3	668.7	290.5	360.8	433.1	509.1	589.2	330.0	394.7	461.9	532.2	306.8	365.3	426.1	489.9	513.2	379.8	536.3	620.5	323.3	516.1
CXW-500ASSW*1	523.0	636.6	756.0	882.3	361.1	451.2	545.9	644.7	748.0	324.9	403.6	484.5	569.5	659.0	369.1	441.4	516.6	595.3	343.2	408.6	476.6	547.9	574.1	424.8	599.9	694.0	361.6	577.3
CXW-550ASSW*1	583.6	710.5	843.7	984.7	403.0	503.5	609.3	719.4	834.8	362.6	450.4	540.7	635.5	735.5	411.9	492.7	576.6	664.3	383.0	456.0	531.9	611.5	640.6	474.1	669.5	774.5	403.5	644.3



Wet Bulb Tem.°C	28°C																					
Range°C	4				5					6					7				8			
Approach °C	4	5	6	7	3	4	5	6	7	3	4	5	6	7	4	5	6	7	4	5	6	7
Inlet water tem.°C	36	37	38	39	36	37	38	39	40	37	38	39	40	41	39	40	41	42	40	41	42	43
Outlet water tem.°C	32	33	34	35	31	32	33	34	35	31	32	33	34	35	32	33	34	35	32	33	34	35
CXW-35ASSW*1	39.4	47.9	57.0	66.4	27.2	34.0	41.1	48.6	56.4	24.5	30.4	36.6	43.0	49.7	27.9	33.3	39.0	44.9	25.9	30.9	36.0	41.4
CXW-40ASSW*1	44.0	53.6	63.7	74.3	30.4	38.0	45.9	54.3	63.0	27.4	34.0	40.9	48.0	55.5	31.2	37.2	43.6	50.2	29.0	34.5	40.2	46.3
CXW-55ASSW*1	61.4	74.7	88.8	103.6	42.4	53.0	64.1	75.7	87.9	38.2	47.4	57.0	67.0	77.5	43.4	51.9	60.8	70.0	40.4	48.1	56.1	64.5
CXW-65ASSW*1	75.3	91.6	108.9	127.0	52.0	65.0	78.6	92.8	107.8	46.9	58.1	69.9	82.2	95.0	53.3	63.7	74.6	85.9	49.5	59.0	68.8	79.1
CXW-70ASSW*1	81.1	98.7	117.3	136.8	56.0	70.0	84.6	100.0	116.1	50.5	62.6	75.3	88.5	102.3	57.4	68.6	80.3	92.5	53.4	63.5	74.1	85.2
CXW-80ASSW*1	92.7	112.8	134.0	156.3	64.0	80.0	96.7	114.3	132.6	57.7	71.5	86.1	101.1	116.9	65.6	78.3	91.8	105.7	61.0	72.6	84.7	97.4
CXW-90ASSW*1	104.3	126.9	150.8	175.9	72.0	90.0	108.8	128.5	149.2	64.9	80.5	96.8	113.8	131.5	73.8	88.1	103.2	118.9	68.6	81.7	95.3	109.5
CXW-100ASSW*1	115.8	141.0	167.5	195.4	80.0	100.0	120.9	142.8	165.8	72.1	89.4	107.6	126.4	146.2	82.0	97.9	114.7	132.1	76.2	90.7	105.9	121.7
CXW-110ASSW*1	127.4	155.1	184.3	214.9	88.0	110.0	133.0	157.1	182.4	79.3	98.4	118.3	139.0	160.8	90.2	107.7	126.2	145.4	83.8	99.8	116.5	133.9
CXW-120ASSW*1	139.0	169.2	201.0	234.5	96.0	120.0	145.1	171.4	198.9	86.5	107.3	129.1	151.7	175.4	98.4	117.5	137.6	158.6	91.5	108.9	127.0	146.1
CXW-130ASSW*1	150.6	183.3	217.8	254.0	104.0	130.0	157.2	185.7	215.5	93.7	116.3	139.9	164.3	190.0	106.6	127.3	149.1	171.8	99.1	118.0	137.6	158.2
CXW-140ASSW*1	162.2	197.4	234.5	273.6	112.0	140.0	169.3	200.0	232.1	100.9	125.2	150.6	177.0	204.6	114.8	137.1	160.6	185.0	106.7	127.0	148.2	170.4
CXW-150ASSW*1	173.8	211.5	251.3	293.1	120.0	150.0	181.3	214.2	248.7	108.2	134.2	161.4	189.6	219.2	123.0	146.9	172.0	198.2	114.3	136.1	158.8	182.6
CXW-160ASSW*1	185.4	225.6	268.0	312.7	128.0	160.0	193.4	228.5	265.3	115.4	143.1	172.1	202.3	233.8	131.2	156.7	183.5	211.4	122.0	145.2	169.4	194.7
CXW-350ASSW*1	398.5	485.0	576.2	672.2	275.3	344.0	415.9	491.3	570.3	248.0	307.7	370.1	434.8	502.8	282.0	336.9	394.6	454.6	262.2	312.2	364.2	418.7
CXW-400ASSW*1	478.4	582.3	691.8	807.0	330.5	413.0	499.3	589.9	684.7	297.8	369.4	444.3	522.1	603.6	338.6	404.5	473.7	545.8	314.8	374.8	437.2	502.7



CXW-450ASSW*1	517.8	630.2	748.8	873.5	357.7	447.0	540.4	638.4	741.1	322.3	399.8	480.9	565.0	653.3	366.4	437.8	512.7	590.7	340.7	405.6	473.2	544.0
CXW-500ASSW*1	579.2	704.9	837.5	977.0	400.1	500.0	604.5	714.1	828.9	360.5	447.2	537.9	632.0	730.8	409.9	489.7	573.5	660.7	381.1	453.7	529.3	608.6
CXW-550ASSW*1	646.4	786.7	934.7	1090.4	446.5	558.0	674.6	797.0	925.1	402.3	499.1	600.3	705.3	815.5	457.4	546.5	640.0	737.4	425.3	506.4	590.7	679.1





Wet Bulb Tem. °C	29°C					32°C				
Range °C	6			8		6			8	
Approach °C	4	6	7	4	7	4	6	7	4	7
Inlet water tem. °C	39	41	42	41	44	42	44	45	44	47
Outlet water tem. °C	33	35	36	33	36	36	38	39	36	39
CXW-35ASSW*1	32.1	45.3	52.4	27.3	43.6	37.6	53.1	61.4	32.1	51.3
CXW-40ASSW*1	35.9	50.6	58.5	30.5	48.8	42.0	59.3	68.6	35.9	57.3
CXW-55ASSW*1	50.0	70.6	81.7	42.6	68.0	58.6	82.8	95.7	50.0	79.9
CXW-65ASSW*1	61.3	86.6	100.1	52.2	83.4	71.9	101.5	117.4	61.4	98.0
CXW-70ASSW*1	66.1	93.2	107.9	56.3	89.8	77.4	109.3	126.5	66.1	105.6
CXW-80ASSW*1	75.5	106.5	123.3	64.3	102.7	88.5	124.9	144.5	75.5	120.6
CXW-90ASSW*1	84.9	119.9	138.7	72.3	115.5	99.5	140.5	162.6	85.0	135.7
CXW-100ASSW*1	94.4	133.2	154.1	80.4	128.3	110.6	156.1	180.6	94.4	150.8
CXW-110ASSW*1	103.8	146.5	169.5	88.4	141.2	121.6	171.8	198.7	103.8	165.9
CXW-120ASSW*1	113.2	159.8	184.9	96.4	154.0	132.7	187.4	216.8	113.3	181.0
CXW-130ASSW*1	122.7	173.1	200.3	104.5	166.8	143.7	203.0	234.8	122.7	196.0
CXW-140ASSW*1	132.1	186.5	215.7	112.5	179.7	154.8	218.6	252.9	132.2	211.1
CXW-150ASSW*1	141.6	199.8	231.1	120.6	192.5	165.8	234.2	271.0	141.6	226.2
CXW-160ASSW*1	151.0	213.1	246.5	128.6	205.3	176.9	249.8	289.0	151.1	241.3
CXW-350ASSW*1	324.6	458.1	530.0	276.5	441.5	380.3	537.1	621.4	324.8	518.8
CXW-400ASSW*1	389.8	550.0	636.3	331.9	530.0	456.6	644.9	746.1	389.9	622.8



CXW-450ASSW*1	421.9	595.3	688.7	359.2	573.7	494.2	698.0	807.5	422.0	674.1
CXW-500ASSW*1	471.9	665.9	770.4	401.8	641.7	552.8	780.7	903.2	472.0	754.0
CXW-550ASSW*1	526.6	743.1	859.7	448.5	716.1	616.9	871.3	1008.0	526.8	841.5