

Zhejiang Dongjie DMNC Ratings Data (R0)

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	7	8	6	6	6	7	8	6	6	6	7	8	6	6	6	7	8	6	6	6	7	8
Approach °C	4	6	7	8	6	4	6	7	8	6	4	6	7	8	6	4	6	7	8	6	4	6	7	8	6
Inlet Process Temperature °C	20	22	23	25	24	23	25	26	28	27	26	28	29	31	30	28	30	31	33	32	31	33	34	36	35
Outlet Process Temperature °C	14	16	17	18	16	17	19	20	21	19	20	22	23	24	22	22	24	25	26	24	25	27	28	29	27
Process Fluid Type	Water																								
DMNC-36/12-25 in l/s	3.17	4.44	5.17	5.25	3.69	3.59	5.07	5.86	6.06	4.21	4.12	5.82	6.74	7.03	4.86	4.53	6.51	7.57	7.78	5.38	5.29	7.58	8.82	9.08	6.28
DMNC-42/12-28 in l/s	4.16	5.83	6.78	6.89	4.85	4.72	6.66	7.69	7.95	5.52	5.40	7.65	8.84	9.23	6.38	5.94	8.55	9.93	10.22	7.06	6.94	9.95	11.57	11.92	8.24
DMNC-48/12-32 in l/s	5.46	7.67	8.91	9.06	6.37	6.20	8.75	10.11	10.45	7.26	7.10	10.05	11.62	12.13	8.39	7.81	11.24	13.05	13.43	9.28	9.12	13.07	15.21	15.66	10.83
DMNC-54/12-36 in l/s	6.95	9.75	11.33	11.52	8.10	7.89	11.12	12.85	13.29	9.23	9.03	12.78	14.78	15.43	10.66	9.93	14.29	16.60	17.08	11.80	11.60	16.62	19.34	19.92	13.77
DMNC-60/12-40 in l/s	8.61	12.08	14.05	14.27	10.04	9.77	13.79	15.93	16.47	11.44	11.19	15.84	18.31	19.12	13.22	12.30	17.71	20.57	21.16	14.63	14.37	20.60	23.97	24.68	17.07
DMNC-76/10-44 in l/s	10.03	14.08	16.37	16.64	11.71	11.39	16.07	18.57	19.19	13.33	13.05	18.46	21.34	22.29	15.40	14.34	20.64	23.98	24.67	17.05	16.75	24.01	27.94	28.77	19.90

Zhejiang Dongjie DMNC Ratings Data (R0)

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	24	24	27	27	27	27	27	29	29	29	29	29	32.2	32.2	32.2	32.2	32.2	21	25.56	27	28
Range °C	6	6	6	7	8	6	6	6	7	8	6	6	6	7	8	6	6	6	7	8	5	6.67	5	5
Approach °C	4	6	7	8	6	4	6	7	8	6	4	6	7	8	6	4	6	7	8	6	6	6.67	5	4
Inlet Process Temperature °C	34	36	37	39	38	37	39	40	42	41	39	41	42	44	43	42.2	44.2	45.2	47.2	46.2	32	38.90	37	37
Outlet Process Temperature °C	28	30	31	32	30	31	33	34	35	33	33	35	36	37	35	36.2	38.2	39.2	40.2	38.2	27	32.23	32	32
Process Fluid Type																								
DMNC-36/12-25 in l/s	6.18	8.86	10.30	10.61	7.34	7.24	10.38	11.75	12.12	8.55	8.07	11.23	13.07	13.58	9.44	9.42	13.36	15.42	15.92	11.25	8.64	10.00	10.14	8.89
DMNC-42/12-28 in l/s	8.10	11.64	13.52	13.92	9.64	9.51	13.62	15.43	15.90	11.23	10.59	14.74	17.15	17.82	12.39	12.36	17.54	20.23	20.89	14.77	11.34	13.13	13.31	11.67
DMNC-48/12-32 in l/s	10.65	15.29	17.77	18.30	12.67	12.50	17.90	20.28	20.90	14.75	13.92	19.37	22.55	23.43	16.28	16.24	23.05	26.59	27.46	19.41	14.91	17.25	17.50	15.33
DMNC-54/12-36 in l/s	13.55	19.45	22.60	23.27	16.11	15.89	22.77	25.78	26.58	18.76	17.71	24.63	28.67	29.79	20.70	20.66	29.31	33.82	34.92	24.68	18.96	21.94	22.25	19.50
DMNC-60/12-40 in l/s	16.79	24.10	28.01	28.84	19.97	19.70	28.22	31.96	32.94	23.25	21.95	30.53	35.53	36.92	25.66	25.60	36.33	41.91	43.27	30.59	23.49	27.19	27.58	24.17
DMNC-76/10-44 in l/s	19.57	28.09	32.65	33.61	23.27	22.96	32.89	37.24	38.40	27.10	25.58	35.58	41.42	43.03	29.90	29.84	42.34	48.85	50.44	35.65	27.38	31.69	32.14	28.17